RADAR™



VISIT USGME.COM TO ORDER SAMPLES



FEATURES & BENEFITS

- Balanced Acoustics. High-NRC and High-CAC provides balance to room acoustics and sound attenuation; ideal for general commercial construction.
- Excellent combination of noise reduction (up to NRC-0.80) and sound attenuation (up to CAC-40).
- 360° non-directional pattern with a fresh, clean appearance that allows for fast, efficient installation.
- Cost-effective all-purpose ceiling pattern solution offered in many sizes and edge details.
- Fire resistant system options for life safety and protection of property.
- Available in HRC (High Recycled Content) for optimized recycled content formulations to help maximize LEED® recycled content contribution and sound absorption.
- Available in 22mm for High NRC & High CAC panels.
- Also available in washable paint and various plank sizes.

APPLICATIONS

- Education
- Corridors
- Cafeterias
- Libraries
- Open office plans
- Retail stores
- Basement

Absorption Coefficient

Frequency, Hz	125	250	500	1000	2000	4000	NRC*
12mm	0.30	**0.30**	**0.40**	**0.55**	**0.75**	0.85	**0.50**
15mm	0.40	**0.35**	**0.45**	**0.60**	**0.70**	0.70	**0.50**
19mm	0.30	**0.35**	**0.55**	**0.75**	**0.75**	0.65	**0.60**
19mm HNRC	0.25	**0.35**	**0.65**	**0.85**	**0.90**	0.90	**0.70**
22mm	0.35	**0.50**	**0.75**	**0.95**	**1.0**	0.90	**0.80**

* *Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.



RADAR™

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS

HIGH SOUND ABSORPTION

CEILING ATTENUATION CLASS

FIRECODE

HIGH RECYCLED CONTENT

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC					<	$
SQ	RDS662 RDS222	600*600*12 610*610*12	0.50	35	85%			25%	Low	$
	RDS665 RDS225	600*600*15 610*610*15	0.50	36	85%			25%	Low	$
	RDC665 RDC225	600*600*15 610*610*15	0.50	36	85%	●		39%	Low	$
	RDX665 RDX225	600*600*15 610*610*15	0.50	37	85%		●	56%	Low	$$
	RDX625 RDX245	600*1200*15 610*1220*15	0.50	37	85%		●	56%	Low	$$
	RDX669 RDX229	600*600*19 610*610*19	0.60	40	85%		●	56%	Low	$$
	RDC325 RDC145	300*1200*15 310*1220*15	0.50	36	85%	●		39%	Low	$$
	RDS669 RDS229	600*600*19 610*610*19	0.60	38	85%			25%	Low	$$
	RDC669-HNRC RDC229-HNRC	600*600*19 610*610*19	0.70	40	85%	●		82%	Low	$$$
	RDC329 RDC149	300*1200*19 310*1220*19	0.60	40	85%	●		39%	Low	$$$
	RDC669 RDC229	600*600*19 610*610*19	0.60	40	85%	●		39%	Low	$$$
	RDC6622 RDC2222	600*600*22 610*610*22	0.80	39	85%	●		39%	Low	$$$$
SLT	RDSR665 RDSR225	600*600*15 610*610*15	0.50	36	85%			25%	Low	$
	RDCR665 RDCR225	600*600*15 610*610*15	0.50	36	85%	●		39%	Low	$
	RDXR669 RDXR229	600*600*19 610*610*19	0.60	40	85%		●	56%	Low	$$
	RDCR325 RDCR145	300*1200*15 310*1220*15	0.50	36	85%	●		39%	Low	$$
	RDSR669 RDSR229	600*600*19 610*610*19	0.60	38	85%			25%	Low	$$
	RDCR669-HNRC RDCR229-HNRC	600*600*19 610*610*19	0.70	40	85%	●		82%	Low	$$$
	RDCR329 RDCR149	300*1200*19 310*1220*19	0.60	40	85%	●		39%	Low	$$$
	RDCR669 RDCR229	600*600*19 610*610*19	0.60	40	85%	●		39%	Low	$$$
	RDCR6622 RDCR2222	600*600*22 610*610*22	0.80	39	85%	●		39%	Low	$$$$
FLB	RDSRF665 RDSRF225	600*600*15 610*610*15	0.50	36	85%			25%	Low	$
	RDCRF665 RDCRF225	600*600*15 610*610*15	0.50	36	85%	●		39%	Low	$
	RDCRF325 RDCRF145	300*1200*15 310*1220*15	0.50	36	85%	●		39%	Low	$$
	RDCRF329 RDCRF149	300*1200*19 310*1220*19	0.60	40	85%	●		39%	Low	$$$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. UL. Tests are available on usgme.com and at spot.ul.com

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

RADAR™

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR ENVIRONMENTAL PRODUCT DECLARATION

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS






HIGH SOUND ABSORPTION

CEILING ATTENUATION CLASS

FIRECODE

HIGH RECYCLED CONTENT

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DX/DXL SLT Edge	DXT FLB Edge	DXF FLB Edge
				

SPECIFICATION DETAILS

Radar™ Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

Materials Classification
Type: III,
Form: 2,
Pattern: C,D, E

Substrate and Surface Finish
Mineral fiber substrate finished with factory-applied water-based paint

Thickness
12mm, 15mm, 19mm, 22mm

Size
300 x 1200mm, 310 x 1220mm, 600 x 600mm, 610 x 610mm, 600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Square, Reveal [SLT, FLB]

Weight
12mm [2.85 kg/m², Regular/ ClimaPlus™], 15mm [3.6 kg/m², Regular/ ClimaPlus™], 15mm [5.1 kg/m², Firecode®], 19mm [4.5 kg/m², Regular/ ClimaPlus™], 19mm [6.45 kg/m², Firecode®], 22mm [5.25 kg/m², Regular/ ClimaPlus™

Noise Reduction Coefficient [NRC]
[0.50] [0.60] [0.70] [0.80]

Ceiling Attenuation Class [CAC]
[35 - 40 dB]

Humidity Resistance
Maximum 99% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.85

Color
White similar to RAL 9016

Surface Burning Characteristics as per ASTM E84
Class A

Reaction to Fire as per EN 13501-1
Euroclass A2-s1, d0

Fire Rating as per ASTM E119
2hrs Time-Rated Assembly [J201]

Thermal Conductivity
λ = 0.057 W/m°K

VOC Class
Greenguard Gold

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

Formaldehyde Classification
Class E1 as per EN717-1

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co. All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma