TAIGA HYGIENE



VISIT USGME.COM TO ORDER SAMPLES

FEATURES & BENEFITS

- Taiga Hygiene in normal condition face and back is ISO 4 according to the norm ISO 14644-1 : 2015.
- All Taiga Hygiene items have a special fungicide treatment in the core and on the finished painted surface to enhance resistance to growth of micro-organisms and ensure regular cleanability. Contains a broad spectrum of antimicrobial additives on the face and back of the panel, which provides resistance against the growth of mold and mildew.
- The microbiological class according to the norm NF S 90-351 : 2013 is as following: M100 / area 2 (Klebsiella pneumoniae), M1 / area 4 (Acinobacter baumannii, Staphylococcus aureus MRSA, Bacillus cereus, Streptococcus pneumoniae, Escherichia coli, Candida albicans), <1 / area 2,3,4 (Aspergillus brasiliensis).
- Taiga Hygiene has been developed to meet the most stringent standards for hygiene and cleanability.
- High light reflectance performance 86%.
- High humidity resistant in ClimaPlus™, suitable for applications with intermittent heating and cooling.

APPLICATIONS AS PER 2018 FGI GUIDELINES

- Class 1 MRI and imaging rooms
- Laboratories
- Nurse's stations
- Patient rooms
- Pharmacies

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

TAIGA HYGIENE

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS

CEILING ATTENUATION CLASS





HEALTHCARE APPLICATION

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC					<	$
SQ	THS665 THS225	600*600*15 610*610*15	0.15	33	86%			25%	Low	$$
	THS669 THS229	600*600*19 610*610*19	0.15	36	86%			25%	Low	$$$
SLT	THSR665 THSR225	600*600*15 610*610*15	0.15	33	86%			25%	Low	$$
	THSR669 THSR229	600*600*19 610*610*19	0.15	36	86%			25%	Low	$$$
FLB	THSRF669 THSRF229	600*600*19 610*610*19	0.15	36	86%			25%	Low	$$$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. UL. Tests are available on usgme.com and at spot.ul.com

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DX/DXL SLT Edge	DXT FLB Edge
			

SPECIFICATION DETAILS

Taiga Hygiene Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

Materials Classification
Type: III,
Form: 2,
Pattern: G

Substrate and Surface Finish
Mineral fiber substrate finished with factory-applied water-based paint

Thickness
15mm, 19mm

Size
600 x 600mm, 610 x 610mm

Edge Detail Trim
Square, Reveal [SLT, FLB]

Weight
15mm [3.6 kg/m² Regular/ ClimaPlus™],
19mm [4.5 kg/m² Regular/ ClimaPlus™]

Noise Reduction Coefficient [NRC]
[0.15]

Ceiling Attenuation Class [CAC]
[33 - 36 dB]

Clean Room Classification as per ISO 14644-1
ISO 4

Mold Prevention Application as per ASTM D3273
Rate 10

Humidity Resistance
Maximum 99% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.86

Color
White similar to RAL 9016

Surface Burning Characteristics as per ASTM E84
Class A

Reaction to Fire as per EN 13501-1
Euroclass A2-s1, d0

Thermal Conductivity
λ = 0.057 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

VOC Class
Greenguard Gold

Formaldehyde Classification
Class E1 as per EN717-1

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma