CEILINGS

OMNI



VISIT USGME.COM TO ORDER SAMPLES



FEATURES & BENEFITS

- Medium-textured panels feature a unique, non-directional pattern with a fresh, clean appearance that allows for fast, efficient installation.
- Mid-range sound absorption and sound attenuation, which make it ideal for general commercial stores.
- Is a cost-effective solution with a wide variety of panel options for various applications.
- Optional Firecode™ formulation designed to meet life safety codes.
- Available in washable paint for easy maintenance (use soft brush or vacuum to clean surface).

APPLICATIONS

- Stores
- Corridors and hallways
- Warehouses
- Mechanical rooms
- Stairways and elevator shafts
- Basement

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

OMNI

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS

CEILING ATTENUATION CLASS

FIRECODE

HIGH RECYCLED CONTENT




TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	NRC	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			NRC	CAC					<	$
SQ	OMS665 OMS225	600*600*15 610*610*15	0.50	35	82%			25%	Low	$
	OMC625 OMC245	600*1200*15 610*1220*15	0.50	35	82%	●		39%	Low	$
	OMX665 OMX225	600*600*15 610*610*15	0.50	35	82%		●	56%	Low	$$
	OMS669 OMS229	600*600*19 610*610*19	0.60	37	82%			25%	Low	$$
	OMX669 OMX229	600*600*19 610*610*19	0.60	37	82%		●	56%	Low	$$
SLT	OMSR665 OMSR225	600*600*15 610*610*15	0.50	35	82%			25%	Low	$$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. UL. Tests are available on usgme.com and at spot.ul.com

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.
For firechief products.

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge	DX/DXL SLT Edge
		

SPECIFICATION DETAILS

Omni Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

Materials Classification
Type: III,
Form: 2,
Pattern: C, D, E

Substrate and Surface Finish
Mineral fiber substrate finished with factory-applied water-based paint

Thickness
15mm, 19mm

Size
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm

Edge Detail Trim
Square, Reveal [SLT]

Weight
15mm [3.6 kg/m², Regular/ ClimaPlus™]
15mm [5.1 kg/m², Firecode®]
19mm [4.5 kg/m², Regular/ ClimaPlus™]
19mm [6.45 kg/m², Firecode®]

Noise Reduction Coefficient [NRC]
[0.50], [0.60]

Ceiling Attenuation Class [CAC]
[35 - 37 dB]

Humidity Resistance
Maximum 95% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.82

Color
White similar to RAL 9016

Surface Burning Characteristics as per ASTM E84
Class A

Reaction to Fire as per EN 13501-1
Euroclass A2-s1, d0

Fire Rating as per ASTM E119
2hrs Time-Rated Assembly [J201]

Thermal Conductivity
λ = 0.057 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

VOC Class
Greenguard Gold

Formaldehyde Classification
Class E1 as per EN717-1

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

LADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma