# AURATONE DESIGNER SERIES




VISIT USGME.COM TO ORDER SAMPLES

## FEATURES & BENEFITS

- Shallow geometric square face masks the grid for a uniform look to make it appear as part of the overall ceiling design.
- 360° non-directional pattern with a fresh, clean appearance offers fast, cost-effective installation
- Face scores create illusion of a smaller-scaled ceiling system.
- Available in 4 different face styles ranging from smooth to textured.
- Low to mid-range sound attenuation. Ideal for general commercial construction.
- Fire resistant system options for life safety & protection of property.
- Easy to trim and install.

## APPLICATIONS

- Reception
- Shopping centers
- Waiting rooms
- Cafe and restaurants
- General offices
- Luxury retail stores

Absorption Coefficient

| Frequency, Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 | NRC* |
|---|---|---|---|---|---|---|---|
| 19mm QCFSR | 0.45 | **0.40** | **0.50** | **0.70** | **0.70** | 0.60 | **0.60** |
| 19mm QTPSR | 0.35 | **0.40** | **0.65** | **0.85** | **0.85** | 0.70 | **0.70** |
| 19mm QOLPCR | 0.30 | **0.45** | **0.70** | **0.70** | **0.70** | 0.60 | **0.65** |
| 19mm QRDSR | 0.35 | **0.40** | **0.50** | **0.65** | **0.80** | 0.90 | **0.60** |

* *Calculated to ASTM C 423-01*

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

# AURATONE DESIGNER SERIES

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS

HIGH SOUND ABSORPTION

CEILING ATTENUATION CLASS


## TABLE OF PERFORMANCE

| Edge Detail | Item | Size (mm) | NRC | CAC | Light Reflectance | Anti-Mold & Mildew/ Sag Resistance | Fire Rating | Recycled Content | VOC Emission | Cost |
|---|---|---|---|---|---|---|---|---|---|---|
| | | | NRC | CAC | | | | | < | $ |
| SLT  | QCFSR669<br>QCFSR229 | 600*600*19<br>610*610*19 | 0.60 | 35 | 82% | | | 25% | Low | $$$ |
| | QTPSR669<br>QTPSR229 | 600*600*19<br>610*610*19 | 0.70 | 35 | 84% | | | 25% | Low | $$$ |
| | QTCR669<br>QTCR229 | 600*600*19<br>610*610*19 | 0.15 | 35 | 84% | ● | | 32% | Low | $$$$ |
| | QTCR669 (36/15)<br>QTCR229 (36/15) | 600*600*19<br>610*610*19 | 0.15 | 37 | 84% | ● | | 32% | Low | $$$$ |
| | QOLPCR669<br>QOLPCR229 | 600*600*19<br>610*610*19 | 0.65 | 37 | 85% | ● | | 32% | Low | $$$$ |
| | QRDSR669<br>QRDSR229 | 600*600*19<br>610*610*19 | 0.60 | 35 | 83% | | | 32% | Low | $$$ |
| | QRDCR669<br>QRDCR229 | 600*600*19<br>610*610*19 | 0.60 | 35 | 83% | ● | | 32% | Low | $$$$ |

**Low Emissions (VOC)**
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health (CDPH) Standard Method V1.2-2017 using a Classroom Environment. Product tested in accordance with UL 2821 test method to show compliance to emission limits on UL 2818. Section 7.1 and 7.2. UL. Tests are available on usgme.com and at spot.ul.com

## GRID PROFILE OPTIONS

**DX/DXL**
**SLT Edge**



## SPECIFICATION DETAILS

Auratone Designer Series Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

**Materials Classification**
Type: III,
Form: 2,
Pattern: C, D, E, G, K

**Substrate and Surface Finish**
Mineral fiber substrate finished with factory-applied water-based paint

**Thickness**
19mm

**Size**
600 x 600mm, 610 x 610mm

**Edge Detail Trim**
Reveal [SLT]

**Weight**
19mm [4.5 kg/m, Regular/ ClimaPlus™]

**Noise Reduction Coefficient [NRC]**
[0.15] [0.60] [0.65] [0.70]

**Ceiling Attenuation Class [CAC]**
[35 - 37 dB]

**Mold Prevention Application as per ASTM D3273**
Application available upon request per ASTM D3273-1, Rate 10 per D3274

**Humidity Resistance**
Maximum 90% RH / 30°C for ClimaPlus™

**Light Reflectance Coefficient [LR]**
[0.83 – 0.85]

**Color**
White similar to RAL 9016

**Surface Burning Characteristics as per ASTM E84**
Class A

**Reaction to Fire as per EN 13501-1**
Euroclass A2-s1, d0

**Thermal Conductivity**
λ = 0.057 W/m°K

**Washability / Scrubbability as per ASTM D4828 & D2486**
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion upon request

**VOC Class**
Greenguard Gold

**Formaldehyde Classification**
Class E1 as per EN717-1

**Relevant LEED® Credit**
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

**Notice:**
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma