CEILINGS

SPARTA



VISIT USGME.COM TO ORDER SAMPLES

FEATURES & BENEFITS

- Laminated washable vinyl facing ceiling tile for easy maintenance.
- Available only in plain facings with smooth appearance.
- Ultra high humidity resistant; sag resistance ensures durability in standard or extreme environmental conditions.
- May be installed in early project stages.
- Standard with aluminum foil at the rear side which acts as a vapor barrier and resists breathing so panel stays clean for a long time
- Scrub resistant, dirt marks are easy to remove.
- Suitable for Healthcare applications.
- Economical and easy to trim and install.

APPLICATIONS AS PER 2018 FGI GUIDELINES

- Hydro-therapy rooms
- Nurse's stations
- Patient rooms
- Kitchen
- Groceries
- Bathroom

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

SPARTA

EN 13964 : 2014 + A1 : 2007

PRODUCT CERTIFIED FOR LOW VOC EMISSIONS

CEILING ATTENUATION CLASS



HEALTHCARE APPLICATION

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	CAC	Light Reflectance	Anti-Mold & Mildew/ Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
			CAC					<	$
SQ	LPW665 LPW225	600*600*15 610*610*15	35	84%			20%	Low	$
	LPW669 LPW229	600*600*19 610*610*19	36	84%			20%	Low	$$

Low Emissions (VOC)
Third party (GREENGUARD Gold) certified for low-emitting performance, meets California Department of Public Health's (CDPH) Standard Method v1.1 - 2010 (CA Section 01350). 'Certificates of Compliance' for Low VOC Emissions are available on usg.com and at spot.ul.com.

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DXT SQ Edge
	

SPECIFICATION DETAILS

Sparta Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

Materials Classification
Type: X,
Pattern: G

Substrate and Surface Finish
Mineral fiber substrates laminated with embossed vinyl-faced membrane and aluminium foil layer at the rear side

Thickness
15mm, 19mm

Size
600 x 600mm, 610 x 610mm

Edge Detail Trim
Square

Weight
15mm [3.75 kg/m^2, Regular/ ClimaPlus™]
19mm [4.75 kg/m^2, Regular/ ClimaPlus™]

Ceiling Attenuation Class [CAC]
[35 - 36 dB]

Mold Prevention Application as per ASTM D3273
Inherent to Mold/Mildew growth

Humidity Resistance
Maximum 99% RH / 40°C for ClimaPlus™

Light Reflectance Coefficient [LR]
0.84

Color
White similar to RAL 9003

Surface Burning Characteristics as per ASTM E84
Class A

Thermal Conductivity
λ = 0.057 W/m°K

Washability / Scrubbability as per ASTM D4828 & D2486
Exceeds 1000 Wash/Scrub cycles without surface break or the extent of abrasion

VOC Class
Greenguard Gold

Formaldehyde Classification
Class E1 as per EN717-1

Relevant LEED® Credit
EA Credit 1 | MR Credit 4 | MR Credit 5| MR Credit 6 IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma