# SKYLITE ACOUSTIC



VISIT USGME.COM TO ORDER SAMPLES



## FEATURES & BENEFITS

- Special R6 wetfleted perforated design meets the growing demand for high sound control ceiling panels with a modern and stylish look.
- Balanced Acoustics. High-NRC and High-CAC.
- Excellent combination of noise reduction (up to NRC-0.70) and sound attenuation (up to CAC-39).
- Excellent for critical lighting applications that require High Light Reflectance (0.89).
- High Humidity Resistance up to RH-95%.
- Produced in HRC (High Recycled Content) for optimized recycled content formulations to help maximize LEED® recycled content contribution and high sound absorption.
- Ideal solutions for educational facilities and offices.

## APPLICATIONS

- Classrooms
- Offices
- Reception and lobby areas
- Restaurant and cafe
- Sports hall
- Shopping centers

Absorption Coefficient

| Frequency, Hz | 125 | 250 | 500 | 1000 | 2000 | 4000 | NRC* |
|---|---|---|---|---|---|---|---|
| 19mm | 0.30 | **0.35** | **0.65** | **0.90** | **0.95** | 0.70 | **0.70** |

*Calculated to ASTM C 423-01



USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

# SKYLITE ACOUSTIC

EN 13964 : 2014 + A1 : 2007






HIGH SOUND ABSORPTION | CEILING ATTENUATION CLASS | FIRECODE | HIGH RECYCLED CONTENT

## TABLE OF PERFORMANCE

| Edge Detail | Item | Size (mm) | NRC | CAC | Light Reflectance | Anti-Mold /Mildew & Sag Resistance | Fire Rating* | Recycled Content | VOC Emission | Cost |
|---|---|---|---|---|---|---|---|---|---|---|
| SQ | SKA669-R6<br>SKA229-R6 | 600*600*19<br>610*610*19 | 0.70 | 39 | 89% | | | 83% | Low | $$$$ |
| | SKA629-R6<br>SKA249-R6 | 600*1200*19<br>610*1220*19 | 0.70 | 39 | 89% | | | 83% | Low | $$$$ |
| SL | SKAR669-R6<br>SKAR229-R6 | 600*600*19<br>610*610*19 | 0.70 | 39 | 89% | | | 83% | Low | $$$$ |
| | SKAR629-R6<br>SKAR249-R6 | 600*1200*19<br>610*1220*19 | 0.70 | 39 | 89% | | | 83% | Low | $$$$ |
| FL | SKARF669-R6<br>SKARF229-R6 | 600*600*19<br>610*610*19 | 0.70 | 39 | 89% | | | 83% | Low | $$$$ |
| | SKARF629-R6<br>SKARF249-R6 | 600*1200*19<br>610*1220*19 | 0.70 | 39 | 89% | | | 83% | Low | $$$$ |

**High Recycled Content**
Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of postconsumer and preconsumer (postindustrial) recycled content per FTC guidelines.

## GRID PROFILE OPTIONS

| DX/DXL SQ Edge | DXT SQ Edge | DX/DXL SLT Edge | DXT FLB Edge | DXF FLB Edge |
|---|---|---|---|---|
|  |  |  |  |  |

## SPECIFICATION DETAILS

Skylite Acoustic Acoustical Ceiling meets specifications in accordance with ASTM E1264 and EN13964.

**Materials Classification**
Type: III,
Form: 2,
Pattern: A

**Substrate and Surface Finish**
Mineral fiber substrate finished with factory-applied water-based paint

**Thickness**
19mm

**Size**
600 x 600mm, 610 x 610mm,
600 x 1200mm, 610 x 1220mm

** Higher acoustic value can be achieved with additional fiber glass/stone wool backer panel*

**Edge Detail Trim**
Square, Reveal [SL, FL]

**Weight**
7 kg/m² [Firecode®]

**Noise Reduction Coefficient [NRC]**
[0.70]*

**Ceiling Attenuation Class [CAC]**
[39 dB]

**Humidity Resistance**
Maximum 95% RH

**Light Reflectance Coefficient [LR]**
0.89

**Color**
White similar to RAL 9016

**Surface Burning Characteristics as per ASTM E84**
Class A

**Reaction to Fire as per EN 13501-1**
Euroclass A2-s1, d0

**Fire Rating as per ASTM E119**
2hrs Time-Rated Assembly [J201]

**Thermal Conductivity**
λ = 0.05 W/m°K

**Formaldehyde Classification**
Class E1 as per EN717-1

**Relevant LEED® Credit**
EA Credit 1 | MR Credit 4 | MR Credit 5 | MR Credit 6 | IEQ Credit 3 | IEQ Credit 3.2 | IEQ Credit 4.6 | IEQ Credit 8.1 | IEQ Credit 9

**Notice:**
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

PLADIS - Complexe Futuris Logistic Lotissement Ennouala Lot N°2 Dépôt A3 Boulevard My Ismaïl- Casablanca
Tel: (212) 5 22 34 44 59 // (212) 5 22 34 44 62
Zi Gzenaya 341- Tanger , Tel: (+212) 5 31 43 65 10 Email: contact@pladis.ma Site Web : www.pladis.ma