LOUNA™ ACOUSTICAL CEILING

1. IDENTIFICATION

Product identifier
Louna™ Acoustical Ceiling
Synonym(s)
Louna™ Baffle, Louna™ Elegant, Louna™ Elite, Louna™ Natural, Louna™ Hygiene, Stone Wool Ceiling Panels/Tiles
Recommended use
Interior use
Recommended restrictions
Use in accordance with manufacturer's recommendations.
Manufacturer / Importer / Supplier / Distributor information/Company name
USG Middle East Ltd
7410 (WASIL) Street #23, Cross 76 (Right)
Second Industrial City
Dammam 34326 – 4201, Kingdom of Saudi Arabia
Tel: +966 13 812 0995 / Fax: +966 13 812 1029
E-mail: info@usgme.com / marketing@usgme.com
Website: https://www.usgme.com

2. HAZARD(S) IDENTIFICATION

Emergency Overview
This product is not expected to produce any hazards during normal use and it's article under reach. Exposure to high dust levels may irritate the skin, eyes, nose, throat, or upper respiratory tract. Man-made mineral wool have been classified by the European Union as irritating to skin.
Signal word
The mechanical effect of fibres in contact with skin may cause temporary itching.
Hazard statement
Decomposition of binder above 190°C may produce carbon dioxide and some trace gases.

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Mixtures

Chemical name	CAS number	%
Mineral wool	Not classified	95 – 99 %
Binder	Not classified	1 – 5 %
Oil	Not classified	0.1 – 0.5 %

4. FIRST-AID MEASURES

Inhalation
Remove from exposure. Rinse the throat and blow nose to clear dust.
Skin contact
If itching occurs because of mechanical effects of the fibres, remove contaminated clothing and wash skin gently with cold water and soap.
Eye contact
Rinse abundantly with water.
Ingestion
This product is not intended to be ingested or eaten. Drink plenty of water if accidentally ingested.
Most important symptoms/effects, acute and delayed
The mechanical effects of fibers can cause temporary itching.
Indication of immediate medical attention and special treatment needed
Not applicable.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media
There are no special demand for extinguishing media. Normal extinguishing media can be used.
Unsuitable extinguishing media
Not applicable.
Specific hazards arising from the chemical
Not applicable.
Special protective equipment and precautions for fire fighters
Selection of respiratory protection for fire fighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire-fighting equipment/instructions
Use standard fire fighting procedures and consider the hazards of other involved materials.
Specific methods
Cool material exposed to heat with water spray and remove it if no risk is involved.
No unusual fire or explosion hazards noted.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures
See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up
Vacuum cleaner or dampen down with water spray prior to brushing up.
Environmental precautions
Not applicable.

7. HANDLING AND STORAGE

Precautions for safe handling
When installing insulation in unventilated spaces a suitable disposable face-mask should be used. When handling product, cover exposed skin. Wear goggles when working with product overhead. Dispose of waste in accordance with local regulations. Clean area using vacuum equipment. If itching occurs, it may be lessened by rinsing in cold water before washing.
Conditions for safe storage, including any incompatibilities
Store in a cool, dry, well-ventilated place. Keep away from incompatible materials, open flames and high temperatures. Keep away from moisture. Protect product from physical damage.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Components	Value
Mineral wool fibre	1 fibre/cm^3 (FI, SWE, LT)
Inorganic dust	10 mg/m^3 (FI, SWE, LT) and 0,4 mg/m^3 (PL)

Appropriate engineering controls personal protective equipment
Individual protection measures, such as personal protective equipment.
Eye/face protection
Wear approved safety goggles.
Skin protection
Cover exposed skin.
Hand protection
It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin contact use suitable protective gloves to avoid itching in conformity with EN 388.
Other
Normal work clothing (long sleeved shirts and long pants) is recommended.
Respiratory protection
When working in unventilated area or during operations which can generate emission of any dust, wear disposable face mask. Type in accordance with EN 149 FFP2 is recommended.
Thermal hazards
None.
Environmental exposure controls
Not applicable.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance
Solid, fibrous, grey.
Odor
Odourless.
Odor threshold
Not applicable.
pH
Not applicable.
Melting point/freezing point
Over 1000°C stone wool begins to soften and melt
Initial boiling point and boiling range
Not applicable.
Flash point
Not applicable.
Evaporation rate
Not applicable.
Flammability (solid, gas)
Non combustible.
Upper/lower flammability or explosive limits
Not applicable.
Vapor pressure
Not applicable.
Vapor density
Not applicable.
Bulk density
90-180 kg/m^3
Solubility(ies)
The products are practically insoluble in water and organic solutions.
Partition coefficient (n-octanol/water)
Not applicable.
Auto-ignition temperature
Not applicable.
Decomposition temperature
Not applicable.
Viscosity
Not applicable.
Explosive properties
Not applicable.
Oxidising properties
Not applicable.
Other information
Formaldehyde Emissions
Complies with Class E1 for Formaldehyde Emissions.

10. STABILITY AND REACTIVITY

Reactivity
Not applicable.
Chemical stability
Not applicable.
Possibility of hazardous reactions
Not applicable.
Conditions to avoid
Not applicable.
Incompatible materials
Not applicable.
Hazardous decomposition products
None in normal condition of use.
For high temperature uses:
Thermal decomposition of binder starts above190°C releasing smelling/odorous gases. The duration and amount of release is dependent upon the thickness of insulation, binder content and the temperature applied. During first heating, good ventilation or appropriate personal protection equipment are required.

11. TOXICOLOGICAL INFORMATION

Acute toxicity
Not toxic.
Skin corrosion/irritation
The mechanical effect of fibres in contact with skin may cause temporary itching.
Serious eye damage/irritation
May cause short-term mechanical irritation.
Respiratory or skin sensitisation
May cause short-term mechanical irritation.
Germ cell mutagenicity
Not applicable.
Carcinogenicity
Not applicable.
Reproductive toxicity
Not applicable.
STOT-single exposure
Not applicable.
STOT-repeated exposure
Not applicable.
Aspiration hazard
Not applicable.
Other information
Not applicable.

12. ECOLOGICAL INFORMATION

Ecotoxicity
Not toxic.
Persistence and degradability
Persistent.
Bioaccumulative potential
A very small possibility for water species.
Mobility in soil
A very small possibility.
Other adverse effects
Not applicable.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods
Stone wool waste is according to the European waste catalogue classified as non-hazardous waste (code 17 06 04) and can be disposed on a landfill for non-hazardous waste.
Local disposal regulations
Dispose of in accordance with local regulations.
Hazardous waste code
Not regulated.
Waste from residues / unused products
Dispose of in accordance with local regulations.
Contaminated packaging
Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT
Not regulated as a hazardous material by DOT.
IATA
Not regulated as a dangerous good.
IMDG
Not regulated as a dangerous good.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
Not applicable.

15. REGULATORY INFORMATION

Saudi Arabian Inventory of Chemical Substance:

CAS#	Not Classifed	Mineral wool
CAS#	Not Classifed	Binder
CAS#	Not Classifed	Oil

Further information
The stone wool fibres meet the claims in Note Q according to the European Classification Regulation No 1272/2008 about classification, labelling and packaging (CLP). USG stone wool has no classification.

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Issue date
27-September-2021
Revision date
1-December-2022
Version #
02
Further information
The International Agency for Research on Cancer (IARC) in June, 1987, categorized continuous filament glass fibers as not classifiable with respect to human carcinogenicity (Group 3). The evidence from human as well as animal studies was evaluated by IARC as insufficient to classify continuous filament glass fiber as a possible, probable, or confirmed cancer causing material. The ACGIH has established a TLV (Threshold Limit Value or recommended exposure limit) for continuous filament glass fiber of 1 fiber per cubic centimeter of air for respirable fibers and 5 mg per cubic meter of air for inhalable glass fiber dust. These levels were established to prevent mechanical irritation of the upper airways.
IARC, NTP (US National Toxicology Program) and OSHA (US Occupational Safety and Health Administration) do not list continuous filament glass fibers as a carcinogen.
As manufactured, continuous filament glass fibers in this product are not respirable. Continuous filament glass products that are chopped, crushed or severely mechanically processed during manufacturing or use may contain a very small amount of respirable particulate, some of which may be glass shards.

"Titanium dioxide: Raw materials and/or coatings in this product contain small amounts of titanium dioxide. The International Agency for Research on Cancer (IARC) has determined that titanium dioxide is possibly carcinogenic to humans (Group 2B) based on inadequate evidence in humans and sufficient evidence in experimental animals. This conclusion relates to long-term inhalation exposure to high concentrations of pigmentary (powdered) or ultrafine titanium dioxide. However, no significant exposure to primary particles of titanium dioxide is thought to occur during the use of products in which titanium dioxide is bound to other materials, such as in paints. The available human studies do not suggest an association between occupational exposure to titanium dioxide and risk for cancer (1). The American Conference of Governmental Industrial Hygienists (ACGIH) has designated this chemical as not classifiable as a human carcinogen (A4). The US National Toxicology Program (NTP) has not listed this chemical in its report on carcinogens."

NFPA Ratings:
Health: 1
Flammability: 0
Physical hazard: 0
Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

NFPA Ratings:

List of abbreviations
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
CAS: Chemical Abstracts Service (division of the American Chemical Society)
IARC: International Agency for Research on Cancer
TWA: Time Weighted Average
PEL: Permissible Exposure Limit

Disclaimer
This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

Notice:
As we are involved in constant products development; this document information is subject to change without prior notice. Please always refer to **usgme.com** for the updated products information document.

©2022 Factory of USG Middle East LTD. Co.
All rights reserved.

USG ME
INNOVATIVE SOLUTIONS. EVERYTIME.