Program 1

Problem Statement
Build a Daraz-style shopping system: store user and order details in a class, compute a 4% discount capped by a coin value, and calculate the final payable amount for either Cash-on-Delivery or an online payment method with an extra payment discount.

Source Code:

```
#include <iostream>
#include <string>
using namespace std;

class Daraz {
public:
string phoneNo;
string uname;
string pass;
string mail;
double coins;
double product_Price;
double disc_Amount;
double final_price;
double voucher_Discount;
double delFee;
double servFee;

void userInfo() {
cout << "Enter Mobile Number: ";
cin >> phoneNo;
cout << "Enter User Name: ";
cin >> uname;
cout << "Enter Password: ";
cin >> pass;
cout << "Enter Email: ";
cin >> mail;
cout << "Enter Product Price: ";
cin >> product_Price;
cout << "Enter Voucher Price: ";
cin >> voucher_Discount;
cout << "Enter Delivery Charge: ";
cin >> delFee;
cout << "Enter Service Charge: ";
cin >> servFee;
coins = 20000;
}

void calcDiscount() {
```

```
disc_Amount = (product_Price * 4.0) / 100.0;
}

double calculate_Coin_Discount() {
double coinVal = coins / 100.0;
double maxAllowed = (product_Price * 4.0) / 100.0;
if (coinVal < maxAllowed) {
return coinVal;
} else {
return maxAllowed;
}
}

void payCOD() {
double coinValue = calculate_Coin_Discount();
final_price = product_Price - coinValue - voucher_Discount + delFee +
servFee;
cout << "\nCash on Delivery Details " << endl;
cout << "Product Price : " << product_Price << " Tk" << endl;
cout << "Coin Price : " << coinValue << " Tk" << endl;
cout << "Voucher : " << voucher_Discount << " Tk" << endl;
cout << "Delivery Charge : " << delFee << " Tk" << endl;
cout << "Service Charge : " << servFee << " Tk" << endl;
cout << "Total Payable Amount : " << final_price << " Tk" << endl;
}

void payOnline() {
int payChoice;
double pay_Discount_Rate = 0.0;
double pay_Discount = 0.0;
double coinValue = calculate_Coin_Discount();

cout << "\nSelect Payment Option " << endl;
cout << "1. bKash (10% Discount)" << endl;
cout << "2. Nagad (15% Discount)" << endl;
cout << "3. Rocket (0% Discount)" << endl;
cout << "4. Card (0% Discount)" << endl;
cout << "Enter choice: ";
cin >> payChoice;

if (payChoice == 1) {
pay_Discount_Rate = 0.10;
} else if (payChoice == 2) {
pay_Discount_Rate = 0.15;
} else if (payChoice == 3 || payChoice == 4) {
pay_Discount_Rate = 0.00;
```

```
} else {
cout << "Invalid Payment Method Selected!" << endl;
return;
}

pay_Discount = product_Price * pay_Discount_Rate;
final_price = product_Price - coinValue - voucher_Discount - pay_Discount +
delFee + servFee;

cout << "\nOnline Payment Summary" << endl;
cout << "Product Price : " << product_Price << " Tk" << endl;
cout << "Product Discount : " << disc_Amount << " Tk" << endl;
cout << "Coin Price : " << coinValue << " Tk" << endl;
cout << "Voucher : " << voucher_Discount << " Tk" << endl;
cout << "Delivery Charge : " << delFee << " Tk" << endl;
cout << "Service Charge : " << servFee << " Tk" << endl;
cout << "Total Payable Amount : " << final_price << " Tk" << endl;
}
};

int main() {
cout << "DARAZ SHOPPING SYSTEM" << endl;

Daraz order;
order.userInfo();
order.calcDiscount();

int type;
cout << "\nChoose Payment Type:" << endl;
cout << "1. Cash on Delivery" << endl;
cout << "2. Online Payment" << endl;
cout << "Your Option: ";
cin >> type;

if (type == 1) {
order.payCOD();
} else if (type == 2) {
order.payOnline();
} else {
cout << "Invalid option Chosen!" << endl;
}

return 0;
}
```

Input:

01712345678 ekra pass123 ekra@gmail.com
5000 500 100 20
1

Output:

