Program 1

Problem Statement
Model employee salaries using a class with static data members that accumulate total pay per role, a constructor that sets them, and a destructor that prints the totals and reports which role has the highest total salary.

Source Code:

```
#include <iostream>
using namespace std;

class employee {
private:
string CEO;
string team_manager;
string programmer;

int CEO_salary;
int team_manager_salary;
int programmer_salary;

static int CEO_total_salary;
static int team_manager_total_salary;
static int programmer_total_salary;

public:
// Constructor
employee(string c, string Tm, string p) {
CEO = c;
team_manager = Tm;
programmer = p;

CEO_salary = 10000;
team_manager_salary = 6000;
programmer_salary = 5000;

// Calculating total salaries based on counts (1 CEO, 3 Managers, 7 Programmers)
CEO_total_salary = 1 * CEO_salary;
team_manager_total_salary = 3 * team_manager_salary;
programmer_total_salary = 7 * programmer_salary;
}

// Destructor
~employee() {
cout << "CEO Total salary: " << CEO_total_salary << endl;
cout << "Team manager total salary: " << team_manager_total_salary << endl;
cout << "Programmer total salary: " << programmer_total_salary << endl;

if (CEO_total_salary > team_manager_total_salary && team_manager_total_salary >
programmer_total_salary) {
cout << "CEO salary are highest" << endl;
}
```

```
else if (team_manager_total_salary > CEO_total_salary && team_manager_total_salary
> programmer_total_salary) {
cout << "Team manger total salary are highest" << endl;
}
else {
cout << "Programmer total salary are highest" << endl;
}
}
};

// Initializing static variables
int employee::CEO_total_salary = 0;
int employee::team_manager_total_salary = 0;
int employee::programmer_total_salary = 0;

int main() {
// Creating object. When main ends, the destructor ~employee() is called
automatically.
employee e1("CEO", "Team manager", "Programmer");

return 0;
}
```

Input:
(no input)

Output:

