

AI Hack — Using Claude

You've been given an **API key** (`sk-...`). It works with **Claude Code** and the **Anthropic SDKs** (Python / TypeScript) by pointing them at our gateway instead of `api.anthropic.com` .

	Value
Base URL	<code>https://ai.hack.lawhive.co.uk</code>
Auth	<code>Authorization: Bearer sk-...</code> (your key)
Model	<code>vertex_ai/claude-opus-4-7</code>

One model only. `vertex_ai/claude-opus-4-7` is the *only* model that routes. Any other name (incl. `sonnet` , `haiku` , `opus` , or standard Anthropic IDs) will fail. The setup below remaps every alias to it so nothing breaks.

Keep your key private — don't commit it or paste it in shared channels.

Claude Code

1. **Install** (needs Node.js 18+):

```
npm install -g @anthropic-ai/claude-code
```

2. **Configure.** Add this to your shell profile (`~/.zshrc` or `~/.bashrc`), replacing the key:

```
export ANTHROPIC_BASE_URL="https://ai.hack.lawhive.co.uk"
export ANTHROPIC_AUTH_TOKEN="sk-xxxxx"           # your key
export ANTHROPIC_MODEL="vertex_ai/claude-opus-4-7"
export CLAUDE_CODE_DISABLE_EXPERIMENTAL_BETAS=1

# Remap all aliases to the one routable model so background/subagent tasks work:
export ANTHROPIC_DEFAULT_OPUS_MODEL="vertex_ai/claude-opus-4-7"
export ANTHROPIC_DEFAULT_SONNET_MODEL="vertex_ai/claude-opus-4-7"
export ANTHROPIC_DEFAULT_HAIKU_MODEL="vertex_ai/claude-opus-4-7"
```

Then `source ~/.zshrc` (or open a new terminal) and run:

```
claude
```

Don't run `/login` . You're authenticating with a key, not an Anthropic account. If Claude Code ever says "*Please run /login*", it's a config issue (see Troubleshooting), not a real login prompt.

One-liner alternative (no profile edits — but set the HAIKU override too, or background tasks fail):

```
ANTHROPIC_AUTH_TOKEN="sk-xxxxx" \
ANTHROPIC_BASE_URL="https://ai.hack.lawhive.co.uk" \
ANTHROPIC_DEFAULT_HAIKU_MODEL="vertex_ai/claude-opus-4-7" \
CLAUDE_CODE_DISABLE_EXPERIMENTAL_BETAS=1 \
claude --model vertex_ai/claude-opus-4-7
```

Anthropic SDK

Same idea: set the base URL and pass the key as a **bearer auth token** (`auth_token` / `authToken`), not `api_key` .

Python

```
pip install anthropic
```

```
import os
import anthropic

client = anthropic.Anthropic(
    base_url="https://ai.hack.lawhive.co.uk",
    auth_token=os.environ["ANTHROPIC_AUTH_TOKEN"], # your sk-... key
)

msg = client.messages.create(
    model="vertex_ai/claude-opus-4-7",
    max_tokens=1024,
```

```
    messages=[{"role": "user", "content": "Hello!"}],
  )
  print(msg.content[0].text)
```

TypeScript / JavaScript

```
npm install @anthropic-ai/sdk
```

```
import Anthropic from "@anthropic-ai/sdk";

const client = new Anthropic({
  baseURL: "https://ai.hack.lawhive.co.uk",
  authToken: process.env.ANTHROPIC_AUTH_TOKEN, // your sk-... key
});

const msg = await client.messages.create({
  model: "vertex_ai/claude-opus-4-7",
  max_tokens: 1024,
  messages: [{ role: "user", content: "Hello!" }],
});

console.log(msg.content);
```

Both SDKs also auto-read `ANTHROPIC_BASE_URL` and `ANTHROPIC_AUTH_TOKEN` from the environment, so if you've exported them (as in the Claude Code step) you can construct the client with no arguments.

Sanity check (curl)

```
curl https://ai.hack.lawhive.co.uk/v1/messages \
-H "Authorization: Bearer sk-xxxxx" \
-H "content-type: application/json" \
-H "anthropic-version: 2023-06-01" \
-d '{
  "model": "vertex_ai/claude-opus-4-7",
  "max_tokens": 64,
  "messages": [{"role": "user", "content": "ping"}]
}'
```

A JSON response with `content` means you're good.

Troubleshooting

- **"Please run /login" / auth errors** — don't log in. Your key isn't being picked up. Check `echo $ANTHROPIC_AUTH_TOKEN` in the *same* terminal, and make sure no stale `ANTHROPIC_API_KEY` or `CLAUDE_CODE_OAUTH_TOKEN` is set (`unset` them if so).
- **Model not found / 400 / background tasks failing** — you missed the alias overrides. Only `vertex_ai/claude-opus-4-7` routes; set all three `ANTHROPIC_DEFAULT_*_MODEL` vars.
- **VS Code / GUI editor doesn't see the key** — GUI apps launched from the Dock don't inherit shell exports. Launch the editor from a terminal where the vars are set, or add an `env` block to `~/.claude/settings.json`.
- **Anything else** — ping an organiser.