Java Persistence API & Related Patterns

Domain Logic, Data Source, Object Relational

www.cs.uoi.gr/~zarras/http://www.cs.uoi.gr/~zarras/se.htm

https://docs.spring.io/springdata/jpa/docs/current/reference/html/#jpa.query-methods https://www.vogella.com/tutorials/JavaPersistenceAPI/article.html/

https://www.baeldung.com/spring-data-derived-queries

1

What is JPA?

Mapping objects to database table rows and vice versa is called Object-Relational Mapping (ORM).

The Java Persistence API (JPA) is an approach to ORM for Java objects.


Via IPA the developer can map, store, update and retrieve data from relational databases to lava objects and vice versa.

JPA is a **specification** from Oracle https://download.oracle.com/otn-pub/jcp/persistence-2 l-fr-eval-spec/JavaPersistence.pdf?AuthParam=1647415880_273dae2fb012962231cd5758a30e83d3

It can have multiple compliant implementations Hibernate, EclipseLink and Apache OpenJPA.

How do we organize Domain layer logic?


3



How do we transfer data from/to the Domain layer to/from the Data Layer?

5

Data Mapper



A layer of Mappers moves data between objects and a database while keeping them independent of each other and the mapper itself.

In Spring Boot these are called JPA Repositories

https://martinfowler.com/eaaCatalog/dataMapper.html

How to map objects to tuples (table rows)?

Identity Field

Saves a database ID field in an object to maintain identity between an inmemory object and a table row.

Intent

Reading data from a database is all very well, but in order to write data back you need to tie the database to the in-memory object system.

In essence, *Identity Field* is mind-numbingly simple. All you do is store the primary key of the relational database table in the object's fields.





https://martinfowler.com/eaaCatalog/identityField.html

Ջ

Foreign Key Mapping

Maps an association between objects to a foreign key reference between tables.

Objects can refer to each other directly by object references. To **save** these **objects** to a **database**, it's vital to **save these references**.

A Foreign Key Mapping maps an object reference to a foreign key in the database.


https://martinfowler.com/eaaCatalog/foreignKeyMapping.html


9


Foreign Key Mapping Maps an association between objects to a


Maps an association between objects to a foreign key reference between tables.


One-to-One relation - Route to Driver












Single Table Inheritance

There's only a single table to worry about on the database. There are no joins in retrieving data. Any refactoring that pushes fields up or down the hierarchy doesn't change the DB.

Fields are sometimes relevant and sometimes not, which can be confusing. Columns used only by some subclasses lead to wasted space in the database. The single table may end up being too large.

15



Class Table Inheritance

Represents an inheritance hierarchy of classes with one table for each class.

All columns are relevant for every row so tables are easier to understand and don't waste space.

The relationship between the domain model and the database is straightforward.

Need to touch multiple tables to load an object, which means a join or multiple queries and sewing in memory.

Any refactoring of fields up or down the hierarchy causes database changes.

17

Concrete Table Inheritance Represents an C Employee inheritance hierarchy int eid String name of classes with one table per <u>leaf</u> class in o methods, constructors, getters, setters, etc... the hierarchy with all fields in the table row. © RetiredEmployee C ActiveEmployee double salary a double pension o methods, constructors, getters, setters, etc.... o methods, constructors, getters, setters, etc... © "Database Table" retired_employees «Database Table» © active_employees ninteger eid o integer eid varchar name double salary double pension https://martinfowler.com/eaaCatalog/concreteTableInheritance.html

Concrete Table Inheritance

Represents an inheritance hierarchy of classes with one table per <u>leaf</u> class in the hierarchy with all fields in the table row.

Each table is self-contained and has no irrelevant fields.

There are no joins to do when reading the data from the concrete mappers.

Each table is accessed only when that class is accessed, which can spread the access load.

Redundancy in the data

With fields are pushed up or down the hierarchy, you don't have to alter the table definitions. If a superclass field changes, you need to change each table.