pst-knot

Plotting special knots; v.0.02

Herbert Voß

April 13, 2023

Contents


1	introduction	1
2	\psKnot	1
3	Special settings	3
	3.1 Scaling	
	3.2 Border color	
	3.3 Border width	4
4	\psBorromean	5
5	List of all optional arguments for pst-knot	6
Re	eferences	6


1 introduction

This is the very first try of drawing knots. The package uses the PostScript subroutines of the file psMath.pro from Matthias Buch-Kromann.) Currently there are only two macros for knots.

2 \psKnot


The macro $\protect\operatorname{NpsKnot}$ has one optional and two mandatory arguments, the origin of the image and the knot type. The following list shows all available knot types.






 $\begin{pspicture}[showgrid=true](-2,-2)(2,2)\\ psKnot[linewidth=3pt,linecolor=red](0,0)\{0-1\}\\ \end{pspicture}$

2 \psKnot 2



\begin{pspicture}[showgrid=true](-2,-2)(8,2)
\psKnot[linewidth=3pt,linecolor=red](0,0){3-1}
\psKnot[linewidth=3pt,linecolor=blue](4,0){4-1}
\end{pspicture}





\begin{pspicture}(-2,-2)(8,2)
\psKnot[linewidth=3pt,linecolor=blue](0,0){5-1}
\psKnot[linewidth=3pt,linecolor=blue](4,0){5-2}
\end{pspicture}







\begin{pspicture}(-2,-2)(10,2)
\psKnot[linewidth=3pt,linecolor=blue](0,0){6-1}
\psKnot[linewidth=3pt,linecolor=blue](4,0){6-2}
\psKnot[linewidth=3pt,linecolor=blue](8,0){6-3}
\end{pspicture}

3 Special settings 3








\begin{pspicture}(-2,-2)(10,2)
\psKnot[linewidth=3pt,linecolor=red](0,0){7-1}
\psKnot[linewidth=3pt,linecolor=blue](4,0){7-2}
\psKnot[linewidth=3pt,linecolor=green](8,0){7-3}
\end{pspicture}







\begin{pspicture}(-2,-2)(10,2)
 \psKnot[linewidth=3pt,linecolor=red](0,0){7-4}
 \psKnot[linewidth=3pt,linecolor=green](4,0){7-5}
 \psKnot[linewidth=3pt,linecolor=blue](8,0){7-6}
 \end{pspicture}



\begin{pspicture}[showgrid=true](-2,-2)(2,2)
\psKnot[linewidth=3pt,linecolor=blue](0,0){7-7}
\end{pspicture}


3 Special settings

There exists three special optional arguments for the macro \psKnot.

3.1 Scaling


The image can be scaled with scale, which can take one or two values for x and y scaling. For only one value it is scaled for x and y with the same value. The default is 1 1.

3 Special settings 4



3.2 Border color

The background color of the border can be controlled by knotbgcolor. It can use any possible color value and it makes only sense for a colored background to get the same color for the crossing.



```
\begin{pspicture}(-2,-2)(6,2)
 \psframe[fillcolor=black!20,fillstyle=solid](-2,-2)(6,2)
 \psKnot[linewidth=5pt,linecolor=red!50](0,0){7-4}
 \psKnot[linewidth=5pt,linecolor=red!50,
 knotbgcolor=black!20](4,0){7-4}
 \end{pspicture}
```

Pay attention that black!20 is the same as 0,8 of gray.

3.3 Border width

The width of the border is controlled by the keyword knotborder and it is preset to 5\pslinewidth. The border width is added to the current linewidth.

4 \psBorromean 5




```
\begin{pspicture}(-2,-2)(6,2)
\psKnot[linewidth=3pt,linecolor=cyan!60](0,0){6-3}
\psKnot[linewidth=3pt,linecolor=red!50,
   knotborder=5\pslinewidth](4,0){6-3}
\end{pspicture}
```

4 \psBorromean

The macro \psBorromean draws the so called Borromean rings. It has one optional and three mandatory arguments, the origin of the image, the inner and outer radius. The following list shows all available knot types.

 $\verb|\psBorromean| [Options]| (x,y) \{ circle \ radius \} \{ inner \ radius \}$



\begin{pspicture}[showgrid=true](-2,-3)(10,4)
\psBorromean(0,0){1cm}{1cm}
\psBorromean[linewidth=8pt,knotborder=2\pslinewidth,
 bmcolor={blue,yellow,magenta}](6,0){2cm}{1.5cm}
\end{pspicture}

5 List of all optional arguments for pst-knot

Key	Type	Default
knotborder	ordinary	2
knotbgcolor	ordinary	1
knotscale	ordinary	1 1
bmcolor	ordinary	[none]

References

- [1] Denis Girou. "Présentation de PSTricks". in Cahier GUTenberg: 16 (april 1994), pages 21-70.
- [2] Michel Goosens **andothers**. *The LATEX Graphics Companion*. 2 **edition**. Reading, Mass.: Addison-Wesley Publishing Company, 2007.
- [3] Laura E. Jackson **and** Herbert Voß. "Die Plot-Funktionen von pst-plot". **in**Die TeXnische Komödie: 2/02 (**june** 2002), **pages** 27–34.
- [4] Nikolai G. Kollock. PostScript richtig eingesetzt: vom Konzept zum praktischen Einsatz. Vaterstetten: IWT, 1989
- [5] Herbert Voß. "Die mathematischen Funktionen von PostScript". **in**Die TeXnische Komödie: 1/02 (**march** 2002).
- [6] Herbert Voß. pst-tools Helper functions. 2012. URL: /graphics/pstricks/contrib/pst-tools.
- [7] Herbert Voß. PSTricks Grafik für TFX und LATFX. 7 edition. Heidelberg and Berlin, 2016.
- [8] Herbert Voß. PSTricks Graphics for TeX and LATeX. Cambridge: UIT, 2011.
- [9] Herbert Voß. ETEX quick reference. Cambridge: UIT, 2012.
- [10] Herbert Voß. Typesetting mathematics with LaTeX. Cambridge: UIT, 2010.
- [11] Eric Weisstein. Wolfram MathWorld. 2007. URL: http://mathworld.wolfram.com.
- [12] Eric W. Weisstein. Noncentral Student's t-Distribution. From MathWorld—A Wolfram Web Resource. Probability and Statistics; Statistical Distributions; Continuous Distributions. URL: https://mathworld.wolfram.com/NoncentralStudentst-Distribution.html.
- [13] Timothy van Zandt. multido.tex a loop macro, that supports fixed-point addition. 1997. URL: /graphics/pstricks/generic/multido.tex.
- [14] Timothy van Zandt. *PSTricks PostScript macros for generic T_EX*. 1993. URL: http://www.tug.org/application/PSTricks.
- [15] Timothy van Zandt **and** Denis Girou. "Inside PSTricks". **in** *TUGboat*: 15 (**september** 1994), **pages** 239–246.
- [16] Timothy van Zandt **and** Herbert Voß. pst-plot: Plotting two dimensional functions and data. 1999. URL: /graphics/pstricks/generic/pst-plot.tex.

Index

```
Dimension
     \protect\ \pslinewidth, 4
File
     psMath.pro, 1
Keyword
     knotbgcolor, 4
     knotborder, 4
     scale, 3
knotbgcolor, 4
knotborder, 4
Macro
     \psBorromean, 5
     \protect\ \psKnot, 1, 3
\psBorromean, 5
\psKnot, 1, 3
\verb|\pslinewidth|, 4
psMath.pro, 1
scale, 3
```