





RECOMMENDED P.C.B. LAYOUT
TOLERANCE UNSPECIFIED ±0.05mm

NOTE:
1.MATERIAL SPECIFICATION:
1−1: HOUSING: HIGH TEMPERATURE PLASTIC.UL94 V−0 BLACK.
1−2: CONTACTS : COPPER ALLOY
1−3: SHELL: STAINLESS STEEL
2.PLATING SPECIFICATION:
2−1.CONTACTS:
Ni PLATING UNDER PLATED OVER ALL
CONTACT AREA : REFER THE PART NUMBER
G/F PLATING SPECIFICATIONS OF THE SOLDER AREA
2−2: SHELL
Ni PLATED OVER ALL
3.SPECIFICATION:
3−1: CURRENT RATING: 3.0A MAX
3−2: VOLTAGE: 48 VAC
3−3: TEMPERATURE RANGE: −30 ℃ ~ 85 ℃
3−4: VBUS & GND PINS AND OTHER PINS: 40mΩ/PIN MAX.
3−5: INSULATION RESISTANCE: 100 MEGOHMS MIN.
3−6: LNSERTION FORCE: 5N~20N
3−7: UNMATING FORCE: 8N~20N
3−8: DURABILITY: 10000 CYCLES
4.PRODUCT PART NUMBER DESCRIPTION:
10176783 − 0 0 0 X X LF
LF: LEAD FREE
X: PACKING TYPE: 1: TAPE/REEL
X: CONTACT AREA PLATING 1: 3u" GOLD

mat'l. code				surface ISO 1302		tolerance ISO 406 ISO 1101		projection	product family		
ltr	ecn no	dr	date	tolerances unless otherwise specified					USB		
A	−	TY Tang	2025/06/27	angles	linear	0.X±0.35		mm	title		
B	ELX-N-302211	TY Tang	2026/08/18			0.XX±0.25			USB TYPE C VERTICAL 8P TH TYPE		
				0°±x°		0.XXX±0.15		scale 1:1			
				dr	Tian−Yu Tang	2026/08/18		Amphenol FCi	dwg no 10176783	sheet 1 of 1	size A3
				engr	Tian−Yu Tang	2026/08/18					
				chr	L−Q Lei	2026/08/18			type Product Customer Drawing		
				appd	Tim Yao	2026/08/18					
sheet index	revision sheet	B 1									

© 2016 AFCI