CUI Devices is now Same Sky! Learn More

same sky

SERIES: UJ2-AH-SMT | DESCRIPTION: USB RECEPTACLE

FEATURES

- USB type A jack
- USB 2.0
- horizontal orientation
- surface mount



RoHS

PART NUMBER KEY

UJ2 - AH - X - SMT - TR

- Base Number
- Contact Plating Thickness (gold): 1 = 3 µ" 4 = 30 µ"
- Packaging Style: SMT = surface mount
- Packaging Options: TR = Tape & Reel

SPECIFICATIONS


parameter	conditions/description	min	typ	max	units
USB standard	USB 2.0				
rated input voltage				30	Vac
rated input current				1.5	A
contact resistance[1]	between terminals and mating plug			30	mΩ
insulation resistance		1000			MΩ
voltage withstand	for 1 minute			500	Vac
insertion force				35	N
withdrawal force		10			N
operating temperature		-40		85	°C
life			1,500		cycles
flammability rating	UL94V-0				
RoHS	yes				


Note: 1. When measured at 20 mV / 100 mA.
2. All specifications measured at 15~35°C, humidity at 25~85%, under atmospheric pressure of 86~106 kPa, unless otherwise noted.


MECHANICAL DRAWING


units: mm
tolerance:
X ±0.38 mm
X.X ±0.30 mm
X.XX ±0.20 mm
X.XXX ±0.10 mm
PCB tolerance: ±0.05 mm
unless otherwise specified

	MATERIAL	PLATING
contact terminals	C2680 t=0.25 mm	contact area: gold over nickel solder area: 80 µ" min. tin over 50 µ" min overall
housing	LCP (UL94V-0)	nickel
shell	C2680 t=0.30	50 µ" min. nickel










Recommended PCB Layout
Top View

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
reel storage	at relative humidity 65~70%	25		30	°C
reflow soldering[3]	see reflow profile		255	260	°C


Note: 3. It is recommended to reflow solder within 3 months from opening vacuum packaging at a temperature of 25~30°C & relative humidity 65~70%.




PACKAGING

units: mm

Reel Size: Ø380
Reel QTY: 500 pcs per reel





REVISION HISTORY

rev.	description	date
1.0	initial release	08/05/2016
1.01	added tape and reel drawing	10/05/2017
1.02	brand update	02/05/2020
1.03	added USB standard	04/07/2022
1.04	logo, datasheet style update	08/05/2022
1.05	CUI Devices rebranded to Same Sky	09/12/2024
1.06	product reengineered for improved manufacturability and production yield, see PCN for details	07/15/2025

The revision history provided is for informational purposes only and is believed to be accurate.

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

sameskydevices.com