CUI Devices is now Same Sky! Learn More



# MODEL: UJ32-C-H-G-H2-SMT-TR | DESCRIPTION: USB RECEPTACLE

## FEATURES

- USB Type C receptacle
- USB 3.2 Gen 2x2
- 20 Gbit/s data transfer speed
- reflow solder compatible
- tape & reel packaging



RoHS

## SPECIFICATIONS


| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| USB standard | USB 3.2 Gen 2x2 | | | | |
| rated input voltage | | | | 20 | Vdc |
| rated input current | as per EIA-364-70, Method B<br>power pins collectively (A1, A4, A9, A12, B1, B4, B9, B12)<br>VCONN pins individually (A5, B5)<br>all other signal pins individually | | | <br>5.0<br>1.25<br>0.25 | <br>A<br>A<br>A |
| contact resistance[1] | between terminals and mating plug | | | 40 | mΩ |
| insulation resistance | between adjacent contacts | 100 | | | MΩ |
| voltage withstand | between adjacent contacts | 100 | | | Vac |
| insertion force | at a rate of 12.5 mm/min | 5 | | 20 | N |
| withdrawal force | at a rate of 12.5 mm/min | 8 | | 20 | N |
| life | at a rate of 200 cycles per hour | | 10,000 | | cycles |
| operating temperature | | -40 | | 85 | °C |
| flammability rating | UL94V-0 | | | | |
| RoHS | yes | | | | |

Note: 1. When measured at 20 mV / 100 mA.
2. All specifications measured at 10~35°C, humidity at 45~85%, under standard atmospheric pressure, unless otherwise noted.

## SOLDERABILITY


| parameter | conditions/description | min | typ | max | units |
|---|---|---|---|---|---|
| reel storage | at relative humidity 65~70% | 25 | | 30 | °C |
| reflow soldering[3] | see reflow profile | | 255 | 260 | °C |

Note: 3. It is recommended to reflow solder within 3 months from opening vacuum packaging at a temperature of 25~30°C & relative humidity 65~70%.





# MECHANICAL DRAWING


units: mm
tolerance:
X. ±0.50 mm
X.X ±0.30 mm
X.XX ±0.20 mm
X.XXX ±0.10 mm
unless otherwise noted





| | MATERIAL | PLATING |
|---|---|---|
| insulator | LCP (UL94V-0) | black |
| contact | copper alloy | contact area: gold flash<br>solder area: matte tin over nickel |
| shell | stainless steel | nickel |
| cover shell | copper alloy | nickel |
| inner ground cover shell | stainless steel | clean |
| mid plate | stainless steel | clean |












## MECHANICAL DRAWING (CONTINUED)

units: mm
PCB tolerance: ±0.05 mm
PCB thickness: 1.6 mm

| PIN CONNECTIONS | | | | | |
|---|---|---|---|---|---|
| PIN | SIGNAL NAME | MATING SEQUENCE | PIN | SIGNAL NAME | MATING SEQUENCE |
| A1 | GND | FIRST | B12 | GND | FIRST |
| A2 | SSTXp1 | SECOND | B11 | SSRXp1 | SECOND |
| A3 | SSTXn1 | SECOND | B10 | SSRXn1 | SECOND |
| A4 | $V_{BUS}$ | FIRST | B9 | $V_{BUS}$ | FIRST |
| A5 | CC1 | SECOND | B8 | SBU2 | SECOND |
| A6 | Dp1 | SECOND | B7 | Dn2 | SECOND |
| A7 | Dn1 | SECOND | B6 | Dp2 | SECOND |
| A8 | SBU1 | SECOND | B5 | CC2 | SECOND |
| A9 | $V_{BUS}$ | FIRST | B4 | $V_{BUS}$ | FIRST |
| A10 | SSRXn2 | SECOND | B3 | SSTXn2 | SECOND |
| A11 | SSRXp2 | SECOND | B2 | SSTXp2 | SECOND |
| A12 | GND | FIRST | B1 | GND | FIRST |
| SHELL | | GND | SHELL | | GND |





Recommended PCB Layout
Top View

## PACKAGING

units: mm

Reel Size: Ø380 mm
Reel QTY: 900 pcs per reel
Carton Size: 405 x 405 x 330 mm
Carton QTY: 7,200 pcs



## REVISION HISTORY

| rev. | description | date |
|---|---|---|
| 1.0 | initial release | 06/15/2022 |
| 1.01 | logo, datasheet style update | 08/05/2022 |
| 1.02 | updated datasheet | 11/13/2023 |
| 1.03 | CUI Devices rebranded to Same Sky | 09/12/2024 |

The revision history provided is for informational purposes only and is believed to be accurate.

same sky

Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**sameskydevices.com**