
Octal D-Type Flip-Flop with 3-STATE Outputs

74VHC574



TSSOP20, 4.4x6.5
CASE 948AQ

General Description

The VHC574 is an advanced high speed CMOS octal flipflop with 3−STATE output fabricated with silicon gate CMOS technology. It achieves the high speed operation similar to equivalent Bipolar Schottky TTL while maintaining the CMOS low power dissipation. This 8−bit D−type flip−flop is controlled by a clock input (CP) and an output enable input ($\overline{OE}$). When the $\overline{OE}$ input is HIGH, the eight outputs are in a high impedance state.

An input protection circuit ensures that 0 V to 5.5 V can be applied to the input pins without regard to the supply voltage. This device can be used to interface 5 V to 3 V systems and two supply systems such as battery back up. This circuit prevents device destruction due to mismatched supply and input voltages.

Features

- High Speed: t_{PD} = 5.6 ns (Typ) at V_{CC} = 5 V
- High Noise Immunity: $V_{NIH} = V_{NIL}$ = 28% V_{CC} (Min)
- Power Down Protection is Provided on All Inputs
- Low Noise: V_{OLP} = 0.6 V (Typ)
- Low Power Dissipation: I_{CC} = 4 μA (Max) @ T_A = 25°C
- Pin and Function Compatible with 74HC574
- These are Pb−Free Devices

Logic Symbol





Figure 1. Logic Symbol


MARKING DIAGRAM



XXXXXX = Specific Device Code
A = Assembly Location
L = Wafer Lot
Y = Year
W = Work Week
▪ = Pb−Free Package

(Note: Microdot may be in either location)

CONNECTION DIAGRAM



PIN DESCRIPTIONS

Pin Names	Description
D_0–D_7	Data Inputs
CP	Clock Pulse Input
$\overline{OE}$	3−STATE Output Enable Input
O_0–O_7	3−STATE Outputs

ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

© Semiconductor Components Industries, LLC, 1993

Functional Description


The VHC574 consists of eight edge−triggered flip−flops with individual D−type inputs and 3−STATE true outputs. The buffered clock and buffered Output Enable are common to all flip−flops. The eight flip−flops will store the state of their individual D inputs that meet the setup and hold time requirements on the LOW−to−HIGH Clock (CP) transition. With the Output Enable ($\overline{OE}$) LOW, the contents of the eight flip−flops are available at the outputs. When the $\overline{OE}$ is HIGH, the outputs go to the high impedance state. Operation of the $\overline{OE}$ input does not affect the state of the flipflops.

TRUTH TABLE

Inputs			Outputs
D_n	CP	$\overline{OE}$	O_n
H	↗	L	H
L	↗	L	L
X	X	H	Z

H = HIGH Voltage Level
L = LOW Voltage Level
X = Immaterial
Z = High Impedance
↗ = LOW−to−HIGH Transition

Logic Diagram



Please note that this diagram is provided only for the understanding of logic operations and should not be used to estimate propagation delays.

Figure 2. Logic Diagram

MAXIMUM RATINGS

Symbol	Parameter		Value	Unit
V_{CC}	DC Supply Voltage		−0.5 to +6.5	V
V_{IN}	DC Input Voltage		−0.5 to +6.5	V
V_{OUT}	DC Output Voltage		−0.5 to V_{CC} + 0.5	V
I_{IN}	DC Input Current, per Pin		±20	mA
I_{OUT}	DC Output Current, per Pin		±25	mA
I_{CC}	DC Supply Current, V_{CC} and GND Pins		±75	mA
I_{IK}	Input Clamp Current		−20	mA
I_{OK}	Output Clamp Current		±20	mA
T_{STG}	Storage Temperature Range		−65 to +150	°C
T_L	Lead Temperature, 1 mm from Case for 10 Seconds		260	°C
T_J	Junction Temperature under Bias		+150	°C
θ_{JA}	Thermal Resistance (Note 2)		150	°C/W
P_D	Power Dissipation in Still Air at 25°C		833	mW
MSL	Moisture Sensitivity		Level 1	
F_R	Flammability Rating	Oxygen Index: 28 to 34	UL 94 V−0 @ 0.574 in	
V_{ESD}	ESD Withstand Voltage (Note 3)	Human Body Model	2000	V
		Charged Device Model	N/A	

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Applicable to devices with outputs that may be tri−stated.
2. Measured with minimum pad spacing on an FR4 board, using 76 mm−by−114 mm, 2−ounce copper trace no air flow per JESD51−7.
3. HBM tested to EIA / JESD22−A114−A. CDM tested to JESD22−C101−A. JEDEC recommends that ESD qualification to EIA/JESD22−A115A (Machine Model) be discontinued.

Share Feedback
Your Opinion Matters

RECOMMENDED OPERATING CONDITIONS

Symbol	Parameter		Min	Max	Unit
V_{CC}	DC Supply Voltage		2.0	5.5	V
V_{IN}	DC Input Voltage (Note 4)		0	5.5	V
V_{OUT}	DC Output Voltage (Note 4)		0	V_{CC}	V
T_A	Operating Temperature		−55	+125	°C
t_r, t_f	Input Rise or Fall Rate	V_{CC} = 3.0 V to 3.6 V	0	100	ns/V
		V_{CC} = 4.5 V to 5.5 V	0	20	

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

4. Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or V_{CC}). Unused outputs must be left open.

DC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions		V_{CC} (V)	T_A = 25°C			T_A = −40°C to +85°C		Unit
					Min	Typ	Max	Min	Max	
V_{IH}	HIGH Level Input Voltage			2.0	1.50	–	–	1.50	–	V
				3.0–5.5	0.7 V_{CC}	–	–	0.7 V_{CC}	–	
V_{IL}	LOW Level Input Voltage			2.0	–	–	0.50	–	0.50	V
				3.0–5.5	–	–	0.3 V_{CC}	–	0.3 V_{CC}	
V_{OH}	HIGH Level Output Voltage	V_{IN} = V_{IH} or V_{IL}	I_{OH} = –50 μA	2.0	1.9	2.0	–	1.9	–	V
				3.0	2.9	3.0	–	2.9	–	
				4.5	4.4	4.5	–	4.4	–	
			I_{OH} = –4 mA	3.0	2.58	–	–	2.48	–	
			I_{OH} = –8 mA	4.5	3.94	–	–	3.80	–	
V_{OL}	LOW Level Output Voltage	V_{IN} = V_{IH} or V_{IL}	I_{OL} = 50 μA	2.0	–	0.0	0.1	–	0.1	V
				3.0	–	0.0	0.1	–	0.1	
				4.5	–	0.0	0.1	–	0.1	
			I_{OL} = 4 mA	3.0	–	–	0.36	–	0.44	
			I_{OL} = 8 mA	4.5	–	–	0.36	–	0.44	
I_{OZ}	3−STATE Output Off−State Current	V_{IN} = V_{IH} or V_{IL} V_{OUT} = V_{CC} or GND		5.5	–	–	±0.25	–	±2.5	μA
I_{IN}	Input Leakage Current	V_{IN} = 5.5 V or GND		0–5.5	–	–	±0.1	–	±1.0	μA
I_{CC}	Quiescent Supply Current	V_{IN} = V_{CC} or GND		5.5	–	–	4.0	–	40.0	μA

NOISE CHARACTERISTICS

Symbol	Parameter	Conditions	V_{CC} (V)	T_A = 25°C		Unit
				Typ	Limits	
V_{OLP} (Note 5)	Quiet Output Maximum Dynamic V_{OL}	C_L = 50 pF	5.0	1.0	1.2	V
V_{OLV} (Note 5)	Quiet Output Minimum Dynamic V_{OL}	C_L = 50 pF	5.0	–0.8	–1.0	V
V_{IHD} (Note 5)	Minimum HIGH Level Dynamic Input Voltage	C_L = 50 pF	5.0	–	3.5	V
V_{ILD} (Note 5)	Maximum LOW Level Dynamic Input Voltage	C_L = 50 pF	5.0	–	1.5	V

5. Parameter guaranteed by design.

Share Feedback
Your Opinion Matters

AC ELECTRICAL CHARACTERISTICS

Symbol	Parameter	Conditions		V_{CC} (V)	T_A = 25°C			T_A = −40°C to +85°C		Unit
					Min	Typ	Max	Min	Max	
t_{PLH} t_{PHL}	Propagation Delay Time (CP to O_n)		C_L = 15 pF	3.3 ±0.3	−	8.5	13.2	1.0	15.5	ns
			C_L = 50 pF		−	11.0	16.7	1.0	19.0	
			C_L = 15 pF	5.0 ±0.5	−	5.6	8.6	1.0	10.0	ns
			C_L = 50 pF		−	7.1	10.6	1.0	12.0	
t_{PZL} t_{PZH}	3−STATE Output Enable Time	R_L = 1 kΩ	C_L = 15 pF	3.3 ±0.3	−	8.2	12.8	1.0	15.0	ns
			C_L = 50 pF		−	10.7	16.3	1.0	18.5	
			C_L = 15 pF	5.0 ±0.5	−	5.9	9.0	1.0	10.5	ns
			C_L = 50 pF		−	7.4	11.0	1.0	12.5	
t_{PLZ} t_{PHZ}	3−STATE Output Disable Time	R_L = 1 kΩ	C_L = 50 pF	3.3 ±0.3	−	11.0	15.0	1.0	17.0	ns
			C_L = 50 pF	5.0 ±0.5	−	7.1	10.1	1.0	11.5	
t_{OSLH} t_{OSHL}	Output to Output Skew	(Note 6)	C_L = 50 pF	3.3 ±0.3	−	−	1.5	−	1.5	ns
			C_L = 50 pF	5.0 ±0.5	−	−	1.0	−	1.0	
f_{MAX}	Maximum Clock Frequency		C_L = 15 pF	3.3 ±0.3	80	125	−	65	−	MHz
			C_L = 50 pF		50	75	−	45	−	
			C_L = 15 pF	5.0 ±0.5	130	180	−	110	−	
			C_L = 50 pF		85	115	−	75	−	
C_{IN}	Input Capacitance	V_{CC} = Open			−	4	10	−	10	pF
C_{OUT}	Output Capacitance	V_{CC} = 5.0 V			−	6	−	−	−	pF
C_{PD}	Power Dissipation Capacitance	(Note 7)			−	28	−	−	−	pF

6. Parameter guaranteed by design. $t_{OSLH} - |t_{PLH}$ max $- t_{PLH}$ min$|$; $t_{OSHL} - |t_{PHL}$ max $- t_{PHL}$ min$|$
7. C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation: I_{CC} (opr.) = C_{PD} x V_{CC} x f_{IN} + $I_{CC}/8$ (per F/F). The total C_{PD} when n pcs. of the Octal D Flip−Flop operates can be calculated by the equation: C_{PD} (total) = 20 + 8n.

AC OPERATING REQUIREMENTS

Symbol	Parameter	V_{CC} (V)	T_A = 25°C			T_A = −40°C to +85°C		Unit
			Min	Typ	Max	Min	Max	
$t_W(H)$ $t_W(L)$	Minimum Pulse Width (CP)	3.3 ±0.3	5.0	−	−	5.0	−	ns
		5.0 ±0.5	5.0	−	−	5.0	−	
t_S	Minimum Set−Up Time	3.3 ±0.3	3.5	−	−	3.5	−	ns
		5.0 ±0.5	3.5	−	−	3.5	−	
t_H	Minimum Hold Time	3.3 ±0.3	1.5	−	−	1.5	−	ns
		5.0 ±0.5	1.5	−	−	1.5	−	

ORDERING INFORMATION


Device	Marking	Package	Shipping†
74VHC574MTC	VHC 574	TSSOP20 (Pb−Free)	75 Units / Rail
74VHC574MTCX	VHC 574	TSSOP20 (Pb−Free)	2500 Units / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters


TSSOP20, 4.4x6.5
CASE 948AQ
ISSUE A

DATE 19 MAR 2009




TOP VIEW

SYMBOL	MIN	NOM	MAX
A			1.20
A1	0.05		0.15
A2	0.80		1.05
b	0.19		0.30
c	0.09		0.20
D	6.40	6.50	6.60
E	6.30	6.40	6.50
E1	4.30	4.40	4.50
e		0.65 BSC	
L	0.45	0.60	0.75
L1		1.00 REF	
θ	0°		8°



SIDE VIEW



END VIEW

Notes:
(1) All dimensions are in millimeters. Angles in degrees.
(2) Complies with JEDEC MO-153.

DOCUMENT NUMBER:	98AON34453E	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TSSOP20, 4.4X6.5	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales