35A, 800V Low V_F Standard Bridge Rectifier

FEATURES

- Glass passivated chip junction
- High case dielectric strength of 2500V_{RMS}
- High surge current capability
- UL Recognized File # E-326243
- RoHS Compliant
- Halogen-free

APPLICATIONS


- General purpose
- AC to DC
- Switching mode power supply (SMPS)

MECHANICAL DATA


- Case: TS-6P
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Polarity: As marked
- Weight: 6.43g (approximately)

KEY PARAMETERS		
PARAMETER	**VALUE**	**UNIT**
I_F	35	A
V_{RRM}	800	V
I_{FSM}	560	A
$T_{J\ MAX}$	150	°C
Package	TS-6P	
Circuit Configuration	In-line	

Pb-Free RoHS COMPLIANT HALOGEN FREE



TS-6P



ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)				
PARAMETER		**SYMBOL**	**VALUE**	**UNIT**
Repetitive peak reverse voltage		V_{RRM}	800	V
Reverse voltage, total rms value		$V_{R(RMS)}$	560	V
Forward current		I_F	35	A
Surge peak forward current, single half sine-wave superimposed on rated load per diode	t = 8.3ms	I_{FSM}	560	A
	t = 1.0ms		1000	
Rating for fusing (t<8.3ms)		I^2t	1301	A^2s
Junction temperature		T_J	- 55 to +150	°C
Storage temperature		T_{STG}	- 55 to +150	°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-lead thermal resistance	$R_{\Theta JL}$	1.1	°C/W
Junction-to-ambient thermal resistance	$R_{\Theta JA}$	6.6	°C/W
Junction-to-case thermal resistance	$R_{\Theta JC}$	0.8	°C/W

Thermal Performance Note: Mounted on Heat sink with 4" x 6" x 0.25" Al-plate

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)

PARAMETER	CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage per diode(1)	I_F = 17.5A, T_J = 25°C	V_F	0.90	0.92	V
	I_F = 17.5A, T_J = 125°C		0.80	-	V
Reverse current @ rated V_R per diode(2)	T_J = 25°C	I_R	-	5	μA
	T_J = 125°C		33	-	μA
Junction capacitance per diode	1MHz, V_R = 4.0V	C_J	200	-	pF

Notes:

1. Pulse test with PW = 0.3ms
2. Pulse test with PW = 30ms

ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
GBJ35KGLV	TS-6P	15 / Tube

CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Fig.1 Forward Current Derating Curve




Fig.2 Typical Junction Capacitance




Fig.3 Typical Reverse Characteristics




Fig.4 Typical Forward Characteristics







Fig.5 Typical Transient Thermal Impedance



PACKAGE OUTLINE DIMENSIONS

TS-6P





MARKING DIAGRAM

G = GREEN COMPOUND
YWW = DATE CODE
F = FACTORY CODE

NOTES: UNLESS OTHERWISE SPECIFIED

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.
3. THERE IS NO EXISTING PACKAGE OUTLINE INDUSTRY STANDARD FOR THIS PACKAGE.
4. MOLDED PLASTIC BODY DIMENSIONS DO NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS.
5. DWG NO. REF: HQ2SD07-TS6P_AM-142 REV B.

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.