4A, 200V - 600V Ultra Fast Surface Mount Rectifier

FEATURES

- Glass passivated chip junction
- Ideal for automated placement
- Ultra Fast recovery time for high efficiency
- Moisture sensitivity level: level 1, per J-STD-020
- RoHS Compliant
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- High frequency rectification
- Freewheeling application
- Switching mode converters and inverters in computer, and telecommunication

MECHANICAL DATA

- Case: DO-214AB (SMC)
- Molding compound meets UL 94V-0 flammability rating
- Terminal: Matte tin plated leads, solderable per J-STD-002
- Meet JESD 201 class 2 whisker test
- Polarity: Indicated by cathode band
- Weight: 0.250g (approximately)

KEY PARAMETERS		
PARAMETER	**VALUE**	**UNIT**
I_F	4	A
V_{RRM}	200 - 600	V
I_{FSM}	75	A
$T_{J\,MAX}$	175	°C
Package	DO-214AB (SMC)	
Configuration	Single die	

Pb-Free RoHS COMPLIANT HALOGEN FREE

DO-214AB (SMC)

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)					
PARAMETER	**SYMBOL**	**MUR420S**	**MUR440S**	**MUR460S**	**UNIT**
Marking code on the device		MUR420S	MUR440S	MUR460S	
Repetitive peak reverse voltage	V_{RRM}	200	400	600	V
Reverse voltage, total rms value	$V_{R(RMS)}$	140	280	420	V
Forward current	I_F	4			A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I_{FSM}	75			A
Junction temperature	T_J	- 55 to +175			°C
Storage temperature	T_{STG}	- 55 to +175			°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	TYP	UNIT
Junction-to-ambient thermal resistance	$R_{\Theta JA}$	45	°C/W
Junction-to-case thermal resistance	$R_{\Theta JC}$	8.5	°C/W

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)

PARAMETER		CONDITIONS	SYMBOL	TYP	MAX	UNIT
Forward voltage[1]	MUR420S	I_F = 4A, T_J = 25°C	V_F	-	0.875	V
	MUR440S MUR460S			-	1.250	V
	MUR420S	I_F = 4A, T_J = 150°C	V_F	-	0.710	V
	MUR440S MUR460S			-	1.050	V
Reverse current@ rated V_R[2]	MUR420S	T_J = 25°C	I_R	-	5	μA
	MUR440S MUR460S			-	10	μA
	MUR420S	T_J = 150°C	I_R	-	150	μA
	MUR440S MUR460S			-	250	μA
Junction capacitance		1MHz, V_R = 4.0V	C_J	65	-	pF
Reverse recovery time	MUR420S	I_F = 0.5A, I_R = 1.0A I_{rr} = 0.25A	t_{rr}	-	25	ns
	MUR440S MUR460S			-	50	ns

Notes:

1. Pulse test with PW = 0.3ms
2. Pulse test with PW = 30ms

ORDERING INFORMATION

ORDERING CODE[1]	PACKAGE	PACKING
MUR4xS	DO-214AB (SMC)	3,000 / Tape & Reel

Notes:

1. "x" defines voltage from 200V(MUR420S) to 600V(MUR460S)

CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Fig.1 Forward Current Derating Curve



Fig.2 Typical Junction Capacitance



Fig.3 Typical Reverse Characteristics



Fig.4 Typical Forward Characteristics



Fig.5 Maximum Non-Repetitive Forward Surge Current



CHARACTERISTICS CURVES

(T_A = 25°C unless otherwise noted)

Fig.6 Reverse Recovery Time Characteristic and Test Circuit Diagram



PACKAGE OUTLINE DIMENSIONS

DO-214AB (SMC)



DIM.	Unit (mm)		Unit (inch)	
	Min.	Max.	Min.	Max.
A	2.00	2.62	0.079	0.103
A1	0.10	0.20	0.004	0.008
b	2.90	3.20	0.114	0.126
c	0.15	0.31	0.006	0.012
D	5.59	6.22	0.220	0.245
E	7.75	8.13	0.305	0.320
E1	6.60	7.11	0.260	0.280
L	1.00	1.60	0.039	0.063

SUGGESTED PAD LAYOUT



Symbol	Unit (mm)	Unit (inch)
A	3.30	0.130
B	2.50	0.098
C	6.90	0.272
D	4.40	0.173
E	9.40	0.370

MARKING DIAGRAM

P/N = Marking Code
G = Green Compound
YW = Date Code
F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Purchasers are solely responsible for the choice, selection, and use of TSC products and TSC assumes no liability for application assistance or the design of Purchasers' products.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.