

Round 2 2015

- [A. Pegman](#)
- B. Kiddie Pool**
- [C. Bilingual](#)
- [D. Drum Decorator](#)

[Contest Analysis](#)
[Questions asked](#)

Submissions	
Pegman	
5pt	Not attempted 2225/2349 users correct (95%)
10pt	Not attempted 2195/2237 users correct (98%)
Kiddie Pool	
7pt	Not attempted 1503/2051 users correct (73%)
18pt	Not attempted 290/709 users correct (41%)
Bilingual	
6pt	Not attempted 955/1564 users correct (61%)
24pt	Not attempted 169/257 users correct (66%)
Drum Decorator	
11pt	Not attempted 208/558 users correct (37%)
19pt	Not attempted 56/88 users correct (64%)

Top Scores	
Gennady.Korotkevich	100
peter50216	100
rng..58	100
ZhukovDmitry	100
hos.lyric	100
semiexp.	100
iwi	100
tkociumaka	100
eatmore	100
EgorKulikov	100

Problem B. Kiddie Pool

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input
7 points

Solve B-small

Large input
18 points

Solve B-large

Problem

A kiddie pool is a big container in which you can put water, so that small children can play in it.

You have access to N different sources of water. The i^{th} source of water produces water at rate R_i and at temperature C_i . Initially, all of the water sources are off. Each source of water can be switched on only once, and switched off only once; the act of switching a source on or off takes no additional time. Multiple sources can be on at the same time.

Your pool can hold an infinite amount of water, but you want to fill the pool to a volume of exactly V with a temperature of exactly X , as quickly as possible. If you turn sources on and off optimally (not every source necessarily has to be used), what's the minimum number of seconds it will take you to do this?

For the purposes of this problem, combining water that has volume V_0 and temperature X_0 with water that has volume V_1 and temperature X_1 will **instantaneously** create water with volume V_0+V_1 and temperature $(V_0X_0 + V_1X_1) / (V_0 + V_1)$. For example, combining 5L of water at 10 degrees with 10L of water at 40 degrees will result in 15L of water at 30 degrees. You should also assume that water does not heat or cool over time except as a result of being combined with other water.

Input

The first line of the input gives the number of test cases, T . T test cases follow. The first line of each test case contains three space-separated numbers: an integer N , and real numbers V and X as described above.

The next N lines each contain two space-separated real numbers, R_i and C_i , the rate of flow and temperature of the i^{th} water source respectively. The volume is expressed in liters, rates of flow are expressed in liters per second, and temperatures are expressed in degrees Celsius.

All real numbers will be exactly specified to four decimal places.

Output

For each test case, output one line containing "Case #x: y", where x is the test case number (starting from 1) and y is the minimum number of seconds it takes to fill the kiddie pool to the right volume and temperature. If it is impossible to do so given the inputs, y should be the string IMPOSSIBLE.

y will be considered correct if it is within an absolute or relative error of 10^{-6} of the correct answer. See the [FAQ](#) for an explanation of what that means, and what formats of real numbers we accept. You can also read there about the format of our input real numbers, in which the decimal point will be represented by the . character.

Limits

$1 \leq T \leq 100.$
 $0.1 \leq X \leq 99.9.$
 $0.1 \leq C_i \leq 99.9.$

Small dataset

$1 \leq N \leq 2.$
 $0.0001 \leq V \leq 100.0.$
 $0.0001 \leq R_i \leq 100.0.$

Large dataset

$1 \leq N \leq 100.$
 $0.0001 \leq V \leq 10000.0.$
 $0.0001 \leq R_i \leq 10000.0.$

Sample

Input	Output
6	Case #1: 50.0000000
1 10.0000 50.0000	Case #2: 207221.843687375
0.2000 50.0000	Case #3: IMPOSSIBLE
2 30.0000 65.4321	Case #4: 0.500000000
0.0001 50.0000	Case #5: 1.428034895
100.0000 99.9000	Case #6: 18.975332068
2 5.0000 99.9000	
30.0000 99.8999	
20.0000 99.7000	
2 0.0001 77.2831	
0.0001 97.3911	
0.0001 57.1751	
2 100.0000 75.6127	
70.0263 75.6127	
27.0364 27.7990	
4 5000.0000 75.0000	
10.0000 30.0000	
20.0000 50.0000	
300.0000 95.0000	
40.0000 2.0000	

Note that Case #6 is not within the limits for the Small dataset.

In Case #1, the one available source happens to be the exact temperature we need. The optimal strategy is to immediately turn it on and let it run until we have 10 L. Since 0.2 L will come out every second, this takes 50 seconds.

In Case #2, one optimal strategy is to turn on the first source and let it run for 207221.843687375 seconds, and then, about 0.092778156 seconds before the end, also turn on the second source.

In Case #3, both available water sources are cooler than the target temperature, so there is no way to reach it.

All problem statements, input data and contest analyses are licensed under the [Creative Commons Attribution License](#).

© 2008-2017 Google [Google Home](#) - [Terms and Conditions](#) - [Privacy Policies and Principles](#)

Powered by



Google Cloud Platform