

Round E APAC Test 2016

A. Lazy Spelling Bee

[B. Robot Rock Band](#)

[C. Not So Random](#)

[D. Sums of Sums](#)

[Questions asked](#)

Submissions

Lazy Spelling Bee

5pt	Not attempted 613/697 users correct (88%)
8pt	Not attempted 539/608 users correct (89%)

Robot Rock Band

6pt	Not attempted 551/580 users correct (95%)
14pt	Not attempted 301/474 users correct (64%)

Not So Random

11pt	Not attempted 340/366 users correct (93%)
20pt	Not attempted 124/201 users correct (62%)

Sums of Sums

8pt	Not attempted 447/490 users correct (91%)
28pt	Not attempted 17/102 users correct (17%)

Top Scores

NAFIS	100
gvaibhav21	100
codecracker4	100
shivar31	100
harshil7924	100
aniket20	100
triveni692	100
sgtlaugh	100
gsa	100
ctzsm	100

Problem A. Lazy Spelling Bee

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input
5 points

Solve A-small

Large input
8 points

Solve A-large

Problem

In the Lazy Spelling Bee, a contestant is given a target word W to spell. The contestant's answer word A is acceptable if it is the same length as the target word, and the i -th letter of A is either the i -th, $(i-1)$ th, or $(i+1)$ th letter of W , for all i in the range of the length of A . (The first letter of A must match either the first or second letter of W , since the 0th letter of W doesn't exist. Similarly, the last letter of A must match either the last or next-to-last letter of W .) Note that the target word itself is always an acceptable answer word.

You are preparing a Lazy Spelling Bee, and you have been asked to determine, for each target word, how many distinct acceptable answer words there are. Since this number may be very large, please output it modulo 1000000007 ($10^9 + 7$).

Input

The first line of the input gives the number of test cases, T . T test cases follow; each consists of one line with a string consisting only of lowercase English letters (a through z).

Output

For each test case, output one line containing "Case #x: y", where x is the test case number (starting from 1) and y is the number of distinct acceptable answer words, modulo $10^9 + 7$.

Limits

$1 \leq T \leq 100$.

Small dataset

$1 \leq \text{length of each string} \leq 5$.

Large dataset

$1 \leq \text{length of each string} \leq 1000$.

Sample

Input	Output
4	Case #1: 4
ag	Case #2: 1
aa	Case #3: 108
abcde	Case #4: 1
x	

In sample case #1, the acceptable answer words are aa, ag, ga, and gg.

In sample case #2, the only acceptable answer word is aa.

Powered by



Google Cloud Platform

Round E APAC Test 2016

[A. Lazy Spelling Bee](#)

B. Robot Rock Band

[C. Not So Random](#)

[D. Sums of Sums](#)

[Questions asked](#)

Submissions

Lazy Spelling Bee

5pt	Not attempted 613/697 users correct (88%)
8pt	Not attempted 539/608 users correct (89%)

Robot Rock Band

6pt	Not attempted 551/580 users correct (95%)
14pt	Not attempted 301/474 users correct (64%)

Not So Random

11pt	Not attempted 340/366 users correct (93%)
20pt	Not attempted 124/201 users correct (62%)

Sums of Sums

8pt	Not attempted 447/490 users correct (91%)
28pt	Not attempted 17/102 users correct (17%)

Top Scores

NAFIS	100
gvaibhav21	100
codecracker4	100
shivari31	100
harshil7924	100
aniket20	100
triveni692	100
sgtlaugh	100
gsa	100
ctzsm	100

Problem B. Robot Rock Band

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input
6 points

Solve B-small

Large input
14 points

Solve B-large

Problem

You're the manager of Xorbitant, the world's first robot rock band. There will be four positions in the band, and there are N robots auditioning for each position. (No robot is auditioning for more than one position.) Every robot has a number, and multiple robots might have the same number, just as two people can have the same name.

You know from market research that your robot audiences won't care how well the robot band members make music, how handsome they are, or what scandalous things the tabloids say about them. Instead, the audience will be checking to see whether the four members' numbers, when bitwise XORed together, equal a certain trendy number K .

How many different sets of four robots (one for each position) is it possible to choose so that the band will have this property? More specifically, given four lists A, B, C, D containing N numbers each, how many ways are there to choose one number a from list A , one number b from list B , and so on, such that $a \oplus b \oplus c \oplus d = K$? (Here \oplus represents the bitwise XOR operation.)

Input

The first line of the input gives the number of test cases, T . T test cases follow. Each case begins with one line with two space-separated integers, N and K , as described above. Then, four more lines follow. Each has N space-separated integers and represents the ID numbers of the robots auditioning for a certain position in the band.

Output

For each test case, output one line containing "Case #x: y", where x is the test case number (starting from 1) and y is the number of different bands that meet the conditions.

Limits

$1 \leq T \leq 10$.
 $0 \leq K \leq 10^9$.
 $0 \leq \text{all robot numbers} \leq 10^9$.

Small dataset

$1 \leq N \leq 50$.

Large dataset

$1 \leq N \leq 1000$.

Sample

Input	Output
2	Case #1: 4
2 3	Case #2: 8
0 0	
2 0	
0 0	
0 1	
2 0	
1 10	
1 10	
1 10	
1 10	

In sample case #1, in order to get a combined bitwise XOR of 3, the robot chosen from the second list must be 2, and the robot chosen from the fourth list must be 1. For the first and third lists, either of the two 0 robots can be chosen, so there are $2 * 2 = 4$ possible bands that meet the criteria. Note that

even though all of these bands are of the form $(0, 2, 0, 1)$, they are considered different because the selections from the lists were different.

All problem statements, input data and contest analyses are licensed under the [Creative Commons Attribution License](#).

© 2008-2017 Google [Google Home](#) - [Terms and Conditions](#) - [Privacy Policies and Principles](#)

Powered by



Google Cloud Platform

Round E APAC Test 2016

[A. Lazy Spelling Bee](#)

[B. Robot Rock Band](#)

C. Not So Random

[D. Sums of Sums](#)

[Questions asked](#)

Submissions

Lazy Spelling Bee

5pt	Not attempted 613/697 users correct (88%)
8pt	Not attempted 539/608 users correct (89%)

Robot Rock Band

6pt	Not attempted 551/580 users correct (95%)
14pt	Not attempted 301/474 users correct (64%)

Not So Random

11pt	Not attempted 340/366 users correct (93%)
20pt	Not attempted 124/201 users correct (62%)

Sums of Sums

8pt	Not attempted 447/490 users correct (91%)
28pt	Not attempted 17/102 users correct (17%)

Top Scores

NAFIS	100
gvaibhav21	100
codecracker4	100
shivari31	100
harshil7924	100
aniket20	100
triveni692	100
sgtlaugh	100
gsa	100
ctzsm	100

Problem C. Not So Random

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input
11 points

Solve C-small

Large input
20 points

Solve C-large

Problem

There is a certain "random number generator" (RNG) which takes one nonnegative integer as input and generates another nonnegative integer as output. But you know that the RNG is really not very random at all! It uses a fixed number **K**, and always performs one of the following three operations:

- with probability **A**/100: return the bitwise AND of the input and **K**
- with probability **B**/100: return the bitwise OR of the input and **K**
- with probability **C**/100: return the bitwise XOR of the input and **K**

(You may assume that the RNG *is* truly random in the way that it chooses the operation each time, based on the values of **A**, **B**, and **C**.)

You have **N** copies of this RNG, and you have arranged them in series such that output from one machine will be the input for the next machine in the series. If you provide **X** as an input to the first machine, what will be the expected value of the output of the final machine in the series?

Input

The first line of the input gives the number of test cases, **T**. **T** test cases follow; each consists of one line with six integers **N**, **X**, **K**, **A**, **B**, and **C**. Respectively, these denote the number of machines, the initial input, the fixed number with which all the bitwise operations will be performed (on every machine), and 100 times the probabilities of the bitwise AND, OR, and XOR operations.

Output

For each test case, output one line containing "Case #x: y", where x is the test case number (starting from 1) and y is the expected value of the final output. y will be considered correct if it is within an absolute or relative error of 10^{-9} of the correct answer. See the [FAQ](#) for an explanation of what that means, and what formats of real numbers we accept.

Limits

$1 \leq T \leq 50$.
 $0 \leq A \leq 100$.
 $0 \leq B \leq 100$.
 $0 \leq C \leq 100$.
 $A+B+C = 100$.

Small dataset

$1 \leq N \leq 10$.
 $0 \leq X \leq 10^4$.
 $0 \leq K \leq 10^4$.

Large dataset

$1 \leq N \leq 10^5$.
 $0 \leq X \leq 10^9$.
 $0 \leq K \leq 10^9$.

Sample

Input	Output
3	Case #1: 3.0000000000
1 5 5 10 50 40	Case #2: 3.6000000000
2 5 5 10 50 40	Case #3: 15.6850579098
10 15 21 70 20 10	

In sample test case #1, the final output will be 5 if AND or OR happens and 0 if XOR happens. So the probability of getting 5 is $(0.1 + 0.5)$ and the probability

of getting 0 is 0.4. So the expected final output is $5 * 0.6 + 0 * 0.4 = 3$.

In sample test case #2, the final output will be 5 with probability 0.72, and 0 otherwise.

All problem statements, input data and contest analyses are licensed under the [Creative Commons Attribution License](#).

© 2008-2017 Google [Google Home](#) - [Terms and Conditions](#) - [Privacy Policies and Principles](#)

Powered by



Google Cloud Platform

Round E APAC Test 2016

[A. Lazy Spelling Bee](#)

[B. Robot Rock Band](#)

[C. Not So Random](#)

D. Sums of Sums

[Questions asked](#)

Submissions

Lazy Spelling Bee

5pt Not attempted
613/697 users
correct (88%)

8pt Not attempted
539/608 users
correct (89%)

Robot Rock Band

6pt Not attempted
551/580 users
correct (95%)

14pt Not attempted
301/474 users
correct (64%)

Not So Random

11pt Not attempted
340/366 users
correct (93%)

20pt Not attempted
124/201 users
correct (62%)

Sums of Sums

8pt Not attempted
447/490 users
correct (91%)

28pt Not attempted
17/102 users
correct (17%)

Top Scores

NAFIS	100
gvaibhav21	100
codecracker4	100
shivar31	100
harshil7924	100
aniket20	100
triveni692	100
sgtlaugh	100
gsa	100
ctzsm	100

Problem D. Sums of Sums

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input
8 points

Solve D-small

Large input
28 points

Solve D-large

Problem

Alice presented her friend Bob with an array of N positive integers, indexed from 1 to N . She challenged Bob with many queries of the form "what is the sum of the numbers between these two indexes?" But Bob was able to solve the problem too easily.

Alice took her array and found all $N*(N+1)/2$ non-empty subarrays of it. She found the sum of each subarray, and then sorted those values (in nondecreasing order) to create a new array, indexed from 1 to $N*(N+1)/2$. For example, for an initial array [2, 3, 2], Alice would generate the subarrays [2], [3], [2], [2, 3], [3, 2], and [2, 3, 2] (note that [2, 2], for example, is **NOT** a subarray). Then she'd take the sums -- 2, 3, 2, 5, 5, 7 -- and sort them to get a new array of [2, 2, 3, 5, 5, 7].

Alice has given the initial array to Bob, along with Q queries of the form "what is the sum of the numbers from index L_i to R_i , inclusive, in the new array?" Now Bob's in trouble! Can you help him out?

Input

The first line of the input gives the number of test cases, T . T test cases follow. Each test case begins with one line with two space-separated integers N and Q , denoting the number of elements in the initial array and the number of Alice's queries. Then, there is one line with N space-separated integers, denoting the elements of Alice's initial array. Finally, there are Q more lines with two space-separated integers each: L_i and R_i , the inclusive index bounds for the i -th query.

Output

For each test case, output one line with Case # x :, where x is the test case number (starting from 1). Then output Q more lines, each with one integer, representing the answers to the queries (in the order they were asked).

Limits

$1 \leq T \leq 10$.
 $1 \leq Q \leq 20$.
 $1 \leq$ each element of the initial array ≤ 100 .
 $1 \leq L_i \leq R_i \leq N*(N+1)/2$.

Small dataset

$1 \leq N \leq 10^3$.

Large dataset

$1 \leq N \leq 200000$.

Sample

Input	Output
1	Case #1:
5 5	1
5 4 3 2 1	45
1 1	105
1 10	26
1 15	48
3 8	
4 11	

In sample case #1, Alice's new array would be: [1, 2, 3, 3, 4, 5, 5, 6, 7, 9, 9, 10, 12, 14, 15].

All problem statements, input data and contest analyses are licensed under the [Creative Commons Attribution License](#).

© 2008-2017 Google [Google Home](#) - [Terms and Conditions](#) - [Privacy Policies and Principles](#)

Powered by



Google Cloud Platform