

AMER Semifinal 2008

[A. Mixing Bowls](#)**B. Code Sequence**[C. Test Passing Probability](#)[D. King](#)[Contest Analysis](#)[Questions asked](#)

Submissions

Mixing Bowls

5pt	Not attempted 84/92 users correct (91%)
9pt	Not attempted 71/81 users correct (88%)

Code Sequence

7pt	Not attempted 15/21 users correct (71%)
15pt	Not attempted 5/16 users correct (31%)

Test Passing Probability

5pt	Not attempted 59/64 users correct (92%)
14pt	Not attempted 25/37 users correct (68%)

King

7pt	Not attempted 82/94 users correct (87%)
38pt	Not attempted 0/10 users correct (0%)

Top Scores

Bohua	62
SkidanovAlexander	62
radeye	62
linguo	53
andersk	47
Reid	47
antimatter	47
ploh	47
fuwenjie	47
pmnox	40

Problem B. Code Sequence

This contest is open for practice. You can try every problem as many times as you like, though we won't keep track of which problems you solve. Read the [Quick-Start Guide](#) to get started.

Small input
7 points

Solve B-small

Large input
15 points

Solve B-large

Problem

You are trying to compute the next number in a sequence S_n generated by a secret code. You know that the code was generated according to the following procedure.

First, for each k between 0 and 29, choose a number C_k between 0 and 10006 (inclusive).

Then, for each integer n between 0 and 1 000 000 000 (inclusive):

- Write n in binary.
- Take the numbers C_k for every bit k that is set in the binary representation of n . For example, when $n=5$, bits 0 and 2 are set, so C_0 and C_2 are taken.
- Add these C_k together, divide by 10007, and output the remainder as S_n .

You will be given a series of consecutive values of sequence S , but you don't know at which point in the sequence your numbers begin (although you do know that there is at least one more number in the sequence), and you don't know what values of C_k were chosen when the sequence was generated.

Find the next number in the sequence, or output UNKNOWN if this cannot be determined from the input data.

Input

The first line will contain an integer T , the number of test cases in the input file.

For each test case, there will be:

- One line containing the integer N , the number of elements of sequence S that you have.
- One line containing N single-space-separated integers between 0 and 10006, the known elements of the sequence.

Output

For each test case, output one line containing "Case # X : Y " where X is the number of the test case, starting from 1, and Y is the next number in the sequence, or the string UNKNOWN if the next number cannot be determined.

Limits

$$1 \leq T \leq 20$$

Small dataset

$$1 \leq N \leq 5$$

Large dataset

$$1 \leq N \leq 1000$$

Sample

Input	Output
3	Case #1: UNKNOWN
7	Case #2: 201
1 2 3 4 5 6 7	Case #3: 3514
4	
1 10 11 200	
4	
1000 1520 7520 7521	

In the first case, C_0 , C_1 and C_2 might have been 1, 2 and 4, and the values of

S_n we have starting at $n=1$. If this is correct, we don't know C_3 , so the next number in the sequence could be anything! Therefore the answer is unknown.

In the second case, we cannot know all the values of C_k or even what n is, but we can prove that in any sequence, if 1, 10, 11, 200 occur in order, then the next value will always be 201.

All problem statements, input data and contest analyses are licensed under the [Creative Commons Attribution License](#).

© 2008-2017 Google [Google Home](#) - [Terms and Conditions](#) - [Privacy Policies and Principles](#)

Powered by



Google Cloud Platform