

TriageNG

Complete User Manual

Step-by-step installation, incident handling, administration, offline operation, integrations, reporting, and troubleshooting.

Version: Local development edition

Prepared: 25 August 2026

Audience: Reporters, Analysts, Senior Analysts, Administrators, Auditors, and technical operators

Read less. Detect faster. Respond smarter.

How to use this manual

This manual begins before installation and finishes with shutdown, backup, verification, and troubleshooting. Follow the numbered steps in order during your first use. Later, use the screen-by-screen sections as a reference.

Important: TriageNG is an independent product. It is not a Nigerian government service and does not claim affiliation with ngCERT, NCCC, NITDA, or another public authority.

Reading conventions

Convention	Meaning
Button names	Shown in bold, for example Submit report.
Code blocks	Commands to type exactly in PowerShell or a terminal.
Local reference	A temporary report identifier created before synchronization.
Incident reference	The permanent TNG reference created by the server.
Human approval	A required analyst or senior-analyst decision. AI recommendations do not approve actions.

Table of contents

1. Product overview and roles
 2. Requirements and preparation
 3. First-time Windows installation
 4. First-time macOS or Linux installation
 5. Starting, opening, and stopping TriageNG
 6. Interface orientation
 7. Submit a public incident report
 8. Work offline and synchronize
 9. Use the Incident Queue
 10. Complete the incident triage workspace
 11. Manage clusters
 12. Use analytics, Judge Mode, and management reports
 13. Approve routing and deliveries
 14. Configure integrations and providers
 15. Notifications and Audit Log
 16. Users and roles
 17. Settings, Help, accessibility, and PWA installation
 18. Data, privacy, evidence, and security
 19. Exports, readiness evidence, and model evaluation
 20. Backup, reset, update, and maintenance
 21. Troubleshooting
 22. Complete start-to-finish operating checklist
- Appendices: status, severity, formats, commands, API map

1. Product overview and roles

What TriageNG does

TriageNG receives cyber incident reports in English or Nigerian Pidgin, extracts privacy-reduced text and indicators, recommends a category and severity, groups related reports, supports analyst review, records decisions, tracks service-level targets, and routes approved incident summaries to controlled destinations.

The end-to-end lifecycle

Stage	Operator	Result
Report	Reporter or analyst	A report and optional evidence are accepted.
Extract	System, then analyst	OCR/text extraction, indicators, redaction, and limitations are shown.
Classify	System, then analyst	Category, severity, route, confidence, and rationale are reviewed.
Assign	Senior Analyst	An owner and SLA are recorded.
Investigate	Analyst	Notes, related reports, privacy review, and corrections are documented.
Route	Senior Analyst	A privacy-reduced payload is approved and delivered.
Close	Analyst or Senior Analyst	Resolution summary and closure reason are recorded.
Audit	Auditor or authorized operator	The immutable activity trail is reviewed or exported.

Roles

Role	Typical permissions
Reporter	Create and track an authorized report; cannot approve internal decisions.
Analyst	Review incidents, evidence, OCR, indicators, privacy controls, and notes.
Senior Analyst	Analyst access plus assignment, routing approval, escalation, closure, and reopening.
Administrator	Manage users, roles, settings, integrations, providers, and routing rules.
Auditor	Read audit and reporting evidence with limited operational changes.

Warning: The local development identity is a Senior Analyst so the full workflow can be tested. Do not treat local development access as a production authentication design.

2. Requirements and preparation

Required software

- Windows 10/11, macOS, or a modern Linux distribution.
- Node.js 22.13 or newer. Node 22 LTS is recommended.
- npm 10 or newer.
- A current Chrome, Edge, Firefox, or Safari browser.
- Python 3.10 or newer only if you will retrain or reevaluate the model.

Check installed versions

Step 1. Open PowerShell on Windows, or Terminal on macOS/Linux.

Step 2. Run the version commands below.

```
node --version  
npm --version  
python --version
```

Step 3. Confirm Node is at least 22.13 and npm is at least 10.

Step 4. If a command is not recognized, install the missing software and reopen the terminal.

Protect local secrets

Warning: Never publish, email, or commit the .dev.vars file. Integration tokens and secrets may be stored there.

3. First-time Windows installation

Step 1. Locate the project folder. The supplied local path is C:\Users\pc\Desktop\TriageNG.

Step 2. Open PowerShell. You may right-click inside the project folder and choose Open in Terminal.

Step 3. Change to the project folder.

```
cd C:\Users\pc\Desktop\TriageNG
```

Step 4. Create the local environment file from the safe example.

```
Copy-Item local.env.example .dev.vars
```

Step 5. Open .dev.vars and confirm TRIAGENG_LOCAL_DEV=true is present. Leave optional provider values empty until needed.

Step 6. Install the locked JavaScript dependencies.

```
npm.cmd install
```

Step 7. Create or migrate the local D1 database and local storage bindings.

```
npm.cmd run local:setup
```

Step 8. Start TriageNG.

```
npm.cmd run dev
```

Step 9. Wait for the terminal to print a localhost address. Normally it is http://localhost:5173.

Step 10. Keep the PowerShell window open while using the software.

Important: Use npm.cmd on Windows. This bypasses the npm.ps1 execution-policy error without weakening the PowerShell execution policy.

4. First-time macOS or Linux installation

Step 1. Open Terminal and change to the extracted TriageNG project folder.

Step 2. Create the local environment file.

```
cp local.env.example .dev.vars
```

Step 3. Confirm TRIAGENG_LOCAL_DEV=true inside .dev.vars.

Step 4. Install dependencies.

```
npm install
```

Step 5. Prepare the local database and storage.

```
npm run local:setup
```

Step 6. Start the application.

```
npm run dev
```

Step 7. Open the localhost address printed in the terminal.

5. Starting, opening, and stopping TriageNG

Start after the first installation

Step 1. Open a terminal in the TriageNG folder.

Step 2. Run `npm.cmd run dev` on Windows or `npm run dev` on macOS/Linux.

Step 3. Open `http://localhost:5173`. If the port is busy, open the alternative address printed by Vite.

Confirm the system is ready

Step 1. Confirm the header shows Online.

Step 2. Open Overview and confirm metric cards appear.

Step 3. Open Incident Queue and confirm it loads rather than showing an authorization or database error.

Step 4. If needed, inspect local Cloudflare services at `http://localhost:5174/cdn-cgi/explorer/api`.

Stop safely

Step 1. Finish or save any text being entered. Analyst-note drafts are stored locally, but explicit saves are safer.

Step 2. Return to the terminal running TriageNG.

Step 3. Press `Ctrl+C` once.

Step 4. Wait for the prompt to return before closing the terminal.

6. Interface orientation




Figure 1. Desktop Overview with institutional header, grouped navigation, metrics, and activity panels.

Global controls

Control	How to use it
Skip to main content	Press Tab immediately after page load, then Enter to bypass navigation.
TriageNG brand	Returns to Overview.
Grouped sidebar	Choose Operations, Intelligence, Administration, or Support destinations.
Collapse sidebar	Reduces the desktop sidebar while retaining navigation icons/labels as designed.
Menu	On mobile, opens the navigation drawer. Escape closes it.
Connection status	Shows whether the browser is online. Offline reports remain device-local until sync.
Global search	Searches the available incident workspace data when supported by the current screen.

Every screen

Group	Screens
Operations	Overview, Incident Queue, Submit Report, Offline Queue
Intelligence	Incident Clusters, Analytics, Judge Mode, Management Reports
Coordination	Routing Centre, Integration Centre, Notifications
Administration	Audit Log, Users & Roles, Settings
Support	Help & Guidance

7. Submit a public incident report

The screenshot displays the 'Secure Public Reporting Portal' for TriageNG. The main heading is 'Report a cyber incident'. Below this, a section titled 'Submit an incident report' provides instructions: 'Tell us what you noticed. English or Nigerian Pidgin is fine.' The form is divided into several sections: 1. 'Describe' (Title), 2. 'Describe' (Description), 3. 'What happened?' (Narrative), 4. 'Affected system' and 'Department' (Dropdowns), and 5. 'Screenshots or file' (File upload). A 'Continue to review' button is at the bottom of the form. The sidebar on the left lists various navigation options under 'All Security Operations' and 'Intelligence'. The footer contains the TriageNG logo, a 'Privacy policy' link, and a 'Service' link.

Figure 2. Public reporting portal with reporting guidance and incident form.

Before you begin

- Prepare a factual description: what happened, when it began, affected systems, and current impact.
- Remove passwords, private keys, bank PINs, and unrelated personal records.
- Prepare supported evidence if needed: PNG, JPG, PDF, or TXT, maximum 10 MB per accepted upload.

Submit while online

Step 1. Select Submit Report in the sidebar.

Step 2. Choose English or Nigerian Pidgin when a language choice is available.

Step 3. Enter the incident title. Make it short and specific, for example Suspected payroll phishing emails.

Step 4. Enter the report description. Include observed behavior, timestamps, impacted assets, sender addresses, URLs, domains, IPs, or hashes when known.

Step 5. Enter reporter or institution contact details only in the fields provided. Do not add unnecessary personal data to the narrative.

Step 6. Select or attach evidence if available. Confirm the file type and size are allowed.

Step 7. Review the independence and privacy notice.

Step 8. Select Submit report once. Do not double-click.

Step 9. Wait for the confirmation screen and record the TNG incident reference.

Step 10. If attachments are being processed, wait for the extraction/privacy result before leaving the workflow.

What happens automatically

- The report is stored in D1 with a permanent reference.
- Evidence bytes are stored separately in R2; database records hold metadata and processing state.
- Text, URLs, domains, IP addresses, and hashes may be extracted.
- Email addresses, phone numbers, institutional IDs, and numeric IDs are masked in privacy-reduced text.
- An explainable classification recommendation is produced for analyst review.

Warning: A recommendation is not a final verdict. An authorized analyst must review the evidence, confidence, limitations, and privacy-reduced text.

8. Work offline and synchronize

Figure 3. Mobile reporting form, optimized for narrow screens and offline-capable use.

Create a report without a connection

- Step 1.** Open TriageNG before losing connectivity so the application shell is available on the device.
- Step 2.** When the connection status shows Offline, open Submit Report.
- Step 3.** Complete the report exactly as an online report.
- Step 4.** Select Submit report.
- Step 5.** Record the TNG-LOCAL reference shown. The report is saved in IndexedDB on this device.
- Step 6.** Open Offline Queue and confirm the pending record appears.

Synchronize

- Step 1.** Reconnect the device to the internet or local development network.
- Step 2.** Keep TriageNG open until the status changes to Online.
- Step 3.** Open Offline Queue and select the synchronization action if it has not started automatically.
- Step 4.** Wait until the pending count decreases and the permanent incident reference is shown.
- Step 5.** Open Incident Queue and verify the synchronized incident.
- Step 6.** If synchronization stops after an error, correct the connection/server problem and retry. The process safely stops on the first failure.

Important: External routing is never executed directly from the offline queue. Routing still requires an online, human-approved action.

9. Use the Incident Queue

Load and filter the queue

Step 1. Select Incident Queue.

Step 2. Wait for the table or cards to load.

Step 3. Use search and filters to narrow by reference, title, category, severity, status, owner, or other available criteria.

Step 4. Review SLA and escalation indicators before selecting work.

Step 5. Open the incident reference or row to enter the triage workspace.

Recommended triage order

Priority	Action
1	Critical or High incidents with active operational impact.
2	Overdue or nearly overdue SLA records.
3	Reports containing actionable indicators or confirmed compromise.
4	Unassigned incidents and low-confidence classifications requiring human review.
5	Duplicates, related reports, and routine low-severity cases.

Status handling

- New: accepted but not yet fully reviewed.
- In review: actively analyzed or assigned.
- Pending: waiting for information, evidence, or an external response.
- Routed: an approved privacy-reduced payload has been sent or queued.
- Closed: a resolution summary and closure decision are recorded.
- Reopened: new facts require renewed investigation.

10. Complete the incident triage workspace




Figure 4. Three-panel incident workspace for report review, analysis, indicators, privacy, and actions.

10.1 Read the report

- Step 1.** Verify the incident reference, created time, language, reporter context, and current status.
- Step 2.** Read the original narrative and extracted evidence text.
- Step 3.** Check attachment names, file sizes, extraction state, OCR confidence, and page limits.
- Step 4.** Treat unexpected files and URLs as potentially hostile. Do not open or execute unknown content outside approved analysis controls.

10.2 Review the AI recommendation

- Step 1.** Read the proposed category, severity, route, and confidence score.
- Step 2.** Read the listed evidence and limitations. Low confidence or sparse evidence requires extra caution.
- Step 3.** Compare the recommendation with the original report and indicators.
- Step 4.** Accept the recommendation only when supported by the evidence.
- Step 5.** To correct it, choose the correct category/severity/route, enter the required rationale, and save. The correction is audited.

10.3 Review privacy redaction

- Step 1.** Compare original and privacy-reduced text.
- Step 2.** Confirm email addresses, phone numbers, institutional IDs, and numeric IDs are masked where appropriate.
- Step 3.** Check that security indicators needed for response were not accidentally destroyed.
- Step 4.** Correct the redacted text if authorized and required.

Step 5. Select Approve privacy review only after the comparison is complete.

10.4 Review indicators

Step 1. Inspect extracted URLs, domains, IP addresses, and hashes.

Step 2. Remove false positives only with a reason or note.

Step 3. Use approved threat-intelligence providers from the Integration Centre when configured.

Step 4. Do not infer maliciousness solely from an indicator appearing in a report.

10.5 Related reports and clusters

Step 1. Review suggested related incidents and the grouping explanation.

Step 2. Compare overlapping indicators, affected institutions, time windows, and tactics.

Step 3. Confirm or reject the relationship according to your operating procedure.

10.6 Assign an owner and SLA

Step 1. Select the assignment control.

Step 2. Choose an authorized analyst.

Step 3. Set or confirm the SLA appropriate to severity.

Step 4. Save and verify the owner and deadline are visible.

Step 5. Use escalation only when required. Escalation creates an audit event and notification.

10.7 Analyst notes

Step 1. Enter concise, factual notes with timestamps or sources where useful.

Step 2. Avoid unnecessary personal data.

Step 3. Save the note. Draft text is also retained locally per incident, but the explicit save is the official action.

10.8 Close or reopen

Step 1. Before closure, confirm classification, privacy review, ownership, routing state, and required evidence are complete.

Step 2. Select Close incident.

Step 3. Enter the required closure reason and resolution summary.

Step 4. Confirm closure and verify status changes to Closed.

Step 5. To reopen, select Reopen, enter the mandatory reason and new evidence/context, then confirm.

11. Manage incident clusters

Step 1. Open Incident Clusters.

Step 2. Select a cluster and review its time range, common indicators, categories, institutions, and incident count.

Step 3. Open representative incidents to validate the grouping.

Step 4. Read the grouping explanation; similarity is assistance, not proof of a shared campaign.

Step 5. Document a human conclusion in incident or management notes.

Step 6. Use the cluster view to coordinate analysis, not to mass-route or mass-close incidents without individual review.

12. Analytics, Judge Mode, and management reports

Analytics

Step 1. Open Analytics.

Step 2. Choose the available time range and filters.

Step 3. Review volumes, categories, severities, SLA performance, routing, and trends.

Step 4. Treat small samples and synthetic evaluation metrics cautiously.

Judge Mode

Step 1. Open Judge Mode to view consolidated evidence intended for product or evaluation review.

Step 2. Review the product workflow, model evidence, offline behavior, privacy controls, routing gate, and readiness information.

Step 3. Download supporting evidence only if you are authorized to handle it.

Management Reports

Step 1. Open Management Reports.

Step 2. Select the reporting period and available scope.

Step 3. Review aggregate operational figures and caveats.

Step 4. Export the report where available.

Step 5. Protect exported files as operational security records.

13. Approve routing and deliveries

Routing Centre

Step 1. Open Routing Centre and inspect pending decisions.

Step 2. Open the source incident and confirm the investigation and privacy review are complete.

Step 3. Review the destination, matching rule, proposed route, and privacy-reduced payload preview.

Step 4. Confirm the payload contains the minimum necessary data and no prohibited secrets or unrelated personal data.

Step 5. Confirm the destination is approved. Private, localhost, or invalid public HTTPS destinations are blocked by design.

Step 6. Enter the approval reason and approve or reject the route.

Step 7. After approval, monitor delivery state, receipt, hash, attempt count, and retry schedule.

Retry a failed delivery

Step 1. Open the failed delivery record.

Step 2. Read the response/error and confirm the destination remains valid.

Step 3. Correct endpoint configuration if required.

Step 4. Use the controlled retry action once.

Step 5. Verify a new attempt and audit entry are recorded.

Warning: Never route original unredacted evidence merely to make integration debugging easier. Use minimum, privacy-reduced test data.

14. Configure integrations and providers

Integration Centre

- Step 1.** Open Integration Centre as an Administrator or appropriately authorized operator.
- Step 2.** Review existing endpoints and their enabled/disabled state.
- Step 3.** Add a descriptive endpoint name and an approved public HTTPS URL.
- Step 4.** Add authentication/signing information through environment variables or designated controls. Do not paste secrets into incident notes.
- Step 5.** Keep the endpoint disabled until testing is complete.
- Step 6.** Run the available safe test with non-sensitive data.
- Step 7.** Review the test result, receipt, and audit record.
- Step 8.** Enable the endpoint only after approval.

Routing rules

- Step 1.** Create a rule with a clear name and narrow matching conditions.
- Step 2.** Select the destination and verify privacy expectations.
- Step 3.** Save it disabled.
- Step 4.** Test against synthetic or approved examples.
- Step 5.** Enable the rule after peer/administrative review.

Important: A matching rule proposes a route. It does not replace the required human routing approval.

15. Notifications and Audit Log

Notifications

Step 1. Open Notifications.

Step 2. Review unread items for assignment, SLA, escalation, delivery, or administrative changes.

Step 3. Open the related record and complete the required action.

Step 4. Mark the notification read only after it has been acknowledged.

Audit Log

Step 1. Open Audit Log.

Step 2. Filter by time, actor, action, incident, or entity when available.

Step 3. Review before/after details and reasons for sensitive actions.

Step 4. Export only for an approved audit, investigation, or compliance purpose.

Step 5. Do not edit database audit records directly. Report discrepancies to the system owner.

16. Users and roles

Step 1. Open Users & Roles as an Administrator.

Step 2. Find the user by their approved identity/email.

Step 3. Review their current role and operational need.

Step 4. Select the least-privileged role that supports their duties.

Step 5. Enter the required reason for a role change.

Step 6. Save and verify the audit entry.

Step 7. Periodically remove or reduce access that is no longer required.

Change	Required check
Promote to Senior Analyst	Routing/closure responsibility and management approval.
Promote to Administrator	Need to manage users, settings, or integrations; strongest scrutiny.
Assign Auditor	Read-only evidence need; avoid operational write permissions.
Disable/reduce access	Employment/assignment status and record-retention requirements.

17. Settings, Help, accessibility, and PWA installation

Settings

Step 1. Open Settings.

Step 2. Review workspace defaults and operational configuration.

Step 3. Change one setting at a time.

Step 4. Save and verify the visible result and audit entry where applicable.

Help & Guidance

Step 1. Open Help & Guidance for in-product instructions, limitations, and operational reminders.

Step 2. Use this PDF for complete installation and workflow instructions.

Keyboard and accessibility

- Use Tab and Shift+Tab to move between controls.
- Use Enter or Space to activate buttons and links.
- Use Escape to close the mobile navigation drawer.
- Use the Skip to main content link to bypass repeated navigation.
- Tables may scroll within their own region on narrow screens.




Figure 5. Mobile Overview with the responsive menu and stacked content.

Install as a web app

Step 1. Open TriageNG in a supported Chromium-based browser.

Step 2. Use the browser Install app action when it appears.

Step 3. Confirm installation and launch from the desktop/start menu.

Step 4. Open the app online at least once after major updates so the current shell/assets are cached.

18. Data, privacy, evidence, and security

Where data is stored

Data	Storage
Incidents, users, audit entries, routing decisions, notifications	Cloudflare D1 locally emulated under .wrangler
Evidence file bytes	Cloudflare R2 locally emulated; metadata remains in D1
Pending offline reports	IndexedDB on the current browser/device
Cached application shell	Service worker cache; API responses are not cached
Analyst note drafts	Device-local browser storage by incident

Evidence rules

- Supported intake formats: PNG, JPG/JPEG, PDF, and TXT.
- Maximum accepted upload size: 10 MB.
- PDF extraction is bounded to the first five pages for predictable local performance.
- OCR results include confidence and limitations and require human review.
- Only privacy-reduced OCR text should be persisted in the operational workflow.

Security practices

- Never upload passwords, authentication tokens, private keys, or banking PINs.
- Do not execute attachments or follow suspicious links on an ordinary workstation.
- Apply least privilege to users, integrations, and exports.
- Verify destination ownership before enabling an integration.
- Rotate secrets if .dev.vars is exposed.
- Use approved retention and deletion procedures for operational records.

19. Exports, readiness evidence, and model evaluation

Export incident or audit data

Step 1. Open the relevant incident, Audit Log, or report screen.

Step 2. Apply filters so the export includes only required records.

Step 3. Select the CSV/export action.

Step 4. Open the downloaded file in a controlled environment and verify headers and record count.

Step 5. Store, transmit, and delete the export according to your security policy.

Model/evaluation evidence

The classifier is a versioned, explainable Multinomial Naive Bayes model trained on a reproducible synthetic labelled dataset. Evidence includes language breakdowns, confusion matrix, errors, limitations, OCR benchmark results, and end-to-end runtime data.

Warning: Synthetic evaluation figures are development evidence. They must not be presented as measured production accuracy.

Regenerate optional evidence

```
npm.cmd run ml:train  
npm.cmd run ml:ocr-evaluate
```

The optional OCR benchmark requires the system tesseract command. Browser OCR does not require a separate OCR account.

20. Backup, reset, update, and maintenance

Back up local service data

Step 1. Stop the development server with Ctrl+C.

Step 2. Copy the .wrangler folder to an access-controlled backup location.

Step 3. Record the application version/date and protect the backup as sensitive operational data.

Start with a clean local database

Warning: Resetting local data removes access to the active local database and bucket state. Back up first.

Step 1. Stop the server.

Step 2. Rename .wrangler to a dated backup name rather than deleting it.

Step 3. Run npm.cmd run local:setup on Windows or npm run local:setup elsewhere.

Step 4. Restart the server and verify Overview, Incident Queue, and submission.

Verify after changes

```
npm.cmd run build
npm.cmd test
npm.cmd run lint
npm.cmd exec tsc -- --noEmit
```

Step 1. Require a successful build and passing tests.

Step 2. Review lint warnings and correct new errors before release.

Step 3. Submit a synthetic test incident and verify D1/R2/audit behavior.

Step 4. Check desktop and mobile layouts.

21. Troubleshooting

Problem	Cause and exact remedy
npm.ps1 cannot be loaded	PowerShell execution policy blocked npm.ps1. Use npm.cmd install and npm.cmd run dev. Do not weaken the global policy.
Hydration mismatch	Use the updated build. Hard refresh once. If stale assets persist, close the installed app/browser tab, clear this localhost site's cache, and restart dev.
API returns 401	Confirm .dev.vars exists and TRIAGENG_LOCAL_DEV=true, then restart the server.
Database table missing	Stop the server, run npm.cmd run local:setup, then restart.
Port 5173 occupied	Open the alternative URL printed by Vite, or stop the other local process.
Provider not configured	Expected until its optional URL/token is added to .dev.vars and the server is restarted.
Report remains offline	Confirm server and network are available, open Offline Queue, retry synchronization, and keep the tab open.
Attachment rejected	Use PNG, JPG, PDF, or TXT; keep the file at or below 10 MB.
OCR is weak	Use a sharper, upright image with good contrast. Manually review and correct privacy-reduced text.
Routing destination blocked	Use an approved public HTTPS endpoint. Localhost and private network destinations are intentionally rejected.
Old interface appears	Hard refresh. If installed as a PWA, close and reopen online so the new service-worker cache activates.

Collect safe diagnostic information

- Record the time, screen, incident reference, and exact error text.
- Capture a screenshot without exposing secrets or unrelated personal data.
- Check the terminal output and the browser developer console.
- Review Audit Log and the local Cloudflare Explorer.
- Never include .dev.vars contents or tokens in a support message.

22. Complete start-to-finish operating checklist

Use this checklist for a complete first operational exercise.

- 1. Install Node 22.13+ and npm 10+.
- 2. Create .dev.vars from local.env.example.
- 3. Confirm TRIAGENG_LOCAL_DEV=true.
- 4. Run dependency installation.
- 5. Run local:setup.
- 6. Start dev and open localhost.
- 7. Confirm Online and Overview metrics.
- 8. Submit a synthetic English or Pidgin incident.
- 9. Record its permanent TNG reference.
- 10. Upload a safe TXT or image sample.
- 11. Open Incident Queue and select the report.
- 12. Review original report and attachment processing.
- 13. Review category, severity, route, confidence, evidence, and limitations.
- 14. Correct the recommendation with a rationale if needed.
- 15. Compare and approve privacy-reduced text.
- 16. Review URLs, domains, IPs, and hashes.
- 17. Review related reports/clusters.
- 18. Assign an analyst and confirm SLA.
- 19. Add and save an analyst note.
- 20. Open Routing Centre and review the privacy-reduced payload.
- 21. Approve or reject routing with a reason.
- 22. Verify delivery receipt or controlled failure state.
- 23. Close the incident with resolution and reason.
- 24. Reopen only when testing that workflow, with a reason.
- 25. Review Notifications and Audit Log.
- 26. Review Analytics, Judge Mode, Management Reports, Users & Roles, Settings, and Help.
- 27. Test an offline submission and synchronize it.
- 28. Run build, tests, lint, and TypeScript checks.
- 29. Back up .wrangler if the local records must be retained.
- 30. Stop the server with Ctrl+C.

Appendix A. Category and severity reference

Typical categories

Category	Examples
Phishing	Credential theft email, fake login page, business email impersonation.
Malware	Trojan, ransomware, suspicious executable, malicious document behavior.
Unauthorized access	Account takeover, exposed admin access, unexplained successful login.
Data exposure	Leaked records, public bucket, misdirected sensitive information.
Denial of service	Service flooding, resource exhaustion, availability attack.
Vulnerability	Security weakness requiring validation and remediation.
Other/unknown	Insufficient evidence or incident outside established categories.

Severity guidance

Severity	Human considerations
Critical	Widespread/ongoing compromise, major essential service impact, severe safety or national-scale consequences.
High	Confirmed compromise, sensitive data loss, material institutional impact, or urgent containment need.
Medium	Credible limited incident requiring investigation, with manageable current impact.
Low	Low-impact event, unsuccessful attempt, informational issue, or routine advisory work.

Appendix B. Command reference

Purpose	Windows PowerShell command
Install	npm.cmd install
Create environment	Copy-Item local.env.example .dev.vars
Prepare database	npm.cmd run local:setup
Start development	npm.cmd run dev
Production build	npm.cmd run build
Automated tests	npm.cmd test
Lint	npm.cmd run lint
Type check	npm.cmd exec tsc -- --noEmit
Train model	npm.cmd run ml:train
OCR evaluation	npm.cmd run ml:ocr-evaluate
Stop server	Ctrl+C

Appendix C. API and service map

Endpoint	Purpose
/api/incidents	List, create, synchronize, classify, assign, close, reopen, and update incidents.
/api/attachments	Evidence upload, metadata, OCR/privacy status, and review.
/api/audit	Persistent audit history.
/api/metrics	Overview and operational metrics.
/api/routing	Human-approved routing decisions.
/api/deliveries	Delivery queue, receipts, attempts, and controlled retry.
/api/integrations	Integration endpoint configuration and test state.
/api/rules	Routing rule configuration and enablement.
/api/providers	Provider readiness and safe test runs.
/api/notifications	Notification list and read state.
/api/users	Workspace roles and audited changes.
/api/evaluation	Evaluation and dataset evidence.
/api/readiness	System readiness evidence.
/api/exports	Incident and audit CSV exports.
/api/email-intake	Token-authenticated email intake.
/api/escalations	Controlled overdue SLA escalation.

Local Cloudflare services

- Application: <http://localhost:5173>
- Explorer API: <http://localhost:5174/cdn-cgi/explorer/api>
- D1 stores relational operational records.
- R2 stores evidence objects.
- Durable Objects and Workflows may be inspected through the Explorer when configured by the local platform.

Appendix D. Operational handover record

Complete this page when handing the local environment to another authorized operator.

Item	Record
Handover date/time	
Outgoing operator	
Incoming operator	
Application version/build	
Local URL	
Data backup location	
Pending offline reports	
Open critical/high incidents	
Failed deliveries	
Known limitations/issues	
Secrets rotated/verified	
Sign-off	

Important: Keep this manual with the application documentation. Update it whenever screens, roles, commands, file limits, or approval workflows change.