



Deployments

Create phone deployment

Create Phone Deployment

This endpoint creates a new phone deployment, linking an agent snapshot to a phone number within a specific region. This is how you make your conversational agents available to handle phone calls.

Request Body

The request accepts a JSON object with the following properties:

- `snapshot_traffic_distribution` (array, required): An array of objects defining the agent snapshots to deploy and their traffic distribution
 - `agent_snapshot_id` (UUID, required): The ID of the agent snapshot to deploy
 - `traffic_proportion` (number, required): The proportion of traffic this snapshot should receive (between 0 and 1)
- `phone_id` (UUID, required): The ID of the phone number to use for this deployment
- `region` (string, required): The region where this deployment should be created (either "eastus" or "sweden")

Traffic Distribution

The `traffic_proportion` values in the `snapshot_traffic_distribution` array must sum to 1.0. This allows for:

- A/B testing different agent versions
- Gradual rollout of new agent versions
- Canary deployments to test changes with a small percentage of traffic

Response

On success, the endpoint returns an array of `PhoneDeployment` objects, each containing:

- `agent_snapshot_id` (UUID): The ID of the deployed agent snapshot
- `traffic_proportion` (number): The proportion of traffic routed to this snapshot
- `phone_id` (UUID): The ID of the phone number
- `inbound_call_url` (string): The URL that handles inbound calls

Available Regions

Leaping AI currently supports two regions for phone deployments:

- `eastus` : Deployed in Azure East US 2 (Virginia), optimized for North American callers
- `sweden` : Deployed in Azure Sweden Central, optimized for European callers

Choose the region closest to your callers to minimize latency and improve call quality.

Example

```
curl -X POST "https://api.leaping.ai/v1/deployments/" \
-H "Authorization: Bearer YOUR_TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "snapshot_traffic_distribution": [
    {
      "agent_snapshot_id": "550e8400-e29b-41d4-a716-446655440000",
      "traffic_proportion": 1.0
    }
  ],
  "phone_id": "a385a208-7b1a-4d27-8c08-a35d7e1f72c2",
  "region": "eastus"
}'
```



Example: A/B Testing

To deploy two different agent snapshots with a 90/10 split:

```
curl -X POST "https://api.leaping.ai/v1/deployments/" \
-H "Authorization: Bearer YOUR_TOKEN" \
-H "Content-Type: application/json" \
-d '{
  "snapshot_traffic_distribution": [
    {
      "agent_snapshot_id": "550e8400-e29b-41d4-a716-446655440000",
      "traffic_proportion": 0.9
    },
    {
      "agent_snapshot_id": "550e8400-e29b-41d4-a716-446655440001",
      "traffic_proportion": 0.1
    }
  ],
  "phone_id": "a385a208-7b1a-4d27-8c08-a35d7e1f72c2",
  "region": "sweden"
}'
```



< Send outbound sms

Get regions >

Ask a question...

