



SMS

Send outbound sms

Send Outbound SMS

Send one or more outbound SMS messages from an agent. Each recipient is validated, screened against your Do Not Call list and per-recipient daily limits, and queued for delivery. Messages are sent asynchronously — this endpoint accepts and schedules them, it does not block until delivery.

The response is **1:1 with the input**: `results` has exactly one entry per recipient, in the same order, so you can map each outcome (`pending` , `conflict` , `dnc_filtered` , `daily_limit_filtered` , `failed`) back to the number you submitted.

 This API is the only way to send outbound SMS today — there is no dashboard UI for it yet.

How Message Bodies Are Built

For each recipient, the effective template is the recipient's `message_template` if set, otherwise the top-level `message_template` . Template variables are resolved from the union of the agent snapshot's fields and the merged `field_overrides` (top-level values overridden by per-recipient values). If a template references a variable that can't be resolved, that recipient fails with `unresolvable_template_vars` and the offending names are listed in `error_metadata.unresolvable_vars` .

If no template is provided and the agent is configured to speak first (its first conversation stage begins on a user turn), the agent itself generates the opening message.

Do Not Call & Daily Limits

Before queuing, every recipient is screened individually — the rest of the batch still proceeds:

- Do Not Call:** recipients on your group's Do Not Call list are not messaged and are returned with status `dnc_filtered` .
- Per-recipient daily limit:** recipients who have reached the configured per-day SMS cap are not messaged and are returned with status `daily_limit_filtered` .

Validation Rules

- Either `agent_id` or `agent_snapshot_id` must be provided. If both are given, `agent_snapshot_id` takes precedence.
- `from_phone_id` and `from_phone_number` are mutually exclusive. If both are omitted, an SMS-deployed phone for the agent is selected automatically.
- `recipient_phone_numbers` must contain between 1 and 1000 entries, each a valid E.164 number.
- `scheduled_for` (top-level or per-recipient) must be **timezone-aware** — a naive datetime is rejected — and must be in the **future**.

Idempotency

To make retries safe, pass an optional `Idempotency-Key` header (Stripe-equivalent semantics). The value is an opaque string up to 255 characters. Use one key per logical operation and reuse it across retries — generating a fresh key per attempt defeats the purpose.

- Replay-safe.** Within the TTL (default 24 hours, configurable via `IDEMPOTENCY_TTL_SECONDS`), an identical retry from the same authenticated user with the same body returns the cached response without re-queuing.
- Body fingerprint.** A retry that reuses the key with a different body returns `422 Unprocessable Entity` instead of silently replaying.
- In-flight conflict.** A retry that arrives while a sibling request with the same key is still processing returns `409 Conflict` .
- Failures are not cached.** If the original request fails, the response is not stored — retry with the same key and it will execute.
- Per-user scope.** Keys are scoped to the authenticated user.
- Optional.** Omit the header (or send a whitespace-only value) to fall back to the non-idempotent behaviour.

Common Errors

- `400 Bad Request` : The agent snapshot was not found, the agent has no group, the sending phone is not found or not SMS-deployed to this agent, the phone's region is not configured for SMS, the phone uses external (BYO) Twilio credentials, or `scheduled_for` is in the past.
- `409 Conflict` : An `Idempotency-Key` was supplied while a sibling request with the same key is still being processed.
- `422 Unprocessable Entity` : The request body failed validation, or an `Idempotency-Key` was reused with a different body.

Example

```
curl -X POST "https://api.leaping.ai/v1/sms/outbound" \
-H "Content-Type: application/json" \
-H "Authorization: Bearer YOUR_TOKEN" \
-H "Idempotency-Key: 7f3c1b2e-9a4d-4b8e-bc51-1d2e3f4a5b6c" \
-d '{
  "agent_id": "550e8400-e29b-41d4-a716-446655440000",
  "from_phone_number": "+15551234567",
  "message_template": "Hi {{ customer_name }}, your appointment is at {{ appointment_time }}.",
  "recipient_phone_numbers": [
    {
      "phone_number": "+15557654321",
      "field_overrides": { "customer_name": "John Doe", "appointment_time": "3:00 PM" }
    },
    {
      "phone_number": "+15559876543",
      "field_overrides": { "customer_name": "Jane Smith", "appointment_time": "4:30 PM" }
    }
  ],
  "scheduled_for": "2026-06-01T15:00:00+00:00"
}'
```

```
{
  "scheduled_count": 1,
  "sent_count": 0,
  "failed_count": 0,
  "conflict_count": 1,
  "dnc_filtered_count": 0,
  "daily_limit_filtered_count": 0,
  "results": [
    {
      "status": "pending",
      "id": "9b1deb4d-3b7d-4bad-9bdd-2b0d7b3dc6d",
      "phone_number": "+15557654321",
      "scheduled_for": "2026-06-01T15:00:00+00:00"
    },
    {
      "status": "conflict",
      "phone_number": "+15559876543",
      "error": "duplicate_pending_row",
      "existing_id": "1f0c2a44-9d2a-4e6b-8b1a-2c3d4e5f6a7b"
    }
  ]
}
```