

## 9926 Series Branch Circuit Breakers (AC)

Circuit Breakers  
Hydraulic Magnetic Type

- 1, 2 and 3 pole versions
- 120/240 VAC, 50/60 Hz
- Up to 25A
- Just 13 mm wide, per pole
- Mounts on 35mm DIN-rail
- cULus listed according to UL489  
CSA C22.2 No. 5.02, CE, VDE

9926 Series  
Single Pole9926 Series  
Double Pole9926 Series  
Triple Pole

Technical Data	
Voltage	120/240 VAC, 50/60Hz
Current minimum	0.5A
Current maximum	25A
Interrupting capacity	10,000A
Dielectric strength	1500V, 50/60Hz
Insulation resistance	100 MΩ
Operating Life	10000 mechanical operations
Operating temperature	-40...+65°C
Wire size*	
*0.5-15A:	14AWG min., 10AWG max.
20-25A:	10AWG min.
Torque	20 in.-lb

## Accessories

Type	Part No.
Bus-bar (1 pole, insulated, 1 m)	67101904
Bus-bar (2 pole, insulated, 1 m)	67101972
Bus-bar end cap, 1 pole	67101973
Bus-bar end cap, 2 pole	67101974
Power lug, straight (14 mm)	67101960
Power lug, 90° (14 mm)	67101961
Power lug, straight (32 mm)	67102480
Power lug, 90° (32 mm)	67102479
Lock-out handle	67101913

\*Wire sizes: gauges specified are the minimum allowable as per CSA and UL standards.

The 9926 circuit breakers do not have provisions for marking tags. A possible solution is to cut the adhesive SchS2 tag rail to length (approximately 20 mm on a single pole unit so the current rating remains visible or approximately 30 mm on a two pole unit). The SchS2 accepts DEK, WS and ESG 8/17 marking tags. The part number for adhesive SchS2 is 1720600000.

See Trip Curves 1, 3, 9, KM, OP - Page 26

## Type: Single Pole (up to 120 VAC)

Current Ratings (amps)	Description	Part No.
0.5	QL-1-13-DM-KM-0.5	9926251000
1	QL-1-13-DM-KM-01	9926251001
2	QL-1-13-DM-KM-02	9926251002
3	QL-1-13-DM-KM-03	9926251003
4	QL-1-13-DM-KM-04	9926251004
5	QL-1-13-DM-KM-05	9926251005
6	QL-1-13-DM-KM-06	9926251006
7	QL-1-13-DM-KM-07	9926251007
8	QL-1-13-DM-KM-08	9926251008
10	QL-1-13-DM-KM-10	9926251010
13	QL-1-13-DM-KM-13	9926251013
15	QL-1-13-DM-KM-15	9926251015
16	QL-1-13-DM-KM-16	9926251016
20	QL-1-13-DM-KM-20	9926251020
25	QL-1-13-DM-KM-25	9926251025

## Type: Double Pole (up to 240 VAC)

Current Ratings (amps)	Description	Part No.
0.5	QL-2-13-DM-KM-0.5	9926252000
1	QL-2-13-DM-KM-01	9926252001
2	QL-2-13-DM-KM-02	9926252002
3	QL-2-13-DM-KM-03	9926252003
4	QL-2-13-DM-KM-04	9926252004
5	QL-2-13-DM-KM-05	9926252005
6	QL-2-13-DM-KM-06	9926252006
7	QL-2-13-DM-KM-07	9926252007
8	QL-2-13-DM-KM-08	9926252008
10	QL-2-13-DM-KM-10	9926252010
13	QL-2-13-DM-KM-13	9926252013
15	QL-2-13-DM-KM-15	9926252015
16	QL-2-13-DM-KM-16	9926252016
20	QL-2-13-DM-KM-20	9926252020
25	QL-2-13-DM-KM-25	9926252025

## Type: Triple Pole (up to 240 VAC)

Current Ratings (amps)	Description	Part No.
1	QL-3(13)-DM-KM-1A	9926253001
2	QL-3(13)-DM-KM-2A	9926253002
5	QL-3(13)-DM-KM-5A	9926253005
10	QL-3(13)-DM-KM-10A	9926253010
15	QL-3(13)-DM-KM-15A	9926253015
20	QL-3(13)-DM-KM-20A	9926253020
25	QL-3(13)-DM-KM-25A	9926253025

## Dimension Diagrams in mm (in.)

