

Product selection result

Project

- Title: Charles County Pomonkey PLC Panel
- Create date: Mar 11, 2026
- Amend date: Mar 25, 2026

User

- Company:
- Name:
- Address:
- City:

Enclosure		Wall		Location	
Type	Wall Mount Enclosure	Material	Stainless Steel	for Outdoor environments / NEMA Type 3R/4/4x	
Height	1,524 mm			Single housing, free-standing on all sides	
Width	914 mm	k	3.7 W/m ² K	Wind speed	No
Depth	406 mm	Insulation	R0 = 0 mm		Wind
		Enclosure Color	Gray	Surface according to VDE 0660 part 600	4.1 m ²

Temperature

Min. ambient temperature	-18 °C
Max. ambient temperature	38 °C
Min. admissible temperature	-10 °C
Max. admissible temperature	55 °C

Rated connection value

Rated voltage:	115 V
Frequency	60 Hz

Dissipation based on manual input 64 W

Switch cabinet acclimatisation

Total dissipation in enclosure	64 W
Dissipation due to solar radiation	0 W
Heat Dissipation from environment	0 W
Heat Dissipation to environment	261 W
Required cooling capacity	0 W
Required heating capacity	116 W

Product selection result

Warning

Ensure there is sufficient clearance for air flow around the cooling unit to prevent a so-called air short-circuit. There should be a minimum distance of approximately 200 mm (7.9 inches) to the next component in the housing and 400 mm (15.7 inches) outside the housing