

Product selection result

Project

- Title: Charles County Pomonkey PLC Panel
- Create date: Mar 11, 2026
- Amend date: Mar 11, 2026

User

- Company:
- Name:
- Address:
- City:

Enclosure		Wall		Location	
Type	Wall Mount Enclosure	Material	Stainless Steel	for Outdoor environments / NEMA Type 3R/4/4x	
Height	60 inch			Single housing, free-standing on all sides	
Width	36 inch	k	3.7 W/m ² K	Wind speed	No
Depth	16 inch	Insulation	R0 = 0 inch		Wind
		Enclosure Color	Gray	Surface according to VDE 0660 part 600	45ft ²
Temperature		Rated connection value			
Min. ambient temperature	0 °F	Rated voltage: 115 V			
Max. ambient temperature	100 °F	Frequency 60 Hz			
Min. admissible temperature	14 °F				
Max. admissible temperature	131 °F				

Dissipation based on manual input 452 BTU/h

Switch cabinet acclimatisation

Total dissipation in enclosure	132 W
Dissipation due to solar radiation	0 BTU/h
Heat Dissipation from environment	0 BTU/h
Heat Dissipation to environment	891 BTU/h
Required cooling capacity	0 BTU/h
Required heating capacity	396 BTU/h

Product selection result

Warning

Ensure there is sufficient clearance for air flow around the cooling unit to prevent a so-called air short-circuit. There should be a minimum distance of approximately 200 mm (7.9 inches) to the next component in the housing and 400 mm (15.7 inches) outside the housing