


EPI-04-V








Table 1				
EPI(R)-10-V	10	25.30[.996]	22.86[.900]	
EPI(R)-08-V	8	20.22[.796]	17.78[.700]	
EPI(R)-06-V	6	15.14[.596]	12.70[.500]	
EPI(R)-04-V	4	10.06[.396]	7.62[.300]	
EPI(R)-02-V	2	4.98[.196]	2.54[.100]	
PROD. NO.	NO. OF POS.	DIM. A	DIM. B	

SCHEMATIC(TYP.)


(2,4,6,8,10 POS AVAIL)


EPI-08-V


1.ALL DIMENSIONS ARE IN MILLIMETERS, BRACKETED DIMENSIONS ARE IN INCHES. 2.GENERAL TOLERANCES±0.20mm. 3.MATERIAL & * :SEE SPECIFICATION. 4.P:Pitch=2.54mm[0.100]

NOTE:










EPM-06-V





[0.035] 0,90 EPMR WITHOUT 20° [0.386] 9.80

P.C.B. LAYOUT

EPM(R)-10-V	10	25.30[.996]	22.86[.900]
EPM(R)-08-V	8	20.22[.796]	17.78[.700]
		45 445 5001	40 705 7003

EPM(R)-06-V 6 15.14[.596] 12.70[.500]
EPM(R)-04-V 4 10.06[.400] 7.62[.300]
EPM(R)-02-V 2 4.98[.196] 2.54[.100]
PROD. NO. POS. DIM. A DIM. B

SCHEMATIC(TYP.)

Table 1

EPM-10-V