Sphere Intersection

We know that a sphere of radius r is the set of all points a distance r from sphere's center. In vector notation, this is

$$(\mathbf{P} - \mathbf{O}_S) \cdot (\mathbf{P} - \mathbf{O}_S) = r^2$$

where \mathbf{P} is a vector touching a point on the sphere and \mathbf{O}_S is the vector describing the sphere's center. We describe a ray via

$$\mathbf{P}(t) = \mathbf{O}_R + \mathbf{D}t$$

where $t \in \mathbb{R}$. Substituting this into the implicit equation for our sphere yields

$$\begin{split} r^2 &= (\mathbf{P}(t) - \mathbf{O}_S) \cdot (\mathbf{P}(t) - \mathbf{O}_S), \\ &= (\mathbf{O}_R + \mathbf{D}t - \mathbf{O}_S) \cdot (\mathbf{O}_R + \mathbf{D}t - \mathbf{O}_S), \\ &= (\mathbf{D}t + (\mathbf{O}_R - \mathbf{O}_S)) \cdot (\mathbf{D}t + (\mathbf{O}_R - \mathbf{O}_S)), \\ &= (\mathbf{D} \cdot \mathbf{D})t^2 + 2\mathbf{D} \cdot (\mathbf{O}_R - \mathbf{O}_S)t + (\mathbf{O}_R - \mathbf{O}_S) \cdot (\mathbf{O}_R - \mathbf{O}_S). \end{split}$$

We can define $\mathbf{U} = \mathbf{O}_R - \mathbf{O}_S$, collect everything on one side, and group terms by orders of t to arrive at

$$(\mathbf{D} \cdot \mathbf{D})t^2 + (2\mathbf{D} \cdot \mathbf{U})t + (\mathbf{U} \cdot \mathbf{U} - r^2) = 0$$

which is a simple quadratic equation in t. Its solution is

$$t = \frac{-2\mathbf{D} \cdot \mathbf{U} \pm \sqrt{(2\mathbf{D} \cdot \mathbf{U})^2 - 4(\mathbf{D} \cdot \mathbf{D})(\mathbf{U} \cdot \mathbf{U} - r^2)}}{2\mathbf{D} \cdot \mathbf{D}}.$$

or, removing a common factor of 2,

$$t = \frac{-\mathbf{D} \cdot \mathbf{U} \pm \sqrt{\left(\mathbf{D} \cdot \mathbf{U}\right)^2 - \left(\mathbf{D} \cdot \mathbf{D}\right) \left(\mathbf{U} \cdot \mathbf{U} - r^2\right)}}{\mathbf{D} \cdot \mathbf{D}}.$$

Evidently, the ray intersects our sphere when the discriminant of this equation is greater than or equal to 0, i.e.

$$(\mathbf{D} \cdot \mathbf{U})^2 - (\mathbf{D} \cdot \mathbf{D})(\mathbf{U} \cdot \mathbf{U} - r^2) \ge 0$$

If this condition is met, the value of t corresponding to the first intersection is the smallest value that is still greater than 0.

Importance Sampling

For a function f(x) of a random variable X, its expected value is given by

$$\mathbb{E}_p[f(X)] = \int_{\Omega} f(x) p_X(x) \, \mathrm{d}x$$

where $p_X(x)$ is the probability density function (PDF) of X. A statistical way to evaluate the expected value is given by the sample mean, defined by

$$\mathbb{E}_p[f(X)] = \lim_{N \to \infty} \frac{1}{N} \sum_{i=1}^{N} f(x_i)$$

where each x_i is a realization of X drawn from the distribution $p_X(x)$. We often want to evaluate integrals of the form $\int_{\Omega} f(x) dx$, which we can do by taking the expected value of $f(x)/p_X(x)$ instead of just f(x). Truncating the sample mean at a finite N, we see the correspondence

$$\int_{\Omega} f(x) \, \mathrm{d}x \approx \frac{1}{N} \sum_{i=1}^{N} \frac{f(x_i)}{p_X(x_i)}$$

If the samples we use are not a good fit to f, we run the risk of adding up a lot of terms that contribute very little to the final result. We can work around this by including a simple multiplicative factor of 1 in the expected value in the form of $q_X(x)/q_X(x)$, where $q_X(x)$ is a PDF that better matches f. Specifically, we see

$$\mathbb{E}_p\left[\frac{f(X)}{p_X(X)}\frac{q_X(X)}{q_X(X)}\right] = \int_{\Omega} \frac{f(x)}{p_X(x)}\frac{q_X(x)}{q_X(x)}p_X(x)\,\mathrm{d}x = \int_{\Omega} \frac{f(x)}{q_X(x)}q_X(x)\,\mathrm{d}x = \mathbb{E}_q\left[\frac{f(X)}{q_X(X)}\right]$$

which gives us the correspondence

$$\int_{\Omega} f(x) dx \approx \frac{1}{N} \sum_{i=1}^{N} \frac{f(x_i)}{q_X(x_i)}$$

where, in this case, each x_i is sampled from the distribution defined by $q_X(x)$. There are, of course, restrictions on the possible choices of $q_X(x)$, but they are surprisingly soft: we simply require that $q_X(x)$ be nonzero wherever $f(x)p_X(x)$ is nonzero.

In path tracing, we use this to estimate the indirect lighting present in the scene. Specifically, we take f(x) to be the integrand of the rendering equation and N to be 1,

$$\int_{\Omega} f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) L_i(\mathbf{x}, \hat{\omega}_i, \lambda, t) |\hat{\omega}_i \cdot \mathbf{n}| d\hat{\omega}_i \approx \frac{f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) L_i(\mathbf{x}, \hat{\omega}_i, \lambda, t) |\hat{\omega}_i \cdot \mathbf{n}|}{p_{\omega}(\hat{\omega}_i)}$$

Lambertian Reflectance

Recall the rendering equation,

$$L_o(\mathbf{x}, \hat{\omega}_o, \lambda, t) = L_e(\mathbf{x}, \hat{\omega}_o, \lambda, t) + \int_{\Omega} f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) L_i(\mathbf{x}, \hat{\omega}_i, \lambda, t) |\hat{\omega}_i \cdot \mathbf{n}| d\hat{\omega}_i$$

where $f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t)$ describes the bidirectional reflectance distribution function (BRDF) of the material under consideration and Ω is the hemisphere centered at the geometry's normal vector.

A diffuse, Lambertian material has an equal chance to scatter light in all directions. This implies that $f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) = \rho_0$ where ρ_0 is a constant. Because of this, the direction of the incoming radiance does not matter and we may take $L_i(\mathbf{x}, \hat{\omega}_i, \lambda, t)$ outside of the integral. Assuming all light is reflected imposes the additional requirement that

$$\int_{\Omega} \rho_0 |\hat{\omega}_i \cdot \mathbf{n}| \, \mathrm{d}\hat{\omega}_i = \rho_0 \int_{\Omega} \cos \theta \, \mathrm{d}\hat{\omega}_i = 1$$

where θ is the angle between $\hat{\omega}_i$ and the normal. On the unit hemisphere, with ϕ describing the azimuthal angle and θ the altitude, this requirement becomes

$$\rho_o \int_0^{2\pi} \int_0^{\pi/2} \cos \theta \sin \theta \, d\theta \, d\phi = \frac{\rho_0}{2} \int_0^{2\pi} \int_0^{\pi/2} \sin(2\theta) \, d\theta \, d\phi$$
$$= \frac{\rho_0}{4} \int_0^{2\pi} -\cos(2\theta) \Big|_0^{\pi/2} \, d\phi$$
$$= \frac{\rho_0}{2} \int_0^{2\pi} d\phi$$
$$= \rho_0 \pi$$
$$= 1$$

i.e. max reflectance occurs when $\rho_0 = 1/\pi$. If we allow this to vary by wavelength via $f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) = \rho(\lambda)/\pi$ with $\rho(\lambda) \in [0, 1]$, the indirect part of the path tracing equation becomes

$$\frac{\rho(\lambda)L_i(\mathbf{x},\hat{\omega}_i,\lambda,t)|\hat{\omega}_i\cdot\mathbf{n}|}{\pi p_{\omega}(\hat{\omega}_i)}$$

If we sample directions uniformly in the unit hemisphere, for example, $p_{\omega}(\hat{\omega}_i) = 1/2\pi$ and the above simplifies

$$2\rho(\lambda)L_i(\mathbf{x},\hat{\omega}_i,\lambda,t)|\hat{\omega}_i\cdot\mathbf{n}|$$

Uniformly Sampling the Unit Sphere (and Unit Hemisphere)

The easiest way to generate uniformly spaced points on the unit sphere is to build a cumulative distribution function (CDF), then use inverse transform sampling. To put it another way, suppose we want to generate samples from a PDF $p_X(x) = dF_X(x)/dx$ but only have access to U, a random variable uniformly distributed between 0 and 1. An obvious way to map from this domain to the range of X is to define $Y = F_X^{-1}(U)$. The CDF of this new random variable is

$$F_Y(y) = \Pr(Y \le y) = \Pr(F_X^{-1}(U) \le y) = \Pr(U \le F_X(y)) = F_X(y),$$

where we have used the fact that all CDFs are monotonic and that $\Pr(U \leq u) = u$ for a random variable uniformly distributed between 0 and 1. Given the uniqueness of the derivative, we can be confident that Y has the same distribution as X.

Moving on to the problem at hand, the PDF of the unit sphere with regard to solid angle Ω must be

$$p_{\Omega}(\Omega) = \frac{1}{4\pi}$$

We can, of course, write this in ϕ - θ space as

$$p_{\Omega}(\Omega) d\Omega = p_{\theta,\phi}(\theta,\phi) d\theta d\phi$$

where, upon identifying $d\Omega = \sin \theta \, d\theta \, d\phi$, we find

$$p_{\theta,\phi}(\theta,\phi) = \frac{\sin\theta}{4\pi}$$

We can integrate over each variable to obtain the PDF of the other,

$$p_{\theta}(\theta) = \int_{0}^{2\pi} \frac{\sin \theta}{4\pi} d\phi = \frac{\sin \theta}{2}$$
$$p_{\phi}(\phi) = \int_{0}^{\pi} \frac{\sin \theta}{4\pi} d\theta = \frac{1}{2\pi}$$

which can then be used to find their respective CDFs

$$F_{\theta}(\theta) = \int_{0}^{\theta} \frac{\sin \theta'}{2} d\theta' = \frac{1 - \cos \theta}{2}$$
$$F_{\phi}(\phi) = \int_{0}^{\phi} \frac{d\phi'}{2\pi} = \frac{\phi}{2\pi}$$

whose inverse functions are

$$F_{\theta}^{-1}(u) = \cos^{-1}(1 - 2u) \equiv \theta$$
$$F_{\phi}^{-1}(v) = 2\pi v \equiv \phi$$

We can substitute these into the conversions from Cartesian to spherical coordinates to get

$$x = \sin \theta \cos \phi = \sqrt{1 - z^2} \cos(2\pi v)$$
$$y = \sin \theta \sin \phi = \sqrt{1 - z^2} \sin(2\pi v)$$
$$z = \cos \theta = 1 - 2u$$

Another method for uniformly sampling the unit sphere is to draw random values from the unit normal distribution for each component of a vector. One then simply needs to normalize the resulting vector. This works because the combined Gaussian PDF is rotationally invariant, and thus must correspond to a uniform distribution on the sphere.

Yet another method is the so-called 'rejection' method. In this, we draw values for the vector's components from a random variable uniformly distributed between -1 and 1. If the vector lies within the unit ball, we normalize it. Otherwise, we repeat the process.

After we have setup a method to sample the unit sphere, sampling the unit hemisphere is just as easy. We simply dot the sampled vector with the desired normal vector: if this result is less than 0, we negate the sampled vector.

Uniformly Sampling the Unit Disc

We follow a similar strategy to above. Over the unit disc, a uniform sampling strategy must yield

$$p_A(A) = \frac{1}{\pi}.$$

Identifying $dA = r dr d\phi$ and equating the above PDF with the equivalent PDF in r- ϕ spaces gives

$$p_A(A) dA = \frac{r}{\pi} dr d\phi = p_{r,\phi}(r,\phi) dr d\phi,$$

i.e. $p_{r,\phi}(r,\phi) = r/\pi$. The PDF of each variable is

$$p_r(r) = \int_0^{2\pi} \frac{r}{\pi} d\phi = 2r$$
$$p_{\phi}(\phi) = \int_0^1 \frac{r}{\pi} dr = \frac{1}{2\pi}$$

and so the corresponding CDFs are

$$F_r(r) = \int_0^r 2r' \, \mathrm{d}r' = r^2$$
$$F_{\phi}(\phi) = \int_0^{\phi} \frac{\mathrm{d}\phi'}{2\pi} = \frac{\phi}{2\pi}$$

and so the inverse CDFs are

$$F_r^{-1}(u) = \sqrt{u} \equiv r$$
$$F_\phi^{-1}(v) = 2\pi v \equiv \phi$$

In Cartesian coordinates, then, a randomly sampled point on the unit disc is given by

$$x = r\cos\phi = \sqrt{u}\cos(2\pi v)$$
$$y = r\sin\phi = \sqrt{u}\sin(2\pi v)$$

Cosine Weighted Sampling of the Unit Hemisphere

Looking back to the section on importance sampling, we see that sampling directions from a cosine weighted distribution has the advantage of removing the $|\hat{\omega}_i \cdot \mathbf{n}|$ term from the rendering equation. Let's figure out how to do this.

A cosine weighted distribution over the unit hemisphere should obey

$$p_{\Omega}(\Omega) d\Omega = A \cos \theta d\Omega = A \cos \theta \sin \theta d\theta d\phi$$

where A is a normalization constant. We can find it by integrating over the unit hemisphere,

$$\int_{\Omega} p_{\Omega}(\Omega) d\Omega = A \int_{0}^{2\pi} \int_{0}^{\pi/2} \cos \theta \sin \theta d\theta d\phi$$

$$= \frac{A}{2} \int_{0}^{2\pi} \int_{0}^{\pi/2} \sin(2\theta) d\theta d\phi$$

$$= -\frac{A}{2} \int_{0}^{2\pi} \frac{\cos(2\theta)}{2} \Big|_{0}^{\pi/2} d\phi$$

$$= \frac{A}{2} \int_{0}^{2\pi} d\phi$$

$$= A\pi$$

$$= 1$$

i.e. $A = 1/\pi$. Using this, we may rewrite the PDF as

$$p_{\theta,\phi}(\theta,\phi) = \frac{\cos\theta\sin\theta}{\pi} = \frac{\sin(2\theta)}{2\pi}$$

The individual PDFs are

$$p_{\theta}(\theta) = \int_0^{2\pi} \frac{\sin(2\theta)}{2\pi} d\phi = \sin(2\theta)$$
$$p_{\phi}(\phi) = \int_0^{\pi/2} \frac{\sin(2\theta)}{2\pi} d\theta = -\frac{\cos(2\theta)}{4\pi} \Big|_0^{\pi/2} = \frac{1}{2\pi}$$

and their respective CDFs are

$$F_{\theta}(\theta) = \int_{0}^{\theta} \sin(2\theta') d\theta' = \frac{1 - \cos(2\theta)}{2}$$
$$F_{\phi}(\phi) = \int_{0}^{\phi} \frac{d\phi'}{2\pi} = \frac{\phi}{2\pi}$$

The inverse CDFs are

$$F_{\theta}^{-1}(u) = \frac{\cos^{-1}(1-2u)}{2} \equiv \theta$$

 $F_{\phi}^{-1}(v) = 2\pi v \equiv \phi$

Before expressing this in Cartesian coordinates, it is useful have the half-angle identities on hand

$$\cos\left(\frac{x}{2}\right) = \pm\sqrt{\frac{1+\cos x}{2}} \qquad \sin\left(\frac{x}{2}\right) = \pm\sqrt{\frac{1-\cos x}{2}}$$

Using the above, we see

$$\cos \theta = \sqrt{1 - u} \qquad \sin \theta = \sqrt{u}$$

where we have chosen the positive square root in each case so as to agree $\cos \theta$ and $\sin \theta$ when $\theta \in [0, \frac{\pi}{2}]$. Altogether this gives us

$$x = \sin \theta \cos \phi = \sqrt{u} \cos(2\pi v)$$
$$y = \sin \theta \sin \phi = \sqrt{u} \sin(2\pi v)$$
$$z = \cos \theta = \sqrt{1 - u}$$

Comparing this to our strategy for randomly sampling the unit disc reveals that this is simply a projection of the former onto the unit hemisphere! Using this sampling method gives a particularly nice form to the integrand in the rendering equation in the case of a Lambertian surface,

$$\rho(\lambda)L_i(\mathbf{x},\hat{\omega}_i,\lambda,t)$$

Lack of Cosine Term in Specular Reflection

Specular reflection requires that the integral term in the rendering equation,

$$\int_{\Omega} f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) L_i(\mathbf{x}, \hat{\omega}_i, \lambda, t) |\hat{\omega}_i \cdot \mathbf{n}| \, d\hat{\omega}_i$$

conserve energy. In this particular case, the we know that $f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) \propto \delta(\mathbf{n} - (\hat{\omega}_i + \hat{\omega}_o)/2)$, and so, to conserve energy, we must have

$$\int_{\Omega} A\delta(\mathbf{n} - (\hat{\omega}_i + \hat{\omega}_o)/2) L_i(\mathbf{x}, \hat{\omega}_i, \lambda, t) |\hat{\omega}_i \cdot \mathbf{n}| \, d\hat{\omega}_i = L_i(\mathbf{x}, 2\mathbf{n} - \hat{\omega}_o, \lambda, t)$$

where A is a normalization constant. We see that the distribution must be

$$f_r(\mathbf{x}, \hat{\omega}_i, \hat{\omega}_o, \lambda, t) = \frac{\delta(\mathbf{n} - (\hat{\omega}_i + \hat{\omega}_o)/2)}{|\hat{\omega}_i \cdot \mathbf{n}|}$$

and hence $|\hat{\omega}_i \cdot \mathbf{n}|$ does not appear in implementations of specular reflection (or indeed any delta function distribution).