

CS 170: Homework #2

Due on January 26, 2026 at 3:10pm

L. Chen and U. Vazirani, Spring 2026

Zachary Brandt

1 The Magical Keys and Locks (Solo Question; 10 points)

In the ancient kingdom of Keylom, there are n magical keys and n enchanted locks, such that each key (and each lock) has a unique size between 1 and n . The unique key of size i opens the unique lock of size i . You cannot directly compare two keys with each other, nor can you compare two locks. The *only* thing you can do is insert any key into any lock and see whether it is too small for the lock's keyhole, too big for it, or if it is a perfect fit.

After a lively lantern festival in the village square, the townsfolk accidentally jumbled all the keys and locks into a single array of $2n$ items, in completely arbitrary order. No one remembers which key matches which lock. Your task is to match each key back to its corresponding lock.

- (a) (5 points) Design a *randomized* algorithm that takes this array of $2n$ items as input and returns an array of n key-lock pairs, each of which is a perfect fit. Explain why your algorithm always outputs the correct answer.
- (b) (5 points) Give an intuitive argument that your algorithm from part (a) usually runs in time $O(n \log n)$. You may make the simplifying assumption that the keys and locks are truly magical, in the sense that if you choose a random key from any set of m keys, you always get the key of median (i.e. $\lfloor m/2 \rfloor$ th largest) size.

2 Maximum Subarray Sum (10 points)

Given an array A of n integers, the maximum subarray sum is the largest sum of any contiguous subarray of A (including the empty subarray). In other words, the maximum subarray sum is:

$$\max_{i \leq j} \sum_{\ell=i}^j A[\ell]$$

For example, the maximum subarray sum of $[-2, 1, -3, 4, -1, 2, 1, -5, 4]$ is 6, the sum of the contiguous subarray $[4, -1, 2, 1]$.

Design an $O(n \log n)$ -time divide-and-conquer algorithm that finds the maximum subarray sum. Briefly explain why your algorithm is correct and justify its running time.

3 Monotone matrices (10 points)

A m -by- n matrix A is *monotone* if $n \geq m$, each row of A has no duplicate entries, and it has the following property: if the minimum of row i is located at column j_i , then $j_1 < j_2 < j_3 \dots j_m$. For example, the following 3-by-6 matrix is monotone (the minimum of each row is bolded), since $j_1 = 1, j_2 = 3, j_3 = 6$:

$$\begin{bmatrix} \mathbf{1} & 3 & 4 & 6 & 5 & 2 \\ 7 & 3 & \mathbf{2} & 5 & 6 & 4 \\ 7 & 9 & 6 & 3 & 10 & \mathbf{0} \end{bmatrix}$$

Give an efficient (i.e., significantly better than $O(mn)$ -time) algorithm that finds the minimum in each row of an m -by- n monotone matrix A .

Bound the running time of your algorithm. Note: you might find it easier to bound the work per level of recursion directly rather than writing a formal recurrence relation.

4 Werewolves (10 points)

You are playing a party game with n other friends, who each play either as a werewolf or a villager. Your friends know who is a werewolf, but all your friends do. But you know that there are more villagers than there are werewolves. And you also know that villagers always tell the truth, while werewolves can either lie or tell the truth.

Your goal is to identify one player who is definitely a villager. Your elementary query is to pair up two people and ask each whether the other is a villager or werewolf. Your algorithm should work regardless of the behavior of the werewolves.

- (a) (5 points) For a given person x , devise an algorithm that returns whether or not x is a villager using $O(n)$ queries.
- (b) (5 points) Show how to find a villager in $O(n \log n)$ queries using a divide-and-conquer algorithm.

5 Shaving Logs or Coding (10 points)

For full credit, you should do **one of the following three** questions. (You may solve the others for fun if you want!)

- (a) Find a $O(n)$ time algorithm for maximum subarray sum (Question 2), if your solution above was slower.
- (b) Find a $O(n)$ query algorithm for werewolves (Question 4), if your solution above was slower.
- (c) Implement the quickselect algorithm in a python jupyter notebook called `quick_select.ipynb`. There are two ways that you can access the notebook and complete the problems:
 - (a) **On Local Machine:** `git clone` (or if you already have it, `git pull`) from the coding homework repo,
`https://github.com/Berkeley-CS170/cs170-sp26-coding`
and navigate to the `hw02` folder. Refer to the `README.md` for local setup instructions.
 - (b) **On Datahub:** Click on `https://github.com/Berkeley-CS170/cs170-sp26-coding` and navigate to the `hw02` folder if you prefer to complete this question on Berkeley DataHub.

Notes:

- *Submission Instructions:* Please run the last cell to download a zip file and submit it to the gradescope assignment titled “HW02 (Coding)”.
- *OH/HWP Instructions:* Designated coding course staff will provide conceptual and debugging help during office hours.
- *Academic Honesty Guideline:* We realize that code for some of the algorithms we ask you to implement may be readily available online, but we strongly encourage you to not directly copy code from these sources. Instead, try to refer to the resources mentioned in the notebook and come up with code yourself. That being said, we **do acknowledge** that there may not be many different ways to code up particular algorithms and that your solution may be similar to other solutions available online.