

CSC 665: Midterm

Chicheng Zhang

October 17, 2019

Please complete the following set of problems. You must do the exercises completely on your own (no collaboration allowed this time). The exam is due **on Oct 24, 12:30pm, on Gradescope**. You are free to cite existing theorems from the textbooks and course notes.

Problem 1

Define $\mathcal{H} = \{\text{sign}(p(x)) : p \text{ is a polynomial of } x \text{ of degree } \leq n\}$ (where $x \in \mathbb{R}$). What is the VC dimension of \mathcal{H} ?

Problem 2

Suppose we have an algorithm \mathcal{B} that learns hypothesis class \mathcal{H} in the following sense. There exists a function $m(\epsilon)$, such that for any $\epsilon > 0$, suppose \mathcal{B} draws $m \geq m(\epsilon)$ training examples from a distribution D realizable by \mathcal{H} , then with probability $\geq \frac{1}{2}$, \mathcal{B} returns a classifier \hat{h} with error at most ϵ on D .

Now, given \mathcal{B} and the ability of drawing fresh training examples, how can you design an algorithm \mathcal{A} that (ϵ, δ) -PAC learns \mathcal{H} for any ϵ, δ ? What is its sample complexity? (You may want to run \mathcal{B} multiple times.)

Problem 3

Suppose X_1, \dots, X_n is a sequence of n iid random variables, and let $\sigma^2 = \text{var}(X_i)$ and $\mu = \mathbb{E}(X_i)$. Suppose $n = mk$ for some integer m and odd integer $k \geq 20 \ln \frac{1}{\delta}$. Denote by

$$\hat{\mu} = \text{median}(\hat{\mu}_1, \dots, \hat{\mu}_k),$$

where $\hat{\mu}_i = \frac{1}{m} \sum_{j=(i-1)m+1}^{im} X_j$.

1. Show that for every j ,

$$\mathbb{P}(|\hat{\mu}_j - \mu| \leq \frac{2\sigma}{\sqrt{m}}) \geq \frac{3}{4}.$$

2. Show that

$$\mathbb{P}(|\hat{\mu} - \mu| \leq \frac{2\sigma}{\sqrt{m}}) \geq 1 - \delta.$$