

CS 245: Database System Principles

Notes 10: More TP

Hector Garcia-Molina

CS 245

Notes 10

1

Sections to Skim:

- Chapter 8: none (read all sections)
- Chapter 9:
 - skim 9.8
- Chapter 10:
 - skim 10.4, 10.5, 10.6, 10.7
 - maybe 10.2 (decide later...)
- Chapter 11: none (read all sections)

CS 245

Notes 10

2

Chapter 10 More on transaction processing

Topics:

- Cascading rollback, recoverable schedule
- Deadlocks
 - Prevention
 - Detection
- View serializability
- Distributed transactions
- Long transactions (nested, compensation)


CS 245

Notes 10

3

Concurrency control & recovery

Example:



☛ Non-Persistent Commit (Bad!)

CS 245

Notes 10

4

Concurrency control & recovery

Example:



☛ Non-Persistent Commit (Bad!) avoided by recoverable schedules


CS 245

Notes 10

5

Concurrency control & recovery

Example:



☛ Cascading rollback (Bad!)


CS 245

Notes 10

6

Concurrency control & recovery

Example:



☛ Cascading rollback (Bad!)

CS 245

Notes 10

7

- Schedule is conflict serializable
- $T_j \longrightarrow T_i$
- But not recoverable

CS 245

Notes 10

8

- Need to make "final" decision for each transaction:
 - **commit decision** - system guarantees transaction will or has completed, no matter what
 - **abort decision** - system guarantees transaction will or has been rolled back (has no effect)

CS 245

Notes 10

9

To model this, two new actions:


- C_i - transaction T_i commits
- A_i - transaction T_i aborts

CS 245

Notes 10

10

Back to example:



CS 245

Notes 10

11

Definition

T_i reads from T_j in S ($T_j \Rightarrow_S T_i$) if

- (1) $w_j(A) <_S r_i(A)$
- (2) $a_j \not<_S r_i(A)$ ($\not<$: does not precede)
- (3) If $w_j(A) <_S w_k(A) <_S r_i(A)$ then $a_k <_S r_i(A)$

CS 245

Notes 10

12

Definition

Schedule S is recoverable if
whenever $T_j \Rightarrow_s T_i$ and $j \neq i$ and $C_i \in S$
then $C_j <_s C_i$

CS 245

Notes 10

13

Note: in transactions, reads and writes
precede commit or abort

- \Rightarrow If $C_i \in T_i$, then $r_i(A) < C_i$
 $w_i(A) < C_i$
- \Rightarrow If $A_i \in T_i$, then $r_i(A) < A_i$
 $w_i(A) < A_i$

- Also, one of C_i, A_i per transaction

CS 245

Notes 10

14

How to achieve recoverable schedules?

CS 245

Notes 10

15

\Rightarrow With 2PL, hold write locks to
commit (strict 2PL)

<u>T_j</u>	<u>T_i</u>
\vdots	\vdots
$w_j(A)$	\vdots
\vdots	\vdots
C_j	\vdots
$u_j(A)$	\vdots
\vdots	$r_i(A)$

CS 245

Notes 10

16

\Rightarrow With validation, no change!

CS 245

Notes 10

17


- S is recoverable if each transaction *commits* only after all transactions from which it read have committed.
- S avoids cascading rollback if each transaction may *read* only those values written by committed transactions.

CS 245

Notes 10

18

- S is strict if each transaction may *read and write* only items previously written by committed transactions.




CS 245

Notes 10

19

Where are serializable schedules?



CS 245

Notes 10

20

Examples

- Recoverable:
 - $w_1(A) \ w_1(B) \ w_2(A) \ r_2(B) \ c_1 \ c_2$
- Avoids Cascading Rollback:
 - $w_1(A) \ w_1(B) \ w_2(A) \ c_1 \ r_2(B) \ c_2$
- Strict:
 - $w_1(A) \ w_1(B) \ c_1 \ w_2(A) \ r_2(B) \ c_2$

Assumes $w_2(A)$ is done without reading

CS 245

Notes 10

21

Deadlocks

- Detection
 - Wait-for graph
- Prevention
 - Resource ordering
 - Timeout
 - Wait-die
 - Wound-wait


CS 245

Notes 10

22

Deadlock Detection

- Build Wait-For graph
- Use lock table structures
- Build incrementally or periodically
- When cycle found, rollback victim



CS 245

Notes 10

23

Resource Ordering

- Order all elements A_1, A_2, \dots, A_n
- A transaction T can lock A_i after A_j only if $i > j$

Problem : Ordered lock requests not realistic in most cases

CS 245

Notes 10

24

Timeout

- If transaction waits more than L sec., roll it back!
- Simple scheme
- Hard to select L

CS 245

Notes 10

25

Wait-die


- Transactions given a timestamp when they arrive $ts(T_i)$
- T_i can only wait for T_j if $ts(T_i) < ts(T_j)$...else die

CS 245

Notes 10

26

Example:



CS 245

Notes 10

27

Starvation with Wait-Die

- When transaction dies, re-try later with what timestamp?
 - original timestamp
 - new timestamp (time of re-submit)

CS 245

Notes 10

28

Starvation with Wait-Die


- Resubmit with original timestamp
- Guarantees no starvation
 - Transaction with oldest ts never dies
 - A transaction that dies will eventually have oldest ts and will complete...

CS 245

Notes 10

29

Second Example:




CS 245

Notes 10

30

Second Example (continued):

One option: T_1 waits just for T_3 , transaction holding lock. But when T_2 gets lock, T_1 will have to die!




CS 245

Notes 10

31

Second Example (continued):

Another option: T_1 only gets A lock after T_2, T_3 complete, so T_1 waits for both $T_2, T_3 \Rightarrow T_1$ dies right away!




CS 245

Notes 10

32

Second Example (continued):

Yet another option: T_1 preempts T_2 , so T_1 only waits for T_3 ; T_2 then waits for T_3 and $T_1 \dots \Rightarrow T_2$ may starve?



CS 245

Notes 10

33

Wound-wait

- Transactions given a timestamp when they arrive ... $ts(T_i)$
- T_i wounds T_j if $ts(T_i) < ts(T_j)$
else T_i waits


"Wound": T_j rolls back and gives lock to T_i

CS 245

Notes 10

34

Example:



CS 245

Notes 10

35

Starvation with Wound-Wait


- When transaction dies, re-try later with what timestamp?
 - original timestamp
 - new timestamp (time of re-submit)

CS 245

Notes 10

36

Second Example:




CS 245

Notes 10

37

Second Example (continued):

One option: T₁ waits just for T₃, transaction holding lock. But when T₂ gets lock, T₁ waits for T₂ and wounds T₂.




CS 245

Notes 10

38

Second Example (continued):

Another option: T₁ only gets A lock after T₂, T₃ complete, so T₁ waits for both T₂, T₃ ⇒ T₂ wounded right away!




CS 245

Notes 10

39

Second Example (continued):

Yet another option: T₁ preempts T₂, so T₁ only waits for T₃; T₂ then waits for T₃ and T₁... ⇒ T₂ is spared!



CS 245

Notes 10

40

User/Program commands

Lots of variations, but in general

- Begin_work
- Commit_work
- Abort_work

CS 245

Notes 10

41

Nested transactions

User program:

```

:
Begin_work;
:
:
If results_ok, then commit work
else abort_work
    
```

CS 245

Notes 10

42

Nested transactions

User program:

```

:
Begin_work;
  Begin_work;
  :
  If results_ok, then commit work
  else {abort_work; try something else...}
:
If results_ok, then commit work
else abort_work
  
```

CS 245


Notes 10

43

Parallel Nested Transactions

```

T1: begin_work
:
parallel:
  T11: begin_work
  :
  commit_work
  T12: begin_work
  :
  commit_work
:
commit_work
  
```



CS 245

Notes 10

44

Locking

Locking

What are we really locking?



CS 245

Notes 10

45

Example:

```

Ti    :
      Read record r1
      :
      Read record r1
      :
      Modify record r3
      :
  
```


do record locking

CS 245

Notes 10

46

But underneath:



CS 245

Notes 10

47

Solution: view DB at two levels

Top level: record actions
 record locks
 undo/redo actions — logical

e.g., Insert record(X,Y,Z)
 Redo: insert(X,Y,Z)
 Undo: delete

CS 245

Notes 10

48


Low level: deal with physical details
latch page during action
 (release at end of action)

CS 245

Notes 10

49

Note: undo does not return physical DB
 to original state; only same logical state



CS 245

Notes 10

50

Logging Logical Actions

- Logical action typically span one block (physiological actions)
- Undo/redo log entry specifies undo/redo logical action
- Challenge: making actions idempotent
 - Example (bad): redo insert \Rightarrow key inserted multiple times!

CS 245


Notes 10

51

Solution: Add Log Sequence Number

Log record:

- LSN=26
- OP=insert(5,v2) into P
- ...




CS 245

Notes 10

52

Still Have a Problem!



CS 245

Notes 10

53

Compensation Log Records

- Log record to indicate undo (not redo) action performed
- Note: Compensation may not return page to exactly the initial state

CS 245

Notes 10

54

At Recovery: Example

Log:

...	lsn=21 T1 a1 p1	...	lsn=27 T1 a2 p2	...	lsn=35 T1 a2 ⁻¹ p2	...
-----	--------------------------	-----	--------------------------	-----	--	-----

CS 245

Notes 10

55

What to do with p2 (during T1 rollback)?

- If $lsn(p2) < 27$ then ... ?
- If $27 \leq lsn(p2) < 35$ then ... ?
- If $lsn(p2) \geq 35$ then ... ?

Note: $lsn(p2)$ is lsn of p copy on disk

CS 245

Notes 10

56

Recovery Strategy

[1] Reconstruct state at time of crash

- Find latest valid checkpoint, ck , and let ac be its set of active transactions
- Scan log from ck to end:
 - For each log entry $[lsn, page]$ do:
 - if $lsn(page) < lsn$ then redo action
 - If log entry is start or commit, update ac

CS 245

Notes 10

57

Recovery Strategy

[2] Abort uncommitted transactions

- Set ac contains transactions to abort
- Scan log from end to ck :
 - For each log entry (not undo) of an ac transaction, undo action (making log entry)
- For ac transactions not fully aborted, read their log entries older than ck and undo their actions

CS 245

Notes 10

58

Example: What To Do After Crash

Log:

chk pt	...	lsn=21 T1 a1 p1	...	lsn=27 T1 a2 p2	...	lsn=29 T1 a3 p3	...	lsn=31 T1 a3 ⁻¹ p3	...	lsn=35 T1 a2 ⁻¹ p2	...
-----------	-----	--------------------------	-----	--------------------------	-----	--------------------------	-----	--	-----	--	-----


CS 245

Notes 10

59

During Undo: Skip Undo's

Log:



CS 245

Notes 10

60

Related idea: Sagas

- Long running activity: T_1, T_2, \dots, T_n
- Each step/transaction T_i has a compensating transaction T_i^{-1}
- Semantic atomicity: execute one of
 - T_1, T_2, \dots, T_n
 - $T_1, T_2, \dots, T_{n-1}, T_{n-1}^{-1}, T_{n-2}^{-1}, \dots, T_1^{-1}$
 - $T_1, T_2, \dots, T_{n-2}, T_{n-2}^{-1}, T_{n-3}^{-1}, \dots, T_1^{-1}$
 - \vdots
 - T_1, T_1^{-1}
 - nothing

CS 245

Notes 10

61

Summary

- Cascading rollback
Recoverable schedule
- Deadlock
 - Prevention
 - Detectoin
- Nested transactions
- Multi-level view

CS 245

Notes 10

62