

Selenium2Library关键字 (2) 原创

Press Key	xpath=//*[@id='appBody']/div/div \\13	#键盘enter建
-----------	---------------------------------------	-----------

Press Keys

注意：press keys发送字符串的时候不能自动清除之前的值，会自动拼接在之前的字符串后面

new in Selenium2Library 3.3

Examples:

`Press Keys`	text_field	AAAAA		# Sends string "AAAAA" to element.
`Press Keys`	None	BBBBB		# Sends string "BBBBB" to currently active browser.
`Press Keys`	text_field	E+N+D		# Sends string "END" to element.
`Press Keys`	text_field	XXX	YY	# Sends strings "XXX" and "YY" to element.
`Press Keys`	text_field	XXX+YY		# Same as above.
`Press Keys`	text_field	ALT+ARROW_DOWN		# Pressing "ALT" key down, then pressing ARROW_DOWN and then releasing both keys.
`Press Keys`	text_field	ALT	ARROW_DOWN	# Pressing "ALT" key and then pressing ARROW_DOWN.
`Press Keys`	text_field	CTRL+c		# Pressing CTRL key down, sends string "c" and then releases CTRL key.
`Press Keys`	button	RETURN		# Pressing "ENTER" key to element.

<http://blog.ssdn.net/cicoulife>

双击元素

5	Double Click Element	locator 双击元素
6		

在一个输入框中输入编号1，然后使用press keys 点击enter按键，注意：press keys后要跟element 定位和enter表示字符RETURN

Input Text	fileNo	1
Press Keys	fileNo	RETURN

Select Frame 选择frame 参数是定位frame 【selenium2Library】

2	Select Frame	xpath=//*[@hidefocus="true"]	
3	Unselect Frame		
	Title Should Be	公共智能调度信息管理系统	
2	Open Browser	\${LOGIN_URL}	\${BROW
3	Maximize Browser Window	最大窗口	
	Maximize browser window		
	Set Selenium Speed	\${DELAY}	

Wait Until Page Contains Element

4	Wait Until Page Contains Element	side-menu id	8s
---	----------------------------------	--------------	----

Wait Until Page Contains 参数是text内容

8	Wait Until Page Contains	\${check_info} 文本内容	
9			

转变一个观念就是，想用if的时候，要想到 run keyword if

6	Sleep	0.5s	run keyword if和unless用法类似
7	Run Keyword Unless	'\${third_menu}'='\${EMPTY}'	Click Element
			xpath=//ul[@id="side-menu"]/li[\${

执行js脚本【竖向滚动条滚动】

1	Execute Javascript	document.getElementById("\${locator}").scrollTop = 500	竖直滚动条向下滚
---	--------------------	--------------------------------------------------------	----------

对于那种只读的输入框，可以先去除他的readonly的属性，在input

text写入文本

Execute Javascript	document.getElementById("startTime").removeAttribute("readonly")	
Input Text	startTime	2019-08-28 15:14:04
clean	***	

js处理iframe

Js处理iframe无需先切换到iframe上，再切回来操作。它可以在iframe上和主页面上来回自由操作——这是Js的强大之处

js = document.getElementById("Editor_Edit_EditorBody_ifr").contentWindow.document.body.innerHTML="%s" % jstext

driver.execute_script(js)

window对象

使用iframe窗口对象操作iframe的内容