TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

AFG 8012 is a Polyethylene (PE) based Antifog masterbatch. It is specially designed for LDPE, LLDPE, HDPE, PP and EVA for use in Injection molding, Blow moulding, Extrusion sheet and film packaging application, requiring excellent dispersion and Antifog properties. It prevents the formation of water droplet on the surface of the film and suitable for cold and hot fog packaging application.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 4% to 8% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	AFG 8012
Carrier Polymer	LLDPE
Appearance	Cylindrical Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	NOT APPLICABLE
Heat Stability	°C	--	260°C
Migration	--	--	NOT APPLICABLE
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.60 ± 0.1
Melt Flow Index at 1900C, 2.16 Kg	Gm/10 min	ASTM D1238	1 TO 10
Specific Gravity	-	ASTM D792	0.93 ± 0.1
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Active Content	%	--	12 ± 0.5
Pellet Count	No's/1 Gm	--	55 - 65
Pellet Size	mm	--	2.5 - 3.5

Regulatory

This product is food compliant as per 21 CFR US FDA 177.1520 and 170.30 and EU 72/2002/EC.

Packaging & Storage

Antifog Masterbatch AFG-8012 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry & moisture free place at room temperature. Recommended storage life is Six month provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.