TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

BLACK 08 FF is a Polyethylene (PE) based Black masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically, addition rates vary up to 10% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	BLACK 08 FF
Colour	Black
Carrier Polymer	PE
Appearance	Cylindrical Black Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	7 - 8
Heat Stability	°C	--	280°C
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.90 ± 0.1
Toxicity	--	--	NON-TOXIC
Melt Flow Index at 1900C, 10 Kg	Gm/10 min	ASTM D1238	2 - 6
Specific Gravity	--	ASTM D792	1.50 ± 0.1
Dispersion	--	--	EXCELLENT
Ash Content	%	ASTM D5630	65 ± 3

Regulatory

The product is not food compliant. It passes heavy metal limits and hence complies with RoHS directive 2015/863/EU.

Packaging & Storage

Black Masterbatch BLACK 08 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry and moisture free place. Recommended storage life is 2 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.