TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

BLACK 93 FF is a Polypropylene (PP) based black masterbatch. It is specially designed for PP in fibers, filament, Injection Molding, Extrusion and Blow Molding application, requiring excellent dispersion.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary up to 10% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	BLACK 93 FF
Colour	Black
Carrier Polymer	PP
Appearance	Cylindrical Black Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	7 - 8
Heat Stability	°C	--	280°C
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.73 ± 0.1
Melt Flow Index at 2300C, 10.0 Kg	Gm/10 min	ASTM D1238	15 ± 5
Specific Gravity	-	ASTM D792	1.06 ± 0.1
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Carbon Black Content	%	ASTM D1603	40 ± 2
Pellet Count	No'S/1 Gm	--	40 - 60
Pellet Size	mm	--	2.5 – 3.5

Regulatory

The product is food compliance as per European Standard EU AP 89(1).

Packaging & Storage

Black Masterbatch BLACK 93 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 2 years provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.