# TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

## Product Description

PPA 249 is a Polyethylene (PE) based Processing Aid masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Extrusion application, requiring excellent dispersion. It reduces die build up and eliminates melt fractures. It can reduce extruder torque and produce film of improved strength and quality.

## Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 1% to 4% masterbatch.

## Masterbatch Information

| Parameter | Value |
|---|---|
| **Product Code** | PPA 249 |
| **Colour** | NATURAL |
| **Carrier Polymer** | PE |
| **Appearance** | Cylindrical Natural Granules |

## Physical Properties

| Properties | Unit | Test Method | Specification |
|---|---|---|---|
| **Light Fastness** | -- | -- | NA |
| **Heat Stability** | °C | -- | 260°C |
| **Moisture Content(Temp120°C, 10Min.)** | % | ASTM D6980 | < 0.20 |
| **Bulk Density** | Gm/cc | ASTM D1895 | 0.60 ± 0.1 |
| **Melt Flow Index At 1900C, 2.16 Kg** | Gm/10 min | ASTM D1238 | 1 TO 10 |
| **Specific Gravity** | - | ASTM D792 | 0.90 ± 0.1 |
| **Typical Active Content** | % | -- | 5 |
| **Toxicity** | -- | -- | NON-TOXIC |
| **Dispersion** | -- | -- | EXCELLENT |

## Regulatory

The product is food compliant as per EU 10/2011. It passes heavy metal limits and hence complies with RoHS directive 2015/863/EU.

## Packaging & Storage

PPA 249 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.