TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

WHITE 356 FF is a Polyethylene (PE) based White masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 8% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	WHITE 356 FF
Colour	White
Carrier Polymer	PE
Appearance	Cylindrical White Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	7 - 8
Heat Stability	°C	--	280°C
Migration	--	--	4 - 5
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	1.40 ± 0.1
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Filler Content	%	ASTM D5630	12 ± 2
TiO2 Content	%	ASTM D5630	70 ± 1

Regulatory

The product is food compliance as per 21 CFR US FDA 177.1520 AND 178.3297, EU AP 89(1) and Indian standard IS 9833:2018.

Packaging & Storage

White Masterbatch WHITE 356 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.