TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

DESICCANT 1204 is a Polyethylene (PE) based Desiccant masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion and moisture removal properties.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 8% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	DESICCANT 1204
Carrier Polymer	PE
Appearance	Cylindrical Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	NOT APPLICABLE
Heat Stability	°C	--	300°C
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	--	ASTM D792	1.20 ± 0.1
Melt flow Index at 190°C/2.16 kg	Gm/ 10Min.	ASTM D1238	NO FLOW
Specific Gravity	--	ASTM D792	1.65 ± 0.1
Ash Content	%	ASTM D5630	75 ± 2
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT

Regulatory

The product is food compliant.It passes heavy metal limits and hence complies with RoHS directive 2002/95/EC.

Packaging & Storage

Desiccant Masterbatch DESICCANT 1204 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.