TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

SAB 1907 is a Polyethylene (PE) based Slip-Antiblock masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Extrusion application, requiring excellent dispersion and Slip- Antiblock properties.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 4% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	SAB 1907
Carrier Polymer	PE
Appearance	Cylindrical Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	NOT APLLICABLE
Heat Stability	°C	--	280°C
Migration	--	--	NOT APLLICABLE
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.60 ± 0.1
Melt Flow Index at 1900C, 2.16 Kg	Gm/10 min	ASTM D1238	NO FLOW
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Active Content	%	--	25 ± 1

Regulatory

This product is food compliance as per EU AP 89(1).

Packaging & Storage

Slip-Antiblock Masterbatch SAB 1907 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.