TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

WHITE 71 FE is a Polyethylene (PE) based White Masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion and opacity.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. For Injection and Blow molding applications - Typical addition rates up to 8% For Extrusion Film and sheet applications - Typical addition rates up to 15%

Masterbatch Information

Parameter	Value
Product Code	WHITE 71 FE
Colour	White
Carrier Polymer	PE
Appearance	Cylindrical White Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	7 - 8
Heat Stability	°C	--	280°C
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	1.3 - 1.5
Melt Flow Index at 1900C, 2.16 Kg	Gm/10 min	ASTM D1238	5 - 15
Specific Gravity	--	ASTM D792	1.98 ± 0.1
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Pellet Count	No'S/1 Gm	--	25 - 45
Pellet Size	mm	--	2.5 - 3.5
Ash Content	%	ASTM D5630	78 ± 2

Regulatory

The product is food compliance as per EU AP 89(1) and EU 10/2011.

Packaging & Storage

White Masterbatch WHITE 71 FE is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 2 years provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.