



TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

AB 222 is a Polyethylene (PE) based Antiblock masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Extrusion (films and sheets) application, requiring excellent dispersion and anti-block properties. It reduces coefficient of friction between layers of film.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 6% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	AB 222
Carrier Polymer	PE
Appearance	Cylindrical Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	NA
Heat Stability	°C	--	280°C
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.60 ± 0.1
Melt Flow Index At 1900C, 2.16 Kg	Gm/10 min	ASTM D1238	35 ± 10
Specific Gravity	-	ASTM D792	1.00 ± 0.1
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Typical Active Content	%	--	20

Regulatory

The product is food compliance as per European directive AP 89(1) and EU 10/2011.

Packaging & Storage



Antiblock Masterbatch AB 222 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.