



TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

AST 335 is a Polystyrene (PS) based Additive masterbatch. It is designed for GPPS and HIPS in Injection molding and Extrusion sheets application, requiring excellent dispersion and antistatic properties.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically, addition rates vary from 2% to 4% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	AST 335
Colour	Off White
Carrier Polymer	PS
Appearance	Cylindrical Off White Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	NA
Heat Stability	°C	--	260°C
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.80 ± 0.1
Melt Flow Index at 2000C, 5 Kg	Gm/10 min	ASTM D1238	100 ± 40
Specific gravity	--	ASTM D792	1.22 ± 0.1
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Typical Active Content	%	--	7.5
Ash Content	%	ASTM D5630	27 ± 2

Regulatory

The product is food compliance as per EU 10/2011 and Indian standard IS 9833:2018.



Packaging & Storage

Additive Masterbatch AST 335 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.