



TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

BLACK 210 FF is a Polypropylene (PP) based black masterbatch. It is specially designed for PP in fibers, filament, Injection Molding, Extrusion and Blow Molding application, requiring excellent dispersion.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 6% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	BLACK 210 FF
Colour	Black
Carrier Polymer	PP
Appearance	Cylindrical Black Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	7 - 8
Heat Stability	°C	--	280°C
Migration	--	--	4 - 5
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.68 ± 0.1
Melt Flow Index At 2300C, 5.0 Kg	Gm/10 min	ASTM D1238	50 ± 10
Specific Gravity	-	ASTM D792	0.98 ± 0.1
Toxicity	--	--	Non-Toxic
Dispersion	--	--	EXCELLENT
Carbon Black Content	%	ASTM D5630	35 ± 1
Pellet Count	No'S/1 Gm	--	40 - 60
Pellet Size	mm	--	2.5 – 3.5

Regulatory



The product is RoHS compliance as per European Standard.

Packaging & Storage

Black Masterbatch BLACK 210 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 1 year provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.