



TECHNICAL DATA SHEET

Distributed by Blau Batch | Manufactured by Coraplast Industries

Product Description

BLACK 31 FF is a Polyethylene (PE) based Black masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 8% masterbatch.

Masterbatch Information

Parameter	Value
Product Code	BLACK 31 FF
Colour	BLACK
Carrier Polymer	PE
Appearance	Cylindrical Black Granules

Physical Properties

Properties	Unit	Test Method	Specification
Light Fastness	--	--	7 - 8
Heat Stability	°C	--	280°C
Migration	--	--	4 - 5
Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
Bulk Density	Gm/cc	ASTM D1895	0.80 ± 0.1
Toxicity	--	--	NON-TOXIC
Dispersion	--	--	EXCELLENT
Carbon Content	%	ASTM D1603	60 ± 1

Regulatory

The product passes heavy metal limits and hence complies with RoHS directive 2002/95/EC.

Packaging & Storage



Black Masterbatch BLACK 31 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place. Recommended storage life is 3 years provided it is stored as directed.

Note: Above report is made in identical condition. Values may be different when processed on different machines and/or different processing conditions, hence cannot be compared with any other same colour or product.