

## **TECHNICAL DATA SHEET**

### **Product Description**

AB 222 is a Polyethylene (PE) based Antiblock masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Extrusion (films and sheets) application, requiring excellent dispersion and anti-block properties. It reduces coefficient of friction between layers of film.

### **Addition Level**

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 6% masterbatch.

### **Masterbatch Information**

1. Product Code AB 222
2. Colour Off-White
3. Carrier Polymer PE
4. Appearance Cylindrical Off-White Granules

### **Physical Properties:**

| Properties                               | Unit      | Test Method | Specification |
|------------------------------------------|-----------|-------------|---------------|
| 1. Light Fastness                        | --        | --          | NA            |
| 2. Heat Stability                        | °C        | --          | 280°C         |
| 3. Moisture Content (Temp 120°C, 10Min.) | %         | ASTM D6980  | < 0.20        |
| 4. Bulk Density                          | Gm/cc     | ASTM D1895  | 0.60 ± 0.1    |
| 5. Melt Flow Index At 190°C, 2.16 Kg     | Gm/10 min | ASTM D1238  | 35 ± 10       |
| 6. Specific Gravity                      | -         | ASTM D792   | 1.00 ± 0.1    |
| 7. Toxicity                              | --        | --          | NON-TOXIC     |
| 8. Dispersion                            | --        | --          | EXCELLENT     |
| 9. Typical Active Content                | %         | --          | 20            |

### **Regulatory**

The product is food compliance as per European directive AP 89(1) and EU 10/2011.

### **Packaging & Storage**

Antiblock Masterbatch AB 222 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 1 year provided it is stored as directed.

Note: Above Report is made in identical condition. Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

**TECHNICAL SERVICES**

**Coraplast Industries**

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India  
T +91 98980 18180 E info@coraplast.com W coraplast.com