

TECHNICAL DATA SHEET

Product Description

AST 335 is a Polystyrene (PS) based Additive masterbatch. It is designed for GPPS and HIPS in Injection molding and Extrusion sheets application, requiring excellent dispersion and antistatic properties.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically, addition rates vary from 2% to 4% masterbatch.

Masterbatch Information

1. Product Code AST 335
2. Colour Off White
3. Carrier Polymer PS
4. Appearance Cylindrical Off White Granules

Physical Properties:

Properties	Unit	Test Method	Specification
1. Light Fastness	--	--	NA
2. Heat Stability	°C	--	260°C
3. Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
4. Bulk Density	Gm/cc	ASTM D1895	0.80 ± 0.1
5. Melt Flow Index at 200°C, 5 Kg	Gm/10 min	ASTM D1238	100 ± 40
6. Specific gravity	--	ASTM D792	1.22 ± 0.1
7. Toxicity	--	--	NON-TOXIC
8. Dispersion	--	--	EXCELLENT
9. Typical Active Content	%	--	7.5
10. Ash Content	%	ASTM D5630	27 ± 2

Regulatory

The product is food compliance as per EU 10/2011 and Indian standard IS 9833:2018.

Packaging & Storage

Additive Masterbatch AST 335 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 1 year provided it is stored as directed.

Note: Above Report is made in identical condition. Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

TECHNICAL SERVICES

Coraplast Industries

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India
T +91 98980 18180 E info@coraplast.com W coraplast.com