

TECHNICAL DATA SHEET

Product Description

AST 347 is a Polystyrene (PS) based Antistatic masterbatch. It is specially designed for GPPS, HIPS and other styrene based polymer in Extrusion (films and sheets) and Injection molding application, requiring excellent anti-static properties and prevents dust build up during processing.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary from 2% to 4% masterbatch.

Masterbatch Information

1. Product Code AST 347
2. Colour Natural
3. Carrier Polymer PS
4. Appearance Cylindrical Natural Granules

Physical Properties:

Properties	Unit	Test Method	Specification
1.Light Fastness	--	--	NA
2.Heat Stability	°C	--	260°C
3.Migration	--	--	NA
4.Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
5.Bulk Density	-	ASTM D1895	1.0 ± 0.1
6.Toxicity	--	--	NON-TOXIC
7.Dispersion	--	--	EXCELLENT
8.Ash Content	%	ASTM D5630	60 ± 2
9.Active Content	%	--	5 ± 0.5

Regulatory

This product is food compliant. It passes heavy metal limits and hence complies with RoHS directive 2002/95/EC.

Packaging & Storage

Antistatic Masterbatch AST 347 is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 1 year provided it is stored as directed.

Note: Above Report is made in identical condition, Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

TECHNICAL SERVICES

Coraplast Industries

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India
T +91 98980 18180 E info@coraplast.com W coraplast.com