

## TECHNICAL DATA SHEET

### Product Description

BLACK 15 FF is a Polyethylene (PE) based Black masterbatch. It is specially designed for LDPE, LLDPE, HDPE and PP in Injection molding, Extrusion and Blow molding application, requiring excellent dispersion.

### Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary up to 10% masterbatch.

### Masterbatch Information

1. Product Code           BLACK 15 FF
2. Colour                   BLACK
3. Carrier Polymer       PE
4. Appearance           Cylindrical Black Granules

### Physical Properties:

| Properties                               | Unit      | Test Method | Specification |
|------------------------------------------|-----------|-------------|---------------|
| 1. Light Fastness                        | --        | --          | 7 - 8         |
| 2. Heat Stability                        | °C        | --          | 280°C         |
| 3. Moisture Content (Temp 120°C, 10Min.) | %         | ASTM D6980  | < 0.20        |
| 4. Bulk Density                          | Gm/cc     | ASTM D1895  | 0.75 ± 0.1    |
| 5. Melt Flow Index at 190°C, 10 Kg       | Gm/10 min | ASTM D1238  | 15 ± 5        |
| 6. Specific Gravity                      | -         | ASTM D792   | 1.23 ± 0.1    |
| 7. Toxicity                              | --        | --          | NON-TOXIC     |
| 8. Dispersion                            | --        | --          | EXCELLENT     |
| 9. Ash Content                           | %         | ASTM D5630  | 50 ± 2        |

### Regulatory

The product is not food compliant. It passes heavy metal limits and hence complies with RoHS directive 2002/95/EC.

### Packaging & Storage

Black Masterbatch BLACK 15 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 3 years provided it is stored as directed.

Note: Above Report is made in identical condition, Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

**TECHNICAL SERVICES**

**Coraplast Industries**

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India  
T +91 98980 18180 E info@coraplast.com W coraplast.com