

TECHNICAL DATA SHEET

Product Description

BLACK 93 FF is a Polypropylene (PP) based black masterbatch. It is specially designed for PP in fibers, filament, Injection Molding, Extrusion and Blow Molding application, requiring excellent dispersion.

Addition Level

The addition level of masterbatch added depends on the performance requirements of the final application. Typically addition rates vary up to 10% masterbatch.

Masterbatch Information

1. Product Code BLACK 93 FF
2. Colour Black
3. Carrier Polymer PP
4. Appearance Cylindrical Black Granules

Physical Properties:

Properties	Unit	Test Method	Specification
1. Light Fastness	--	--	7 - 8
2. Heat Stability	°C	--	280°C
3. Moisture Content (Temp120°C, 10Min.)	%	ASTM D6980	< 0.20
4. Bulk Density	Gm/cc	ASTM D1895	0.73 ± 0.1
5. Melt Flow Index at 230°C, 10.0 Kg	Gm/10 min	ASTM D1238	15 ± 5
6. Specific Gravity	-	ASTM D792	1.06 ± 0.1
7. Toxicity	--	--	NON-TOXIC
8. Dispersion	--	--	EXCELLENT
9. Carbon Black Content	%	ASTM D1603	40 ± 2
10. Pellet Count	No'S/1 Gm	--	40 - 60
11. Pellet Size	mm	--	2.5 – 3.5

Regulatory

The product is food compliance as per European Standard EU AP 89(1).

Packaging & Storage

Black Masterbatch BLACK 93 FF is supplied in regular pellet form packed in 25 kg bags. It should be stored in dry place.

Recommended storage life is 2 years provided it is stored as directed.

Note: Above Report is made in identical condition, Values may be different when process on different machines and/or different processing condition, hence cannot be compare with any other same colour or product.

TECHNICAL SERVICES

Coraplast Industries

Survey No:180, Udvada Pariya Road, Village Dungri, Tal. Pardi, Dist. Valsad, Gujarat - 396185 India
T +91 98980 18180 E info@coraplast.com W coraplast.com